



Above Ground Tanks - small-medium range - slimline

Vertical - Baffled - Rectangular - 400-1000 Litres *All Applications including WRAS*

Volume (Litres)	Volume (Gallons)	Shape	Length (mm)	Height (mm)	Depth (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	SKU
400	88	Rectangle	1,200	1,050	400	1.5"	1	255mm VENTED	35	BLACK	PS-171504
800	176		1,350	1,200	600	1.5"	1	255mm VENTED	55	BLACK	PS-171508
1,000	220		1,650	1,200	600	1.5"	1	255mm VENTED	70	BLACK	PS-171510



Vertical use, rectangular, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with a single, vented lid and multiple slots for securing with ratchet/cargo straps and/or a metal frame, this tank has moulded-in baffles to prevent sloshing and increase stability when on the move.

Multiple applications: potable drinking water, rainwater harvesting, liquid transport, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.

Flat - Baffled - Rectangular - 400-1000 Litres *All Applications including WRAS*

Volume (Litres)	Volume (Gallons)	Shape	Length (mm)	Depth (mm)	Height (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	SKU
400	88	Rectangle	1,200	1,050	400	1.5"	1	255mm VENTED	35	BLACK	PS-171704
800	176		1,350	1,200	600	1.5"	1	255mm VENTED	55	BLACK	PS-171708
1,000	220		1,650	1,200	600	1.5"	1	255mm VENTED	70	BLACK	PS-171710



Flat use, rectangular, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with a single, vented lid and multiple slots for securing with ratchet/cargo straps and/or a metal frame, this tank has moulded-in baffles to prevent sloshing and increase stability when on the move.

Multiple applications: potable drinking water, rainwater harvesting, liquid transport, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.

Vertical - Non-baffled - 1000 Litres *All Applications including WRAS*

Volume (Litres)	Volume (Gallons)	Shape	Length (mm)	Height (mm)	Depth (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	SKU
1,000	220	Rectangle	1,650	1,200	670	1.5"	1	455mm VENTED	55	BLACK	PS-171310
1,000	220		1,650	1,200	670	1.5"	2	455mm VENTED	56	BLACK	PS-17131201



Vertical use, slightly bulbous, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with one or two vented lids but no internal baffles, this is a static tank, not designed for transporting liquids.

Multiple applications: potable drinking water, rainwater harvesting, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.









A "catch-all" 1½" **Hansen** fitting is supplied loose with each tank. Complete with male and female threads, once the tank is in position this fitting can be positioned exactly where you want it and allows you to connect pipework, ball valves etc. Alternative size fittings are available (see page 2).



Above Ground Tanks - small-medium range - slimline

Options Rainwater Harvesting Kits, Outlets and Linking Kits

Name	Contents	Application	Image
Small Outlet Fittings WRAS-approved	0.5" / 0.75" / 1" / 1.25" / 1.5" Hansen Fittings	Allows connection to a range of fittings. Taps, valves, water pump, etc.	
Medium Outlet Fittings WRAS-approved	2" / 3" / 4" Hansen Fittings	Allows connection to a range of fittings. Taps, valves, water pump, etc.	
Simple Link Kits (without ball valves)	Suitable for water or waste. Link tanks together, 1m apart to increase capacity.	2 x tank connectors, 2 x hose barbs, 2 x pipe clips & 1m long flexible hose. available in 1" 2" 3" or 4" sizes.	
Link Kits (with isolating ball valves)	Suitable for water or waste. Link tanks together, 1m apart to increase capacity. Facility to isolate tanks from each other.	2 x tank connectors, 2 x hose barbs, 2 x pipe clips, 2 x ball valves & 1m long flexible hose. available in 1" 2" 3" or 4" sizes.	
Simple Rainwater Kit	Filter collector with 1m link kit. Fits all UK downpipes from 65mm-110mm (round or square). Filter cartridge easily cleaned.	90m ² roof Use with small tanks and water butts. Will need regular maintenance to clear debris from filter.	
Rainwater Harvesting Kit A	Filter, dirt collection basket, siphon overflow c/w skimming inlet, siphon overflow to fit a 130mm hole in storage tank wall, calmed inlet to prevent incoming water disturbing tank sediment. Use with large tanks.	200m ² roof Use when there is only 1 capture tank. Will need regular maintenance to clear debris from filter.	
Rainwater Harvesting Kit B		450m ² roof Use when surplus water can be siphoned off to mains drainage. Maintain every 3 months to remove debris.	

Please note: tank sizes quoted are subject to a +/-3% variation. We reserve the right to amend the technical specification to improve the product without prior notification. Plastic process and material guarantee: 10 years based on UV8: excludes damage due to misuse. Any customised tanks cannot be returned.



Vertical - Baffled



Flat - Baffled



Vertical - Non-baffled



Hansen Tank Connectors