



Superior Performance

The Liquid Element PCIe Add-In-Card (AIC) features high dense capacity and extreme performance for mission critical and performance-demanding workloads. It is an ultra-thin, standard form factor half-height half-length (HHHL) card that works seamlessly with systems that have existing PCIe slots. This makes the Element AIC ideal for deployment in data center and enterprise applications.

The Element AIC offers a Gen 3.0 x8 PCIe interface, which enables high-throughput and low-latency transactions. It utilizes the latest NVMe protocol in order to deliver increased performance and efficiency from a single device. The AIC outperforms legacy architectures by delivering 1.25 M IOPS of random performance, over 7 GB/s of throughput and ultra-low transactional latency of 20 μ s.

The Element AIC's innovative design enables multiple drive configurations ranging from maximum performance to maximum redundancy. The AIC also features enterprise-class power failure protection for increased reliability to prevent data loss and ensure uninterrupted work in case of power failure.

- > Ultra Fast PCIe Gen 3.0 x8 Interface
- > Performance of 1.25 M IOPS and 7 GB/s
- > High-capacity NVMe SSD, up to 16 TB
- > Enterprise-class Power Failure Protection

Key Features

- High Performance PCIe SSD
- Ultra Fast PCIe 3.0 x8 Interface
- NVMe 1.2.1 Protocol Supported
- High Capacity Design, up to 16 TB
- Standard Form Factor SSD
- Low Profile HHHL Card
- Plug-n-Play Compatibility
- UEFI Boot Support
- Enterprise Grade Reliability
- Power Loss Data Protection
- Active Thermal Throttling
- Active Power Management
- Advanced ECC and Data Protection
- Advanced Error Recovery
- Active Telemetry Monitoring
- Low Overhead Architecture
- No Host CPU or DRAM Off Load
- RAID on Card Supported
- Data Protection



LIQID

Element LQD3000 PCIe AIC SSD Specifications

Specification

Model: Element LQD3000 PCIe AIC SSD

Raw Capacity	Up to 16 TB
NAND Type	TLC 3D NAND
Read Bandwidth (GB/s)	~7.0
Write Bandwidth (GB/s)	~6.3
Ran. Read IOPS (4k)	~1,250,000
Ran. Write IOPS (4k)	~900,000
Ran. Write IOPS (4k) (SS)	~275,000
Read Access Latency	~80 µs
Write Access Latency	~20 µs
Protocol	NVMe 1.2.1
Bus Interface	PCI Express 3.0 x8
Endurance	Up to 30.76 PBW*
Security	256 Bits AES Data Encryption
Weight	6-10 oz
Warranty	3 years, or maximum endurance used
Form Factor	Standard Form Factor HHHL Card
Temperature	Op: 0 to 55 deg C Non-Op: -40 to 75 deg C
Power	Active: ~25 W Typical Input: 12 V Only (optional aux power cable)
Air Flow	Min 400 LFM
Humidity	5% to 95% (non-condensing)
Altitude	0 ft to 10,000 ft
Operating Environments	Windows, Windows Server 2012, 2012 R2 RHEL; SLES; CentOS, Solaris, SUSE, VMware
Agency & Safety	UL, CB, CE, CCS, KCC, HF, BSMI, VCCI, FCC Class B and CISPR Class B, JEDEC

*PBW table per capacity/configuration available upon request

Data Center Selection

Toshiba 3D NAND:

- LQD-E1APNAA04M960G00
960GB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M001T92
1.92TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M003T84
3.84TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M007T68
7.68TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M015T40
15.40TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD

Samsung 3D NAND:

- LQD-E1APNBD04M003T84
3.84TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNBD04M007T68
7.68TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNBD04M015T40
15.40TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD

Enterprise Selection

Toshiba 3D NAND:

- LQD-E1APNAA04M800G00
800GB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M001T60
1.60TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M003T20
3.20TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M006T40
6.40TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNAA04M012T80
12.80TB, TN, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD

Samsung 3D NAND:

- LQD-E1APNBD04M003T20
3.20TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNBD04M006T40
6.40TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD
- LQD-E1APNBD04M012T80
12.80TB, 983, NVMe PCIe Gen 3.0 x8 HHHL AIC SSD

Please contact your sales rep for more information and to determine which configuration is best for use. Specification subject to change without notice.

About Liqid

A leader in composable infrastructure, Liqid enables users to configure and manage physical, bare-metal server systems in seconds. Storage, compute, networking and graphics processing devices are interconnected over PCI-Express fabric to deliver dynamically configurable bare-metal servers perfectly sized with the exact physical resources required by the application being deployed.

Contact Information

Liquid, Inc.
329 Interlocken Pkwy., Ste 200
Broomfield, CO 80021
office: +1 303.500.1551
email: sales@liquid.com