

# High speed and reliability. You can count on.

The high-end, solution capable A3 mono printer will meet all of your demanding office requirements. With a print speed of up to 60 pages per minute for A4 size paper and a fast first print out in 3.8 seconds, it will be ready when you need it. A user-friendly 9 inch full-colour and intuitive touch panel makes all the device's features easily accessible. This combined with our long-life components will provide exceptional efficiency and reliability, making this printer the perfect choice to increase overall productivity in workgroups and production offices.

**ECOSYS P4060dn****A3 Laser Monochrome****60/30 ppm for A4/A3****1,200 x 1,200 dpi resolution**

## Specifications

### GENERAL

KYOCERA ECOSYS Laser Monochrome,  
HyPAS™ solution platform  
**Operation panel:** 9 inch full-colour touch panel display, 15–90° swivel mounted  
**Engine speed:** Up to 60/30 pages A4/A3 per minute,  
Duplex print speed: 60 pages A4 per minute  
**Resolution:** 1,200 × 1,200 dpi, 2 bit depth for print quality of 4,800 dpi equivalent × 1,200 dpi  
**Warm-up time:** Approx. 17 seconds or less  
**Time to first print:** Approx. 3.8 seconds or less  
**CPU:** Freescale QorIQ T1024 (Dual Core) 1.2 GHz  
**Memory:** 4 GB RAM, 8 GB SSD + 320 GB HDD  
**Standard interfaces:** 4 × USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10 BaseT/100 BaseTX/1,000 BaseT, slot for optional print server, slot for optional SD card  
**Integrated accounting:** 1,000 department codes  
**Dimensions (W × D × H):** 602 mm × 665 mm × 790 mm  
**Weight:** 77.2 kg  
**Power source:** AC 220–240 V, 50/60 Hz  
**Power consumption:**  
Printing: 820 W  
Ready Mode: 40 W  
Sleep Mode: 1.0 W  
**Noise (sound pressure level ISO 7779 measurement distance of 1 meter):**  
Printing: 55.8 dB(A)  $L_{pA}$   
Ready Mode: 32.4 dB(A)  $L_{pA}$   
**Safety standards:** TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.  
**Input capacity:** Multi-purpose tray: 150 sheets, 52–300 g/m<sup>2</sup> (Banner 135–165 g/m<sup>2</sup>), A6R–SRA3 (320 × 450 mm), Tab paper (136 × 256 g/m<sup>2</sup>) Banner max. 320 × 1,220 mm;  
Universal paper cassette: 2 × 500 sheets, 52–300 g/m<sup>2</sup>, upper cassette A6R up to A4R (320 × 450 mm), lower cassette A6R up to SRA3;  
Max. input capacity with options: 7,150 sheets A4  
**Duplex:** Duplex as standard supports 64–256 g/m<sup>2</sup>, A6R–SRA3 (320 × 450 mm)  
**Output capacity:** Standard 500 sheets face-down, max. output capacity with options 4,300 sheets

### CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752.  
**TK-6334 Toner Kit:** Microfine toner black for 32,000 pages A4, Capacity of starter toner is 16,000 pages A4  
**WT-8500 Waste Toner Bottle:** 70,000 sheets or more (in accordance with ISO/IEC 19752)  
**Staples:** SH-10 for DF-7120/BF-730, SH-12 for DF-7110

### PRINT FUNCTIONS

**Controller language:** PRESCRIBE IIc  
**Emulations:** PCL6 (PCL-5e/PCL-XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS  
**Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request  
**Fonts/barcodes:** 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)  
**Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality, Duplex print mode, N-Up printing mode, Toner save mode  
**Mobile printing support:** AirPrint, Mopria, Google Cloud Print compliant, NFC, Direct Wi-Fi (optional), MyPanel and KYOCERA Mobile Print app for iOS and Android

### OPTIONS

**PF-7100 Paper feeder:** 2 × 500 sheets, 52–300 g/m<sup>2</sup>; A6R–SRA3 (320 × 450 mm), folio  
**PF-7110 Paper feeder:** 2 × 1,500 sheets, 52–300 g/m<sup>2</sup>; A4, B5, letter  
**PF-7120 Paper feeder:** A4 side Deck: 3,000 sheets, 60–300 g/m<sup>2</sup>; A4, B5 (PF-7100 or PF-7110 required)  
**JS-7100 Job separator:** 100-sheet internal job separator, 52–300 g/m<sup>2</sup>; A5R–SRA3  
**CB-7100W Wooden Cabinet:** desk with storage capacity  
**CB-7110M Metal Cabinet:** desk with storage capacity  
**DF-7110<sup>1</sup> Document Finisher + AK-7100:**  
Main tray: Max. 4,000 sheets A4 (3,000 sheets with attachment BF-730); max. 52–300 g/m<sup>2</sup>; max. A6R–SRA3  
Sub tray: 200 sheets A4; 52–300 g/m<sup>2</sup>; A6R–SRA3  
AK-7100: 100 sheets; 52–300 g/m<sup>2</sup>; A6R–SRA3  
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5–SRA3

### DF-7120<sup>1</sup> Document Finisher + AK-7100:

Main tray: 1,000 sheets A4, 52–300 g/m<sup>2</sup>, A6R–SRA3, 3 positions stapling up to 50 sheets A4 or 30 sheets SRA3  
AK-7100: 100 sheets; 52–300 g/m<sup>2</sup>, A6R–SRA3  
**PH-7C Punch Unit:** for DF-7120/DF-7110: 2-hole/4-hole/Swedish type, 60–300 g/m<sup>2</sup>, A5R–A3  
**MT-730(B) Mailbox sorter:** for DF-7110, 7 bins × 100 sheets A4, 50 sheets A3/B4, 60–165 g/m<sup>2</sup>  
**BF-730 Booklet and tri-folding unit:** for DF-7110  
Half-folding: 52–256 g/m<sup>2</sup>, A3, B4, A4R  
Booklet: Max. 16 sheets (64 pages, 60–90 g/m<sup>2</sup>)  
Non-staple folding: Max. 5 sheets (60–90 g/m<sup>2</sup>)  
Tri-folding: 60–105 g/m<sup>2</sup>, A4R  
Multi tri-folding: 5 sheets (60–90 g/m<sup>2</sup>), 3 sheets (91–105 g/m<sup>2</sup>)  
**Data Security Kit (E):** Encrypts data stored on SSD/HDD.  
In line with ISO 15408 (common criteria) with security level EAL2.  
**NK-7100(B):** Numeric keypad  
**Card Authentication Kit (B) AC:**  
USB IC Card Reader supports various authentication card keys  
**UG-33:** ThinPrint support  
**UG-34:** Emulation (IBM Proprinter/EPSON LQ-850/Line Printer)  
**Optional interfaces:**  
**IB-35:** Direct Wi-Fi Interface  
**IB-50:** Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)  
**IB-51:** Wireless LAN (802.11b/g/n)

<sup>1</sup> Bridge unit AK-7100 is required for the use of DF-7110/DF-7120.

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. Kyocera's long-life components cost you and the environment less.

HyPAS™



**Copysonic Australia**  
**315 Huntingdale Rd, Oakleigh**  
**Ph: 03 9544-0944**  
**Email: info@copysonic.com.au**

**KYOCERA Document Solutions Partner**

FEBRUARY2020DSECOSSP4060DN/VER1.0

**KYOCERA Document Solutions Australia**  
**Ph: 13 59 62**  
**www.kyoceradocumentsolutions.com.au**

**KYOCERA Document Solutions New Zealand\***  
**Ph: 0800 459 623**  
**www.kyoceradocumentsolutions.co.nz**



**kyoceradocumentsolutions.com.au**