

PRODUCT DATA SHEET

PTC-2002/WA2 ABRASIVE SURFACES WIPES KIT PTI WIPES KIT SERIES

DESCRIPTION

PTC-2002/WA2 Abrasive Surface Wipes Kit includes a concentrated cleaner, wipes for abrasive surfaces and dispensing bucket that all meet and exceed current military and commercial specifications. The dispensing bucket is an airtight container with a gasket to reduce contamination and/or evaporation. PTC-2002/WA2 kit gives you more control over the dispensing and application of your cleaning solution; because the amount of solution added is measured and fully saturated into each wipe results in a max 20% reduction in chemical usage. All these factors make this detail kit the most productive and efficient way to clean parts and equipment with abrasive surfaces.

CLEANER PROPERTIES & CHARACTERISTICS

Odor	None
PH	9-10
Flammable	Non-Flammable
Biodegradable	Yes
Weight (Pounds per gallon)	8.6 lbs
Solvents	No organic or inorganic solvents
Carcinogenic	No
Hazardous Air Pollutants	None
VOC	0 g/l
Specifications	MIL-PRF-85570E TYII &TYII RTU

CLEANING WIPE PROPERTIES & CHARACTERISTICS

Silicone	None
Extremely Low Lint	Reduces risk of FOD (foreign object damage)
No glues, adhesives or binders	Reduces risk of FOD
Compatible Solvents	MEK, MPK, TCE, Acetone, IPA etc.
Compatible Cleaners	PTC-2001 & PTC-2002TYII
Specifications	AMS 3819C (QPL) & BMS 15-5F
Color	White or Off White
Water Abs	>400%
Linting	<10mg/sqft
pH- Water Extract	6.0 – 7.5

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers.
1 year when stored between 50°-85° Fahrenheit.

PRODUCT DATA SHEET

MIXING/APPLICATION INSTRUCTIONS

1. Dilute PTC-2002 TYII before use, to a volume of 1.2 gallons (4.50L). Use more or less liquid for desired saturation.
 - a. For heavy duty degreasing / cleaning, dilute 4 parts water to 1 part product.
 - b. For Medium Duty Cleaning, dilute 10 parts water to 1 part product
 - c. For Light Duty Cleaning, dilute up to 14 parts water to 1 part product.
2. Place the role of wiper in the bucket.
3. Slowly poor the solution over the top of the roll.
4. Thread the end of the wiper from the center of the roll through the lid opening
5. After the wipers are used, refill only the same wiper (WA2) & chemical solution (PTC-2002TYII) as indicated on the label.

NOTE: Application of PTI products requires the use of all OSHA approved safety equipment, including proper ventilation. Additionally, PTI products require the recommended temperature/humidity conditions and film thickness ranges for optimal performance. The material, hangar, and aircraft skin temperatures should be no lower than 75° F / 25° C before, during and after application.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.