



PRODUCT DATA SHEET

MIL-T-19588A PTI SOLVENT BLEND

DESCRIPTION

MIL-T-19588A is a specially formulated solvent blend that is photochemically reactive. This product is used as a thinner for vinyl-red anti-fouling paint, vinyl-red lead primer, and vinyl-alkyd type exterior paint. It is NOT satisfactory for use as a thinner for pretreatment, wash primer.

SOLVENT PROPERTIES & CHARACTERISTICS

Flash Point	44°F
Weight (lbs per gallon)	6.9 lbs
Color	Clear
Volatile Organic Compounds (VOC)	833 g/l

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.