

# PRODUCTS TECHNIQUES, INC.

## Safety Data Sheet

### SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: MIL-PRF-85285E TY.I/III/IV CL.H GLOSS BLACK Product Code: PT-799#17038

MANUFACTURER:  
Products/Techniques, Inc.  
3271 S. Riverside Ave.  
Bloomington, CA 92316

PH: 909.877.3951  
FX: 909.877.6078  
E-mail: [pti@ptipaint.com](mailto:pti@ptipaint.com)  
Web: [www.ptipaint.com](http://www.ptipaint.com)

OPERATING HOURS: 8:00 am - 4:30 pm PDT

In an emergency, call:  
CHEMTREC: 1.800.424.9300

### SECTION 2 - HAZARDS IDENTIFICATION

HMIS:230X

#### GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Oral Toxicity	4	Oral>300+<=2000mg/kg
Dermal Toxicity	4	Dermal>1000+<=2000mg/kg
Inhalation Toxicity	4	Gases>2500+<=20000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Respiratory sensitizer	1	Respiratory sensitizer

#### GHS Hazards

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H316	Causes mild skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled

#### GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P285	In case of inadequate ventilation wear respiratory protection

P363 Wash contaminated clothing before reuse  
P302+P352 IF ON SKIN: Wash with soap and water  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing  
P370+P380+P375 In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion  
P402+P404 Store in a dry place. Store in a closed container  
P403+P235 Store in a well ventilated place. Keep cool

**Signal Word: Danger**



### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Trade secrets, proprietary, non-hazardous, and unlisted ingredients are not hazardous to humans, the environment, and are not regulated materials.

Chemical Name	CAS number	Weight Concentration %
POLYESTER POLYOL RESIN	TRADE SECRET OF MFG.	57.17%
HEPTAN-2-ONE	110-43-0	12.85%
N-BUTYL ACETATE NORMAL	123-86-4	11.02%
1-METHOXY-2-PROPANOL ACETATE	108-65-6	8.71%
CARBON BLACK PIGMENT	1333-86-4	2.99%
METHYL ETHYL KETONE	78-93-3	2.12%
DIISOBUTYL KETONE	108-83-8	1.77%
TRADE SECRET NON HAZARDOUS	PROPRIETARY SURFACTANT	0.78%
PENTANEDIONE ADDITIVE	123-54-6	0.52%
1-OCTENE	111-66-0	0.44%
CELLULOSE ACETATE BUTYRATE	9004-36-8	0.32%
Poly(oxy-1,2-ethanediyl), a-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-~-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	104810-47-1	0.32%
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	0.31%
Poly(oxy-1,2-ethanediyl), a-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-~-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	104810-48-2	0.24%
SOLVENT NAPHTHA	64742-95-6	0.13%
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	0.13%
SILANE	1760-24-3	0.11%
CATALYST ADDITIVE	77-58-7	0.00%

### SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, **LEAVE AREA IMMEDIATELY** and get fresh air. If breathing problems remain, **SEEK IMMEDIATE MEDICAL ATTENTION**.

EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.

INGESTION: Do not induce vomiting. Get immediate medical attention.

## SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: -6 C (21 F)

LEL: 1.0%

UEL: 11.0%

All flashpoints: TCC LEL AND UEL expressed as percent (%)

EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water spray/water fog extinguishing systems

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

## SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

## SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

POLYESTER POLYOL RESIN TRADE SECRET OF MFG.	Not Established	Not Established	Not Established
HEPTAN-2-ONE 110-43-0	100 ppm TWA; 465 mg/m3 TWA	50 ppm TWA	NIOSH: 100 ppm TWA; 465 mg/m3 TWA
N-BUTYL ACETATE NORMAL 123-86-4	150 ppm TWA; 710 mg/m3 TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
1-METHOXY-2-PROPANOL ACETATE 108-65-6	TWA 50 PPM	Not Established	Not Established
CARBON BLACK PIGMENT 1333-86-4	3.5 mg/m3 TWA	3.5 mg/m3 TWA	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (as PAH, carbon black in presence of polycyclic aromatic hydrocarbons)
METHYL ETHYL KETONE 78-93-3	200 ppm TWA; 590 mg/m3 TWA	300 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 590 mg/m3 TWA 300 ppm STEL; 885 mg/m3 STEL
DIISOBUTYL KETONE 108-83-8	50 ppm TWA; 290 mg/m3 TWA	25 ppm TWA	NIOSH: 25 ppm TWA; 150 mg/m3 TWA
TRADE SECRET NON HAZARDOUS PROPRIETARY SURFACTANT	Not Established	Not Established	Not Established
PENTANEDIONE ADDITIVE 123-54-6	Not Established	Not Established	Not Established
1-OCTENE 111-66-0	TWA: 75ppm	Not Established	Not Established
CELLULOSE ACETATE BUTYRATE 9004-36-8	Not Established	Not Established	Not Established
Poly(oxy-1,2-ethanediyl), a- [3-[3-(2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4- hydroxyphenyl]-1-oxopropyl]- ~-[3-[3-(2H-benzotriazol-2-yl) -5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropoxy]- 104810-47-1	Not Established	Not Established	Not Established
bis(1,2,2,6,6-pentamethyl-4- piperidyl)sebacate 41556-26-7	Not Established	Not Established	Not Established

Poly(oxy-1,2-ethanediyl), a-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-~-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-104810-48-2	Not Established	Not Established	Not Established
SOLVENT NAPHTHA 64742-95-6	Not Established	Not Established	Not Established
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 82919-37-7	Not Established	Not Established	Not Established
SILANE 1760-24-3	Not Established	Not Established	Not Established
CATALYST ADDITIVE 77-58-7	Not Established	Not Established	Not Established

**ENGINEERING CONTROLS:** Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**VENTILATION & RESPIRATORY PROTECTION:** Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

**ADMINISTRATIVE CONTROLS:** All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set its own policies regarding the use of respirators and other Personal Protective Equipment.

**SKIN PROTECTION:** Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.

**OTHER PROTECTIVE EQUIPMENT:** Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before

reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

## SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

This product exhibits the following properties under normal conditions:

<p style="text-align: center;"><b>Appearance</b> Pigmented liquid</p> <p><b>Vapor Pressure:</b> 8.9 mmHg</p> <p><b>Vapor Density:</b> 4.0</p> <p><b>Density:</b> 1.05</p> <p><b>Freezing point:</b> N/A</p> <p><b>Boiling Range:</b> 80 - 163°C</p> <p><b>Evaporation rate:</b> N/A</p> <p><b>Explosive Limits:</b> 1% - 11%</p> <p><b>Autoignition temperature:</b> 315°C</p> <p><b>VOC(g/l) Less H2O and Exempt Compounds</b> 376.33</p> <p><b>Specific Gravity</b> 1.05</p> <p><b>Weight/Gallon</b> 8.75</p>	<p style="text-align: center;"><b>Odor</b> Solvent like</p> <p><b>Odor threshold:</b> N/A</p> <p><b>pH:</b> N/A</p> <p><b>Melting point:</b> N/A</p> <p><b>Solubility:</b> N/A</p> <p><b>Flash point:</b> -21F</p> <p><b>Physical State</b> Liquid</p> <p><b>Partition coefficient (n-octanol/water):</b> N/A</p> <p><b>Decomposition temperature:</b> N/A</p> <p><b>VOC(lbs/gal) Less H2O and Exempt Compounds</b> 3.14</p> <p><b>% VOC (C.A.R.B)</b> 35.91</p> <p><b>% Weight VOC in Can</b> 43%</p>
--	--

## SECTION 10 - REACTIVITY & STABILITY

STABILITY:

STABLE

INCOMPATIBILITY (Materials to avoid): strong acids and bases, oxidizers, and selected amines.

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

No Data

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO<sub>2</sub>). Other unknown hazardous products are possible.

No Data

Hazardous polymerization will not occur.

## SECTION 11 - TOXICOLOGICAL INFORMATION

**Mixture Toxicity**

Inhalation Toxicity LC50: 549mg/L

**Component Toxicity**

110-43-0	HEPTAN-2-ONE Oral LD50: 1,670 mg/kg (Rat)
123-86-4	N-BUTYL ACETATE NORMAL Inhalation LC50: 390 ppm (Rat)
108-65-6	1-METHOXY-2-PROPANOL ACETATE Dermal LD50: 5,000 mg/kg (Rabbit); Inhalation LC50: 100 ppm (Rat)
78-93-3	METHYL ETHYL KETONE Oral LD50: 2,737 mg/kg (Rat) Inhalation LC50: 32 g/m3 (Mouse)

108-83-8	DIISOBUTYL KETONE Dermal LD50: 16 g/kg (Rabbit) Inhalation LC50: 2,300 ppm (Rat:)
123-54-6	PENTANEDIONE ADDITIVE Oral LD50: 55 mg/kg (Rat) Dermal LD50: 810 µL/kg (Rabbit) Inhalation LC50: 1,224 ppm (Rat)
111-66-0	1-OCTENE Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 3,600 mg/kg (Rabbit)
9004-36-8	CELLULOSE ACETATE BUTYRATE Oral LD50: 3,200 mg/kg (Rat) Dermal LD50: 1,000 mg/kg (Guinea Pig)
77-58-7	CATALYST ADDITIVE Oral LD50: 175 mg/kg (Rat)

**INHALATION:** Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

**INGESTION:** This material may be harmful or fatal if swallowed.

**SKIN CONTACT:** May cause sensitization or allergic reaction.

**EYE CONTACT:** Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

Routes of Entry:

Inhalation      Skin Contact      Eye Contact      Ingestion

Exposure to this material may affect the following organs:

**Effects of Overexposure**

**CARCINOGENICITY:**

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
1333-86-4	CARBON BLACK PIGMENT	2.99%	CARBON BLACK PIGMENT: NIOSH: Potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed

**ACUTE TOXICITY:**

**INHALATION: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

**CONDITIONS AGGRAVATED:** Unknown.

**CHRONIC EFFECTS: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.**

## SECTION 12 - ECOLOGICAL INFORMATION

No information available.

**Component Ecotoxicity**

HEPTAN-2-ONE	96 Hr LC50 Pimephales promelas: 131.0 mg/L [flow-through]
N-BUTYL ACETATE NORMAL	96 Hr LC50 Leuciscus idus: 62 mg/L [static] 48 Hr EC50 water flea: 44 mg/L 96 Hr EC50 Scenedesmus subspicatus: 320 mg/L; 72 Hr EC50 Scenedesmus subspicatus: 674.7 mg/L
1-METHOXY-2-PROPANOL ACETATE	96 Hr LC50 Pimephales promelas: 161 mg/L [static] 48 Hr EC50 Daphnia magna: >500 mg/L
CARBON BLACK PIGMENT	24 Hr EC50 Daphnia magna: >5600 mg/L

METHYL ETHYL KETONE	96 Hr LC50 Pimephales promelas: 3220 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1690 mg/L 48 Hr EC50 water flea: 520 mg/L; 48 Hr EC50 Daphnia magna: 5091 mg/L
DIISOBUTYL KETONE	96 Hr LC50 Oncorhynchus mykiss: 140 mg/L [semi-static] 96 Hr EC50 Selenastrum capricornutum: 100 mg/L
PENTANEDIONE ADDITIVE	96 Hr LC50 Pimephales promelas: 104 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 29 mg/L 48 Hr EC50 Daphnia magna: 34.4 mg/L
CATALYST ADDITIVE	48 Hr LC50 Oryzias latipes: 2 mg/L

### SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

### SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material! Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
D.O.T.	PAINT	UN 1263	II	3

### SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed under California Proposition 65:

1333-86-4 CARBON BLACK PIGMENT 2.99% Carcinogen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

110-43-0 HEPTAN-2-ONE  
 123-86-4 N-BUTYL ACETATE NORMAL  
 108-65-6 1-METHOXY-2-PROPANOL ACETATE  
 1333-86-4 CARBON BLACK PIGMENT  
 78-93-3 METHYL ETHYL KETONE  
 108-83-8 DIISOBUTYL KETONE

The following chemicals appear on the Pennsylvania Right-To-Know list:

110-43-0 HEPTAN-2-ONE 12.85%  
 123-86-4 N-BUTYL ACETATE NORMAL 11.02%  
 108-65-6 1-METHOXY-2-PROPANOL ACETATE 8.71%  
 1333-86-4 CARBON BLACK PIGMENT 2.99%  
 78-93-3 METHYL ETHYL KETONE 2.12%  
 108-83-8 DIISOBUTYL KETONE 1.77%



SARA HAZARD CATEGORY: The product has been reviewed according to the EPA 'Hazard Categories' promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

- 110-43-0 HEPTAN-2-ONE Fire Hazard
- 123-86-4 N-BUTYL ACETATE NORMAL Fire Hazard, Acute Health Hazard
- 108-65-6 1-METHOXY-2-PROPANOL ACETATE Fire Hazard, Acute Health Hazard
- 1333-86-4 CARBON BLACK PIGMENT Acute Health Hazard, Chronic Health Hazard
- 78-93-3 METHYL ETHYL KETONE Fire Hazard, Acute Health Hazard, Chronic Health Hazard
- 108-83-8 DIISOBUTYL KETONE Fire Hazard, Acute Health Hazard

TOXIC SUBSTANCES CONTROL ACT: TSCA 2018 RESET COMPLIANT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No Data

**Country** **Regulation** **All Components Listed**

**EU Risk Phrases**

**Safety Phrase**

All ingredients are TSCA 2018 Reset Compliant. The chemical substances listed below are not on the TSCA Section 8 Inventory:

No Data

SARA Section 313: The product contains the following substances subject to the reporting requirements of section 313 and Title II of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

**SECTION 16 - OTHER INFORMATION**

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.


(C) Copyright, 2015 Products Techniques, Inc.

**Hazardous Material Information System (HMIS)**

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH

**National Fire Protection Association (NFPA)**



Date revised: 2016-04-06  
Date Prepared: 6/3/2019

Reviewer Revision