



CLAD WOOD CLASSIC CLAD PANORAMIC VIEW

Featuring “concealed” sashes that are not visible from the outside. Fixed and operable windows share a single, contemporary, and seamless horizontal glass line. With hidden hinges and 90 degree frame profiles, it offers one of Zola’s most unique frame designs. A solid timber frame construction with German, aluminum rain screen cladding.

PERFORMANCE

Frame Depth = 68mm (2 43/64")
Uw = 1.2W/m2K (0.21 Btu/hr.sqftF)

Air Permeability = Class 3
(EN1026/EN12207)

Water Tightness Class 5A
(EN1027/EN12208)

Wind Load = Class C2
(EN12211/EN12210)

IGU Packet = double pane
Standard Ug = 0.176 (R 5.7)
Standard SHGC = 0.62 (0.3 avail.)
VT = 80%
Low-E standard
Argon gas-filled
Warm edge spacers

NFRC Values:

Fixed

U = 0.27

SHGC = 0.42

VT = 0.56

Operable

U = 0.29

SHGC = 0.42

VT = 0.56

TIMBER & FINISH OPTIONS

Timbers available: finger jointed pine (base timber), Clear Pine, Meranti, Sapele, European White Oak, and Larch.

Pine and Oak timbers are standard FSC® Certified. FSC Certified Meranti is available.
FSC License: FSC-C112130

Interior Finish Options: RAL painted timber, or standard set of interior stains.

Exterior Finish Options: RAL powder coated finish (matte) cladding.

CONFIGURATIONS AVAILABLE

Fixed

Tilt-turn, Tilt-only, Turn-only, Tilt-first

Fixed/Operable combinations

French window opening

Balcony doors (tilt-turn, inswing only)

Lift-Slide Doors

HARDWARE

European multi-point locking
Roto (concealed hinges), standard

SIZING

Min frame width = 577mm (22")

Max frame width = 1521mm (59.8")

Min frame height = 406mm (16")

Max balcony door height = 2450mm (96")

