CLAD WOOD
THERMO CLAD PANORAMICVIEW™

Using a hidden operable sash, Thermo Clad Panoramic View fixed and operable windows cannot be distinguished from each other on the outside. Using a slightly larger frame than Classic Clad Panoramic View, Thermo Clad Panoramic View achieves the discerning look of consistency with the high thermal frame and glass performance. A laminated, warp-resistant, solid timber construction frame. Triple compression air seals and exterior aluminum rainscreen cladding mounted on rails for an ultimate durability and rot resistance.

PERFORMANCE

Frame Depth = 88mm (3.46")

NFRC Values:
- Fixed
  - U = 0.16 Btu/(h.ft2.F)
  - SHGC = up to 0.37
  - VT = 0.51
  - Condensation Resistance = 74
- Operable
  - U = 0.15 Btu/(h.ft2.F)
  - SHGC = up to 0.36
  - VT = 0.51
  - Condensation Resistance = 74

TIMBER & FINISH OPTIONS

Timbers available: finger jointed pine (base timber), Clear Pine, Meranti, European White Oak, and Larch.

Interior Finish Options: RAL painted timber, or standard set of interior stains.

Exterior Finish Options: RAL Standard, RAL FS Premium, Tactile Series, and Anodized options.

CONFIGURATIONS AVAILABLE

Fixed
Tilt-turn, Tilt-only, Turn-only, Tilt-first
Fixed/Operable combinations
French window opening
Lift-Slide Doors

HARDWARE

European multi-point locking system with upto eight locking points on windows and four points on entry doors. Concealed hinges standard.

SIZING

Min frame width = 450mm (17.7")
Max frame width = 1521mm (59.8")
Min frame height = 402mm (16")
Max balcony door height = 2743mm (108")

All performance data based on typical assemblies. Discuss specific performance values with a Zola Project Manager

Questions? Contact us for assistance at 303.578.0001