

M3 SM15X



Key Features



Android 7.1 (Android 8.x is scheduled)



5" FHD TFT LCD (1920 X 1080)



Fast Charging / Battery Hot Swap
Li-ion Battery 4100mAh / 6150mAh



Physical Key : Front 4 keys, Side 5 Keys



2.2 GHz Octa Core CPU



4GB RAM / 32GB ROM



IEEE 802.11 a/b/g/n/ac



1D Laser, 2D Imager



IP65 Sealing
1.8M drop



16.0MP Auto Focus Camera



HF(NFC), UHF



Wet-touch



Glove-touch



Pen-touch

SPEED IS POWER



M3 SM15X

Rugged Mobile Computer with Full Touch Screen

5" FHD TFT LCD (1920 X 1080)
2.2GHz Octa Core CPU
Android 7.1
1D Laser, 2D Imager
16.0MP Auto Focus Camera
Fast charging / Battery Hot Swap



Specification

Physical	SM 15 X	SM 15 N	SM 15 W
DIMENSION (W x H x D)	76.4 x 154.8 x 21.6 mm (3.00 x 6.09 x 0.85 in)		
WEIGHT	Standard : 280g (9.8oz) , Extended : 340g (11.9oz)		
DISPLAY	5in. FHD(Full High Definition)(1920X1080) Outdoor viewable	5 in. HD TFT LCD (1280 x 720) Outdoor viewable	
TOUCH	Wet-touch / Glove-touch / Pen touch with Corning Gorilla Glass 3		
BATTERY	Standard: Li-ion 3.8V 4,100mAh, Extended: Li-ion 3.8V 6,150mAh		
POWER MANAGEMENT	Fast Charging / Battery Hot Swap		
SIM / SAM	2 SIM or 1 SIM / 1 SAM		
PHYSICAL KEYS	Volume +/- key, Camera key, Power Key 2 Scanner keys (Left, Right), 4 Bottom Keys (Home, Back, menu, Enter (Scan))		
Performance	SM 15 X	SM 15 N	SM 15 W
PROCESSOR	2.2 GHz Octa core	2.0 GHz Octa core	
OS	Android 7.1 (Android 8.x is scheduled)		
MEMORY	4 GB RAM	2 GB RAM	
	32 GB ROM	16 GB ROM	
	Card Slot: Micro SD(Up to 128GB)		
INTERFACE	Docking connector: Micro USB		
SENSORS	Gyro Sensor / Proximity Sensor / Light Sensor		
Wireless	SM 15 X	SM 15 N	SM 15 W
WWAN	2G GSM/GPRS/EDGE(850/900/1800 MHz) 3.8G UMTS/HSPA+(850/2100 MHz) 4G FDD LTE (850 / 900 / 1800 / 2100/ 2600 MHz)		N/A
WLAN	IEEE 802.11 a/b/g/n/ac		
BLUETOOTH	Class II, V4.1 LE		
GPS	A-GPS, GLONASS, BEIDOU		N/A
Data Capture	SM 15 X	SM 15 N	SM 15 W
SCANNER	1D Laser, 2D Imager		
CAMERA	Front: 5.0MP Auto Focus Rear: 16.0MP Auto Focus	Rear: 13.0MP Auto Focus	Rear: 13.0MP Auto Focus
RFID	HF (NFC ISO 14443 A/B, ISO 15693), UHF (EPC C1 Gen2, ISO18000 6C via Snap on/ Gun reader)		
User Environment	SM 15 X	SM 15 N	SM 15 W
TEMPERATURE	Operating : -20 to 60 °C / Storage : -30 to 80 °C		
HUMIDITY	95% non-condensing		
DROP TEST	1.2M / 1.8M(with protective boot)		
IP RATING	IP65		

M3 MOBILE
Your Best Mobile Business Partner

Headquarter
Seoul, Korea
+82-2574-0037
sales@m3mobile.co.kr

Factory/Service Center
Bucheon, Korea
+82-32-623-0037
cs@m3mobile.co.kr

EU Headquarter
Frankfurt, Germany
+49-69-6696-9420
sales_eu@m3mobile.net

Germany Office
Nuremberg, Germany
+42-(0)70-4891-4651
sales_eu@m3mobile.net

UK Office
Stafford, UK
+44-1785-887914
sales_eu@m3mobile.net

France Office
Paris, France
+82-(0)70-4891-4653
sales_eu@m3mobile.net

Turkey Office
Istanbul, Turkey
+82-(0)70-4801-0358
sales_eu@m3mobile.net