

**Part 1 – General****1.01 – SUMMARY**

- A. Corner guard system for wall protection and decoration.

**1.02 – SECTION INCLUDES**

- A. wX16 Series, Stainless Steel Corner Guards
- B. The following sections contain product info related to this section:
  1. Handrails, Wall Guards, Wall Covering, Door Protection, Rub Rail, refer to section 10 26 00 "Wall and Door Protection"

**1.03 – SUBMITTALS**

- A. Product Data: Manufacturer's printed product data for each type of corner guard specified.
- B. Shop Drawings: Mounting details with the appropriate fasteners for specific substrates.
- C. Samples: Verification samples of the corner guard, 8" (203mm) long, in full size profiles for each product indicated.
- D. Manufacturer's Installation Instruction: Printed installation instructions for each corner guard.
- E. Maintenance Data: Wall protection maintenance data for inclusion in the Division 1 operating and maintenance manuals.

**1.04 – QUALITY ASSURANCE**

- A. Appoint an installer with 3 or more years of experience in installation projects of similar complexity.
- B. Manufacturer has 5 or more years of experience in the production of specified product and reliable product performance.
- C. Assemblies should follow all applicable codes including IBC, UBC, SBCCI, BOCA, and Life Safety.
- D. *Impact Strength*: Provide rigid vinyl profile materials that have an Impact Strength value of 19 ft-lbs/in or greater as tested in accordance with the procedures specified in ASTM D-256, Notched Izod Test.
- E. Corner guards to be made from type 304, 16 gauge stainless steel.

**1.05 – DELIVERY, STORAGE, AND HANDLING**

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at time of delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight and from exposure to the elements. Maintain a minimum room temperature of 40°F and a maximum of 100°F.
- D. Store material flat and do not stack.

**1.06 – PROJECT CONDITIONS**

- A. Environmental Requirements: Products must be acclimated to a temperature of 65°F to 75° F for at least 24 hours before beginning installation.
- B. Install products in an enclosed and weatherproofed area of the same temperature.

**1.07 – WARRANTY**

- A. Standard Wallprotex limited lifetime warranty against material and manufacturing defects.

**Part 2 – Products****2.01 – MANUFACTURER**

- A. Acceptable Manufacturer: Wallprotex, 3750 Ohio Ave., St. Charles, IL 60174, Phone: 877-880-8115, www.

wallprotex.com

- B. Substitutions: Not permitted.
- C. Provide all corner guards and wall protection from a single source.
- D. All products are to be manufactured in the USA.

**2.02 – MANUFACTURED UNITS****A. Corner Guard Profile**

- 1. wX16 Series Stainless Steel Corner Guards Wing Sizes:

- 1" (25mm) x 1" (25mm), 90°
- 1-1/2" (38mm) x 1-1/2" (38mm), 90° or 135°
- 2" (51mm) x 2" (51mm), 90° or 135°
- 2-1/2" (64mm) x 2-1/2" (64mm), 90° or 135°
- 3" (76mm) x 3" (76mm), 90° or 135°
- 3-1/2" (89mm) x 3-1/2" (89mm), 90° or 135°
- Nose Radius: 1/8"

Grade: 304 Stainless Steel

Thickness: 16 gauge Standard Length: 48" (1.22m) and 96" (2.44m)

**2. Attachment Methods:**

- Pre-drilled counter sunk holes and screws
- Construction adhesive

**2.03 – MATERIALS**

- A. Stainless Steel: Corner guards shall be manufactured from Type 304, 16 gauge Stainless Steel (meets NSF standard 51).

**2.04 – ACCESSORIES****A. Attachment**

1. Fasteners: Predrilled counter sunk holes and Phillips head screws.
2. Adhesive: Field applied construction adhesive.

**2.05 – FABRICATION**

- A. Fabricate corner guard systems according to design, dimensions, detail, and finish per plans and specifications.

**2.06 – FINISHES**

- A. Stainless Steel with a No. 4 satin finish.

**Part 3 – Execution****3.01 – EXAMINATION**

- A. Prior to installation, examine areas and conditions in which the corner guards will be installed for defects, damage, or incomplete site preparation.
- B. Complete all finishing operations, including painting, before beginning installation of corner guard systems. New paint must be allowed to cure for an appropriate amount of time according to the paint manufacturer before corner guards are installed.
- C. Do not install corner guards if wall surface is not adequately prepared.

**3.02 – PREPARATION**

- A. Prior to installation of the corner guard system, clean substrate to remove dust, debris, grease, or any loose particles.

**3.03 – INSTALLATION**

- A. Locate corner guard as indicated on the approved shop drawing for the appropriate substrate. Install corner guard flush and tight at the height indicated on the appropriate drawing, with surfaces free from distortion or other defects in appearance.
- B. Use the approved mounting hardware.
- C. Install all corner guard systems in accordance and compliance with Wallprotex installation instructions.



**3.04 - CLEANING**

- A. At completion of the installation, clean surfaces in accordance with the Wallprotex cleanup and maintenance instructions.
- B. Remove extra materials and debris accumulated from installation.

