



GE ENDURIS™ 3500 ROOF COATING

KEEP CREWS WORKING THROUGH THE WINTER WITH GE ENDURIS™ 3500 ROOF COATING.

OUR 100% SILICONE FORMULA CAN BE APPLIED IN TEMPERATURES AS LOW AS 0°F (-18°C).

- Application, even spraying, in temperatures as low as 0°F (-18°C)
- UV Resistant
- Rain readiness in 30 minutes or less without freezing or cracking
- No heating required to prepare for application
- Primerless adhesion to most substrates
- Cold weather storage for up to 18 months



High productivity and uninterrupted schedules can be achieved during winter construction with GE Enduris 3500 Roof Coating. Keep your projects and teams moving—despite bitter cold snaps, frigid conditions, and unseasonable rain or snow.

GE Silicones Enduris 3500 Roof Coating offers maximum protection from the elements. The 100% silicone formula of our GE Enduris product family is durable, breathable, and permanently flexible through fluctuating conditions. It expands and contracts with the roof of the building for a long, resilient life—and won't crack, wash off, or come apart at the seams, as may occur with the alternatives.

You can keep projects on track with a solution that installs in extreme temperatures—as cold as 0°F (-18°C)—and is rain ready in 30 minutes or less. GE Enduris coatings are fast cure, so you can complete touchups without delay and move on to the next phase of your project.

Unbeaten in any season.

WATERPROOF.

A single coat cures quickly to form a durable membrane that is both vapor-permeable and airtight.

EXCEPTIONAL DURABILITY.

UV-resistant upon cure, and maintains its elasticity even after years of exposure to weather extremes. The seamless, permanently flexible membrane will not crack or separate.

EASY TO USE.

Can be applied by spray, power roller, conventional rollers, or brush—resulting in lower installation costs. One-coat application with no primer required, and compatible with most silicone sealants.

PERFORMS IN FRIGID CONDITIONS.

Can be applied in temperatures as low as 0°F (-18°C) without freezing or significant change in viscosity, allowing use in all seasons. In cold weather conditions, Enduris does not require heating or mixing of additives, and low temperatures do not impact the silicones' ability to bond and cure (assuming they are applied to clean and dry substrates). Can be exposed to a medium to heavy rain in as little as 30 minutes.



BENEFIT NOW AND LATER

TIME AND LABOR SAVINGS

With no mixing or primer required, this product can offer significant cost savings associated with labor and materials.

COLD WEATHER APPLICATION

Can be applied, even sprayed, throughout the year in temperatures as low as 0°F (-18°C), helping to keep service departments and crews working.

Ready to start your next project?

CONTACT US: gesilicones.com

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a trademark of General Electric Company. Used under trademark license.
The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.
Copyright 2020 Momentive Performance Materials Inc. All rights reserved.