

BLACK POLY WRAP SLEEVE



Provides a clean, professional look to any application.



In light abrasion environments utilize Black Poly to protect & quickly access power cord bundles.



An easy choice in applications with tight hose bends & high UV exposure.

MATERIAL ATTRIBUTES

 ABRASION RESISTANCE

 PUNCTURE RESISTANCE

 CHEMICAL RESISTANCE

 UV PROTECTION

 NON - WICKING ABILITY

 SPALL / SPARK PROTECTION

 WEIGHT / FLEXIBILITY

 TEMPERATURE RATING

ECONOMICAL CHOICE FOR FAST, EASY BUNDLING

Black Poly was designed specifically as an economical solution for hose, cable, & wire management. The 600 denier substrate is coated with a light layer of PVC, enhancing the sleeves ability to resist damage caused from water or sunlight. The economical design of Black Poly makes it a quick & easy solution in applications requiring bundling protection, light abrasion resistance, or simply a clean, professional look.

Black Poly features Military-Spec Extreme Hook & Loop closure, allowing the sleeve to be applied post hose assembly. The proprietary fastener has proven to reduce costs associated to installation or maintenance by up to 70%!

Typical Applications: Static hoses on mobile equipment, power cord bundles, computer cables, CNC hose bundles and pneumatic lines

- Economical solution for a variety of bundling requirements
- Excellent UV protection; meets EN13758-1
- Lightweight and flexible
- Provides a clean and professional look to any application
- Cut to length; easily installed or retrofitted

SIZING & ORDERING INFORMATION

BLACK POLY WRAP SLEEVE

PART NUMBER	MAX I.D.	CIRCUM
SL-1.0-JD	1.0"	3.14
SL-1.25-JD	1.25"	4.08
SL-1.5-JD	1.5"	4.71
SL-1.75-JD	1.75"	5.65
SL-2.0-JD	2.0"	6.28
SL-2.25-JD	2.25"	7.53
SL-2.5-JD	2.5"	7.85
SL-2.75-JD	2.75"	8.79
SL-3.0-JD	3.0"	9.42

PART NUMBER	MAX I.D.	CIRCUM
SL-3.25-JD	3.25"	10.36
SL-3.5-JD	3.5"	10.99
SL-4.0-JD	4.0"	12.56
SL-4.5-JD	4.5"	14.13
SL-5.0-JD	5.0"	15.70
SL-6.0-JD	6.0"	18.84
SL-7.0-JD	7.0"	21.99
SL-8.0-JD	8.0"	25.13
SL-9.0-JD	9.0"	28.27

PART NUMBER	MAX I.D.	CIRCUM
SL-9.5-JD	9.5"	29.84
SL-10.0-JD	10.0"	31.41
SL-11.0-JD	11.0"	34.55
SL-12.0-JD	12.0"	37.69
SL-13.0-JD	13.0"	40.84
SL-14.0-JD	14.0"	43.98
SL-15.0-JD	15.0"	47.12
SL-16.0-JD	16.0"	50.26

Standard lengths sold in 150' increments.

