

<b>National Pipe</b>				
Dash Size	Nominal Size	Torque (lb-ft)	Torque (ffft)	Pressure Rating (psi)
2	1/8	X	2-2.5	5000
3	3/16	X	X	X
4	1/4	X	2-2.5	5000
5	5/16	X	X	X
6	3/8	X	1.5-2	4000
8	1/2	X	2-2.5	3500
10	5/8	X	X	X
12	3/4	X	1.5-2	2500
14	7/8	X	X	X
16	1	X	1.5-2	2000
20	1 1/4	X	1.5-2	1150
24	1-1/2	X	1.5-2	1000
32	2	X	1.5-2	1000

ffft = Flats from finger tight

<b>JIC 37 Degree Flare</b>				
Dash Size	Nominal Size	Torque (lb-ft)	Torque (ffft)	Pressure Rating (psi)
2	1/8	6-7		
1	5000			
3	3/16	8-9	1	5000
4	1/4	11-12	1.5	5000
5	5/16	14-15	1	5000
6	3/8	18-20	1.5-1.75	5000
8	1/2	36-39	1.5-1.75	4000
10	5/8	57-63	1.5-1.75	3000
12	3/4	79-88	1.5-1.75	3000
14	7/8	94-103	1.5-1.75	2500
16	1	108-113	1.5-1.75	2500
20	1 1/4	127-133	2	2000
24	1-1/2	158-167	2	1500
32	2	245-258	2	1125

<b>SAE O-Ring Boss</b>				
Dash Size	Nominal Size	Torque (lb-ft)	Torque (ffft)	Pressure Rating (psi)
2	1/8	6-7		
1	5000			
3	3/16	8-9	1	5000
4	1/4	11-12	1.5	5000
5	5/16	14-15	1	5000
6	3/8	18-20	1.5-1.75	5000
8	1/2	36-39	1.5-1.75	4000
10	5/8	57-63	1.5-1.75	3000
12	3/4	79-88	1.5-1.75	3000
14	7/8	94-103	1.5-1.75	2500
16	1	108-113	1.5-1.75	2500
20	1 1/4	127-133	2	2000
24	1-1/2	158-167	2	1500
32	2	245-258	2	1125

<b>O-Ring Face Seal</b>				
Dash Size	Nominal Size	Torque (lb-ft)	Torque (ffft)	Pressure Rating (psi)
2	1/8	X		
X	6000			
3	3/16	X	X	6000
4	1/4	10-12	1.5-1.75	6000
5	5/16	X	X	6000
6	3/8	18-20	1.5-1.75	6000
8	1/2	32-35	1.5-1.75	6000
10	5/8	46-50	1.5-1.75	6000
12	3/4	65-70	1.5-1.75	6000
14	7/8	65-70	1.5-1.75	6500
16	1	92-100	1.5-1.75	5000
20	1 1/4	125-140	2	4000
24	1-1/2	150-165	2	3000
32	2	X	X	X