

# SPX LOW POUR HYDRAULIC OIL

PREMIUM HIGH VI ANTI-WEAR HYDRAULIC OIL FOR WIDE TEMPERATURE RANGES

SPX Low Pour Hydraulic Oil is a premium, high viscosity index, anti-wear hydraulic oil for use in various industrial and mobile hydraulic systems and applications operating in cold climates or locations subject to wide variations in ambient temperature. It meets the performance requirements of all major pump manufacturers, and is recommended for use in all types of high-pressure, high-speed hydraulic pumps. SPX Low Pour Hydraulic Oil is formulated with high-quality base oils and a zinc anti-wear and anti-oxidant additive package to protect hydraulic system components from wear and to minimize deposit formation providing long service life. The high viscosity index helps maintain oil viscosity at operating temperatures and improves hydraulic system efficiency compared to conventional hydraulic oils.

## Advantages

- High VI to increase hydraulic system efficiency
- Excellent service over a wide temperature range
- Excellent oxidation resistance and thermal stability
- Excellent wear protection for hydraulic pumps and motors
- Protects against rust and corrosion
- Excellent water-separating properties
- Good foam resistance

## Applications

- Hydraulic systems on industrial, mobile, and marine equipment operating in cold weather or in locations subject to temperature fluctuations
- Automated machine tools
- Elevators, hoists, presses, and floor jacks
- Marine cargo winches and steering systems
- Mobile and off-road construction equipment
- Service station lifts
- Chain drives

## Specifications

SPX Low Pour Hydraulic Oil meets the following industry and OEM specifications:

- ISO 11158:1997, Family H (Hydraulic Systems), Type HV
- DIN 51524 Part 3, Anti-wear Hydraulic Oils, Type HVLP
- Parker Hannifin (Denison) HF-0, HF-1, HF-2
- Eaton-Vickers I-286-S, M-2950-S



Industrial



Web: [www.pilotthomas.com](http://www.pilotthomas.com)  
Email: [ptl.orders@pilotthomas.com](mailto:ptl.orders@pilotthomas.com)  
Tel: 844.785.8326



# SPX LOW POUR HYDRAULIC OIL

## TYPICAL PROPERTIES

|   |           |
|---|-----------|
| <b>ISO Grade</b>                                  | <b>32</b> |
| Specific Gravity @ 60°F                           | 0.862     |
| Density, lbs/gal @ 60°F                           | 7.18      |
| Color, ASTM D1500                                 | 0.5       |
| Flash Point (COC), °C (°F)                        | 204(399)  |
| Pour Point, °C (°F)                               | -51(-60)  |
| Viscosity   |           |
| cSt @ 40°C  | 32.0      |
| cSt @ 100°C                                       | 6.7       |
| SUS @ 100°F                                       | 150       |
| SUS @ 210°F                                       | 48.2      |
| Viscosity Index                                   | 173       |
| Acid Number, ASTM D974, mg KOH/g                  | 0.60      |
| Dielectric Strength, ASTM D877, kV <sup>(1)</sup> | 35        |
| Demulsibility, ASTM D1401, min to pass            | 10        |
| Oxidation Stability, TOST, ASTM D943, hours       | >7,000    |
| Copper Corrosion, ASTM D130                       | 1a        |
| Rust Test, ASTM D665 A&B                          | Pass      |
| Zinc, wt %  | >0.06     |

<sup>(1)</sup> At the point of manufacture. In order to maintain dielectric strength, the oil must be kept clean and dry. It is recommended to maintain this product in sealed containers until use.

Minor variations in typical properties data are to be expected in normal manufacturing.

## Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial

