

# SPX SYNTHETIC GEAR OIL EP

PREMIUM SYNTHETIC EXTREME-PRESSURE INDUSTRIAL GEAR OIL

SPX Synthetic Gear Oil EP is a premium quality, full synthetic, extreme-pressure (EP) industrial gear oil developed for the lubrication of heavily loaded enclosed industrial gear drives and heavily loaded plain or rolling element bearings operating under severe service or at extreme temperatures. SPX Synthetic Gear Oil EP is suitable for use over a wider temperature range than conventional mineral based gear oils. It is recommended for use in all applications where the equipment manufacturer specifies a synthetic AGMA EP gear oil.

## Advantages

- High load-carrying capacity for protection against scuffing and wear
- Outstanding oxidation resistance and thermal stability at high temperatures
- Outstanding low temperature properties
- High viscosity index and low pour point for use over wide temperatures
- Suitable for year round use
- Protects against rust and corrosion
- Fast water separation
- Quick foam release
- Extended service intervals compared to mineral based gear oils

## Applications

- Enclosed industrial gear drives operating at very low or very high temperatures, or operating continuously at higher than normal operating temperatures
- Heavily loaded plain and rolling-element bearings operating at extreme temperatures
- Heavily loaded enclosed gear drives and other applications where the equipment manufacturer recommends a high VI, synthetic, extreme-pressure gear oil

## Specifications

SPX Synthetic Gear Oil EP meets the requirements of the following industry specifications:

- ANSI/AGMA Standard 9005-E02, Anti-Scuff/Anti-Wear (EP) Oils
- U.S. Steel 224
- DIN 51517 Part 3
- ISO 12925-1 (CKD)
- Cincinnati Machine



Industrial



Web: [www.pilotthomas.com](http://www.pilotthomas.com)  
Email: [ptl.orders@pilotthomas.com](mailto:ptl.orders@pilotthomas.com)  
Tel: 844.785.8326



# SPX SYNTHETIC GEAR OIL EP

## TYPICAL PROPERTIES

ISO Grade	150	220	320
AGMA Grade	4 EP	5 EP	6 EP
Specific Gravity @ 60°F	0.861	0.865	0.868
Density, lbs/gal @ 60°F	7.17	7.21	7.22
Color, ASTM D1500	0.5	0.5	0.5
Flash Point (COC), °C (°F)	238(460)	238(460)	246(475)
Pour Point, °C (°F)	-44(-47)	-40(-40)	-40(-40)
Viscosity			
cSt @ 40°C	150	220	320
cSt @ 100°C	19.7	26.8	35.7
Viscosity Index	152	155	156
Copper Corrosion, ASTM D130	1b	1b	1b
Rust Prevention, ASTM D665 A&B	Pass	Pass	Pass
Timken OK Load, lbs, ASTM D2782	>90	>90	>90
Four Ball EP, ASTM D2783, Weld Load, kgf	250	250	250
FZG Scuffing Test, ASTM D5182, Failure Load Stage	>12	>12	>12

Minor variations in typical properties data are to be expected in normal manufacturing.

### Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial

