

SPX METHANOL

METHYL ALCOHOL

SPX Methanol is a light, volatile, colorless, flammable, hygroscopic liquid at room temperature.

Applications

- Gas pipeline heaters
- Gas processing
- Gas/Air dehydration
- Natural gas storage
- Gas field gathering
- Line and bath heaters
- Waste heat recovery

TYPICAL PROPERTIES

Color, Pt-Co	5 max
Specific Gravity 20/20°C	0.791-0.793
Methanol, wt%	99.85 min
Ethanol mg/kg	50 max
Acetone, mg/kg	30 max
Water, wt%	0.1 max
Acidity as acetic acid, mg/kg	30 max
Chloride as Cl, mg/kg	0.5 max
Sulphur mg/kg	0.5 max
Carbonisable Substances (Sulfuric Acid Was Test) Pt-Co Scale	30 max
Non Volatile Matter mg/1000 ml	8 max

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com
Email: ptl.orders@pilotthomas.com
Tel: 844.785.8326

Page: 1 of 1
Date: 02.13.20



Industrial

