

SPX ASHLESS GEO

ASHLESS STATIONARY GAS ENGINE OIL

SPX Ashless GEO is an ashless, dispersant detergent gas engine oil for use in naturally aspirated and turbocharged 2-stroke cycle natural gas engines. Engines operating in this type of service typically are found on crude oil and gas transmission pipelines, electrical power generators, gas compressors, irrigation water pumps, and well drilling rigs.

Advantages

- Ashless formulation helps minimize port deposits
- High dispersancy protects against sludge and varnish formation
- Excellent resistance to oxidation and nitration
- Protects against scuffing and wear
- Protects against rust and corrosion
- Does not contain any bright stock, which can cause harmful carbon deposits

Applications

- 2-stroke cycle and some 4-stroke cycle natural gas engines where the manufacturer specifies an ashless gas engine oil

SPX Ashless GEO is recommended for use in natural gas engines manufactured by:

- Ajax
- Climax
- Colt-Fairbanks Morse
- Cooper-Bessemer
- Dresser Clark
- Dresser Rand (Category I, II)
- Worthington



Industrial



Web: www.pilotthomas.com
Email: lubesinfo@pilotthomas.com
Tel: 844.785.8326



SPX ASHLESS GEO

TYPICAL PROPERTIES

SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.883	0.892	0.871
Density, lbs/gal @ 60°F	7.36	7.43	7.26
Color, ASTM D1500	3.0	3.0	3.0
Flash Point (COC), °C (°F)	260(500)	270(518)	240(464)
Pour Point, °C (°F)	-30(-22)	-27(-17)	-40(-40)
Viscosity			
cSt @ 40°C	92.8	142	106
cSt @ 100°C	11.0	14.3	14.4
Viscosity Index	103	98	139
Cold Cranking Viscosity, cP @ (°C)	-	-	6200(-20)
Sulfated Ash, ASTM D874, wt%	<0.01	<0.01	<0.01
Total Base Number (TBN), ASTM D2896	1.3	1.3	1.3
Phosphorus, wt%	0.067	0.067	0.067

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial

