

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 11/19/2017 Revision date: 08/22/2018 Supersedes: 11/19/2017



Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SPX FULL SYN LO-VIS MV ATF
Synonyms

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Passenger car automatic transmission fluid

1.3. Supplier

Manufacturer

Pilot Thomas Logistics
201 North Rupert Street
Fort Worth, TX 76107
T: 844-785-8326
www.pilotthomas.com



1.4. Emergency telephone number

Emergency number PERS: 1-800-633-8253
CUSTOMER #1898

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways

Full text of hazard classes and H-statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) : P301+P310 - If swallowed: Immediately call a poison center or doctor
P331 - Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS-No.) 64742-54-7	<= 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%)	(CAS-No.) 64742-55-8	<= 50	Asp. Tox. 1, H304
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS-No.) 68649-42-3	1 - 5	Eye Irrit. 2A, H319 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.
- First-aid measures after skin contact : Wash skin with mild soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. To prevent aspiration, keep head below knees. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into lungs. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
- Symptoms/effects after eye contact : Eye irritation.
- Symptoms/effects after ingestion : May damage lungs if swallowed and aspirated. Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

- Reactivity : Reacts with : Strong acids. Oxidizer.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Stop leak, if possible without risk. Eliminate ignition sources. Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Stop leak, if possible without risk. Eliminate every possible source of ignition. Ventilate area. Avoid contact with skin and eyes.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Product can accumulate electrostatic charges that may cause fire by electrical discharges. Never use pressure to empty container. Over pressure may rupture containers, cause serious injury, cause or accelerate fire.

Precautions for safe handling : Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Take precautionary measures against static discharge. Store in a well-ventilated place. Keep container tightly closed.

Incompatible materials : Strong oxidizers. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)		
Not applicable		

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Monitoring methods

Monitoring methods (oil)

NIOSH Manual of Analytical Methods, Mixed Cellulose Ester Filter (MCEF) 0.8 microns

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid splashing. Avoid creating mist or spray. Either local exhaust or general room ventilation is usually required.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. VITON gloves. nitrile rubber gloves

Eye protection:

Use splash goggles when eye contact due to splashing is possible

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use an approved respirator equipped with oil/mist cartridges.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Red liquid.
Color	: red
Odor	: petroleum-like odor
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 315 °C
Flash point	: 215 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.01 mm Hg
Relative vapor density at 20 °C	: > 1
Relative density	: 0.89 @ 15.6 °C (60.1°F)
Solubility	: Soluble in organic solvents. insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: 5.9-6.2 cSt @ 100 °C (212°F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong acids and oxidizers.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Do not store with incompatible materials.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 10.5 mg/l/4h

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
LD50 oral rat	26100 mg/kg
ATE US (oral)	26100 mg/kg body weight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 9.5 cSt @ 100 °C (212°F)
Likely routes of exposure	: Dermal.
Potential Adverse human health effects and symptoms	: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Symptoms/effects after ingestion	: May damage lungs if swallowed and aspirated. Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

EC50 Daphnia 1	> 10000 mg/l
----------------	--------------

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

LC50 fish 1	101 mg/l > 100 mg/l LL50. 101 is put in for calculations, per request of IPAC
-------------	---

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LC50 fish 1	10 (10 - 35) mg/l Pimephales promelas OECD GDL 203 (water accomodated fraction)
EC50 Daphnia 1	1 (1 - 1.5) mg/l OECD GDL 202 (water accomodated fraction)
NOEC (acute)	10 mg/l Pimephales promelas OECD GDL 203 (water accomodated fraction)
NOEC chronic crustacea	< 1 mg/l

12.2. Persistence and degradability

SPX SYNTHETIC MULTI-VEHICLE ATF

Persistence and degradability	This product is not expected to be biodegradable.
-------------------------------	---

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste disposal recommendations : If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Distillates (petroleum), hydrotreated light paraffinic (DMSO <3%) (64742-55-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations

⚠ WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Toluene(108-88-3)		X			7000	

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/22/2018
Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>.
Component Supplier SDSs.
Manufacturer Information.

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
IARC: International Agency for Research on Cancer

SPX FULL SYN LO-VIS MV ATF

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50: Lethal Dose for 50% of the test population
STEL: Short Term Exposure Limits
TWA: Time Weighted Average

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:

Section	Changed item	Change	Comments
2.1	Show classification (GHS US)	Added	
2.2		Modified	Modified to be consistent with classification

SDS prepared by:
The Redstone Group, LLC
6077 Frantz Rd. Suite 206
Dublin, OH USA 43017
T 614-923-7472
www.redstonegrp.com.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product