

SPX Endurance Low Ash GEO 40

SDS Number: 61901

Revision Date: 5/15/2020

Page 1 of 3

1	PRODUCT AND COMPANY IDENTIFICATION
----------	---

Vendor

Pilot Thomas Logistics
201 North Rupert Street
Fort Worth, TX 76107



Phone: 1-844-785-8326
Emergency: 1-800-424-9300 (Chemtrec)

Product Identifier: SPX Endurance Low Ash GEO 40
SDS Number: 61901
Product Code: 61901
Revision Date: 5/15/2020
CAS Number: Blend

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Skin corrosion/irritation, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H319 - Causes serious eye irritation
H315 - Causes skin irritation

GHS Precautionary Statements:

P280b - Wear protective gloves/eye protection/face protection.
P302 + P350 - IF ON SKIN: Gently wash with plenty of soap and water.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

3	COMPOSITION/INFORMATION OF INGREDIENTS
----------	---

CAS#	%	Chemical Name:
*****	>90%	Non-hazardous material
64742-54-7	<10%	Mineral Oil, Petroleum Distillates, Hydrotreated (mild) Heavy Paraffinic
*****	<2%	Long chain salicylate, calcium salt (confidential)

SPX Endurance Low Ash GEO 40

SDS Number: 61901

Revision Date: 5/15/2020

Page 2 of 3

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact: Flush with water for several minutes. If effects occur, consult a physician.
Ingestion: Rinse mouth with water. If symptoms develop, obtain medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: >267 C (>513 F)

Suitable extinguishing media: Use dry chemical, CO, water spray (fog) or foam.
 Unsuitable extinguishing media: Do not use water Jet

6 ACCIDENTAL RELEASE MEASURES

Contain spilled material.
 Collect in suitable and properly labeled containers.
 Pick up excess with inert absorbent material
 Keep away from drains and ground water.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
 Keep away from sources of ignition.
 Handle with care and avoid spillage on the floor (slippage).
 Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements: Keep away from sources of ignition.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment: Hand protection: Chemical resistant gloves are recommended.
 Eye protection: Safety glasses with side shields are recommended.
 Respiratory protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber	Odor:	Petroleum-like
Physical State:	Liquid	Solubility:	Nil in water
Spec Grav./Density:	0.88	Freezing/Melting Pt.:	Not available
Viscosity:	15 cSt @ 100 C	Flash Point:	>267 C (>513 F)
Boiling Point:	Not available	Vapor Density:	Not available
Flammability:	Not available	Bulk Density:	7.31 lbs/gal
Partition Coefficient:	Not available	UFL/LFL:	Not available
Vapor Pressure:	Not available		
pH:	Not available		
Evap. Rate:	Not available		
Decomp Temp:	Not available		

SPX Endurance Low Ash GEO 40

SDS Number: 61901

Revision Date: 5/15/2020

Page 3 of 3

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Chemical Stability: Product is stable under normal conditions.
Conditions to Avoid: Excessive temperatures and open flame.
Materials to Avoid: Strong oxidizing agents.
Hazardous Decomposition: Combustion will produce carbon dioxide and, possibly toxic chemicals such as carbon monoxide.
Hazardous Polymerization: Will not occur.

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

Repeated skin contact with this product may cause dermatitis or an oil acne.
 No test data available on product.
 LD50 / LC50 - No data available

Sensitization None known.
Germ Cell Mutagenicity None known.
Carcinogenicity None known
Reproductive toxicity None known.
Specific target organ systemic toxicity (single exposure) None known.
Specific target organ systemic toxicity (repeated exposure) None known.

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

Avoid exposing to the environment, no specific aquatic data available.

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Dispose of waste material in accordance with all local, state/provincial, and national requirements.
 Do not flush to surface water or drains.

14	TRANSPORT INFORMATION
-----------	------------------------------

DOT: Not regulated as a dangerous goods
 IATA: Not regulated as a dangerous goods
 IMDG: Not regulated as a dangerous goods

15	REGULATORY INFORMATION
-----------	-------------------------------

[%] RQ (CAS#) Substance - Reg Codes

 TSCA: All components listed or exempt
 DSL: All components listed or exempt

Regulatory Code Legend

 TSCA = United States Toxic Substance Control Act
 DSL = Canadian Domestic Substance List

16	OTHER INFORMATION
-----------	--------------------------

The information contained in this Safety Data Sheet relates only to the specific material designated. Pilot Thomas Logistics assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Pilot Thomas Logistics.