

SPX PUMP OIL

HIGHLY REFINED BASE OIL FOR MULTIPURPOSE USE

SPX Pump Oil is a highly refined, un-additized mineral base oil for general purpose use. Due to the vigorous refining process, this premium base oil is very pure and crystal clear in color. It can be used as a process oil, flush oil, or in other applications not requiring an additized product. SPX Pump Oil is a light viscosity grade of approximately an SAE 10W which covers the ISO 22 to 32 grade ranges.

Advantages

- Crystal clear and non-staining
- Natural oxidation stability
- Low volatility
- Low aromatics, sulfur, and nitrogen
- Good VI characteristics

Applications

- General purpose lubrication of pumps, bearings, circulating systems etc.
- Once through applications, or flush oil use
- Irrigation drip oil
- Process oil
- Seal oil
- Diluent for blending into other lubricants

TYPICAL PROPERTIES

Specific Gravity @ 60°F	0.843
Density, lbs/gal @ 60°F	7.03
Color, ASTM D1500	<0.5
Flash Point (COC), °C (°F)	208()
Pour Point, °C (°F)	-15(5)
Viscosity	
cSt @ 40°C	21.2
cSt @ 100°C	4.38
Viscosity Index	116

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com
Email: lubesinfo@pilotthomas.com
Tel: 844.785.8326



Page: 1 of 1
Date: 08.21.20



Industrial

