

# SPX COMPRESSOR OIL EB

## COMPRESSOR OIL FOR NATURAL GAS SERVICE

SPX Compressor Oil EB is a high-quality lubricant developed for the lubrication of oil-flooded rotary compressors in natural gas service and for cylinder lubrication in reciprocating compressors in natural gas service. SPX Compressor Oil EB is specially formulated to provide excellent service and protection in gas compression service.

### Advantages

- Excellent oxidation resistance and thermal stability at high temperatures
- Formulated to minimize the effects of gas dilution and oil absorption
- Good wear protection
- Protects against rust and corrosion
- Good foam resistance

### Applications

- Oil-flooded rotary screw, rotary lobe, and rotary vane compressors in natural gas service
- Industrial reciprocating compressors pumping natural gas
- Reciprocating compressors commonly found in remote gas gathering stations



Industrial



Web: [www.pilotthomas.com](http://www.pilotthomas.com)  
Email: [lubesinfo@pilotthomas.com](mailto:lubesinfo@pilotthomas.com)  
Tel: 844.785.8326



# SPX COMPRESSOR OIL EB

## TYPICAL PROPERTIES

<b>ISO Grade</b>	<b>150</b>
Specific Gravity @ 60°F	0.879
Density, lbs/gal @ 60°F	7.32
Color, ASTM D1500	2.5
Flash Point (COC), °C (°F)	277(531)
Pour Point, °C (°F)	-18(0)
Viscosity	
cSt @ 40°C	150
cSt @ 100°C	14.9
SUS @ 100°F	787
SUS @ 210°F	79.3
Viscosity Index	99
Acid Number, ASTM D974, mg KOH/g	0.14
Demulsibility, ASTM D1401, minutes to pass	10
Copper Corrosion, ASTM D130	1a
Rust Test, ASTM D665 A&B	Pass

Minor variations in typical properties data are to be expected in normal manufacturing.

### Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial

