

SPX SUPER HD FULL SYN CK-4

FULL SYNTHETIC DIESEL ENGINE OIL FOR INDUSTRIAL AND MOBILE EQUIPMENT

SPX Super HD Full Syn CK-4 is a premium product that provides excellent protection for engines operating under varying loads and service conditions. It is designed for use in 2007 and newer engines requiring a diesel engine oil that meets EPA regulations and is compatible with exhaust after treatment systems. The premium formulation is backwards serviceable for use in pre-2007 diesel engines as well. In addition, SPX Super HD Full Syn CK-4 allows users to maximize drain intervals, which reduces maintenance expenses and waste oil. SPX Super HD Full Syn CK-4 has good soot dispersancy, wear protection, and an excellent oxidation life to minimize deposit formation.

Advantages

- Good soot control for protection against abrasive wear and soot-induced oil thickening
- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust, bearing corrosion, and wear
- Excellent performance at colder operating temperatures

Applications

- Naturally aspirated and turbocharged four-stroke diesel engines in which the API CK-4 service category is recommended
- Older diesel equipment with conventional, non-EGR or ACERT engines
- Off-highway construction, earth moving, and mining equipment

Specifications

SPX Super HD Full Syn CK-4 is licensed and certified for:

- API CK-4, CJ-4, CI-4 Plus

SPX Super HD Full Syn CK-4 is suitable for use with the following OEMs and specifications:

- Caterpillar ECF-3, ECF-2, ECF-1-a
- Cummins CES 20086
- Detroit Diesel DFS 93K222
- Ford WSS-M2C171-F1
- Mack EOS 4.5
- MTU Type 2.1
- Renault
- Volvo VDS 4.5



Heavy Duty



Web: www.pilotthomas.com
Email: lubesinfo@pilotthomas.com
Tel: 844.785.8326



SPX SUPER HD FULL SYN CK-4

TYPICAL PROPERTIES

SAE Grade	10W-30	5W-40	15W-40
Specific Gravity @ 60°F	0.860	0.855	-
Density, lbs/gal @ 60°F	7.17	7.11	-
Flash Point (COC), °C (°F)	230(446)	250(482)	229(444)
Pour Point, °C (°F)	-45(-49)	-42(-44)	-36(-33)
Viscosity			
cSt @ 40°C	80	80	112
cSt @ 100°C	12.0	13.7	15.5
Viscosity Index	148	150	146
Cold Cranking Viscosity, cP @ (°C)	<6600(-25)	<6600(-20)	<7000(-20)
Sulfated Ash, ASTM D874, wt%	1.00	1.00	1.00
Total Base Number (TBN), ASTM D2896	10.0	11.8	10.0
Phosphorus, wt%	0.080	0.063	0.110
Zinc, wt%	0.090	0.135	0.109

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Heavy Duty

