

SPX SUPER HD CF/CF-2

MONOGRADE DIESEL ENGINE OIL FOR INDUSTRIAL AND MOBILE EQUIPMENT

SPX Super HD CF/CF-2 is designed for use in older diesel engines in both on and off highway applications. SPX Super HD CF/CF-2 is formulated with premium API Group II base stocks and high quality additives containing a balanced amount of dispersant, detergent, antioxidants, anti-wear, and corrosion inhibitors to provide a smoother running engine and extended equipment life.

Advantages

- Good soot control for protection against abrasive wear and soot-induced oil thickening
- Good resistance to viscosity and thermal breakdown at high temperatures
- Protects against rust, bearing corrosion, and wear

Applications

- Older diesel equipment calling for a mono grade diesel engine oil
- 2-cycle diesel engines in heavy duty fleets and marine applications
- Off-highway construction, earth moving, mining, or marine engines calling for an API CF/CF-2 type of engine oil

Specifications

SPX Super HD CF/CF-2 meets the following industry and OEM certifications:

- API CF/CF-2 (SAE 30 & 40)

TYPICAL PROPERTIES

SAE Grade	10W	30	40	50
Specific Gravity @ 60°F	0.882	0.884	0.887	0.888
Density, lbs/gal @ 60°F	7.33	7.35	7.38	7.39
Flash Point (COC), °C (°F)	220(428)	225(437)	230(446)	230(446)
Pour Point, °C (°F)	-30(-22)	-30(-22)	-30(-22)	-20(-4)
Viscosity				
cSt @ 40°C	44.0	98.0	110	190
cSt @ 100°C	7.2	11.0	13.0	17.0
Viscosity Index	112	112	113	105
Sulfated Ash, ASTM D874, wt%	1.08	1.08	1.08	1.08
Total Base Number (TBN), ASTM D2896	6.9	6.9	6.9	6.9

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 10.22.20



Heavy Duty

