

SPX CHAIN OIL

GENERAL PURPOSE LUBRICANT FOR NON-CRITICAL OIL FIELD AND MINING EQUIPMENT

SPX Chain Oil is a mineral oil product for lubrication of non-critical applications including roller chains and sprockets, once-through hydraulics, and other oil field or mining equipment requiring frequent manual lubrication. SPX Chain Oil is suitable for use in other applications where a high viscosity mineral oil is recommended.

Advantages

- Protects against wear
- Protects against rust and corrosion
- Controls costs when used in non-critical applications

Applications

- Once-through applications in mining or oil-field equipment
- Non-critical hydraulic systems
- Roller chains and sprockets
- Chain saws (bar guide, chain, drive sprocket)
- Machine tool guides and slideways

TYPICAL PROPERTIES

SAE Grade	Varies
Specific Gravity @ 60°F	0.878
Density, lbs/gal @ 60°F	7.31
Flash Point (COC), °C (°F)	180(356)
Viscosity	
cSt @ 40°C	68 - 150

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).



Industrial



Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 10.20.20