

SPX COMPRESSOR OIL EB

COMPRESSOR OIL FOR NATURAL GAS SERVICE

SPX Compressor Oil EB is a high-quality lubricant developed for the lubrication of oil-flooded rotary compressors in natural gas service and for cylinder lubrication in reciprocating compressors in natural gas service. SPX Compressor Oil EB is formulated to provide excellent service and protection in gas compression service.

Advantages

- Excellent oxidation resistance and thermal stability at high temperatures
- Formulated to minimize the effects of gas dilution and oil absorption
- Protects against rust and corrosion
- Good foam resistance

Applications

- Oil-flooded rotary screw, rotary lobe, and rotary vane compressors in natural gas service
- Industrial reciprocating compressors pumping natural gas
- Reciprocating compressors commonly found in remote gas gathering stations

TYPICAL PROPERTIES

ISO Grade	150	220
Specific Gravity @ 60°F	0.879	0.881
Density, lbs/gal @ 60°F	7.33	7.35
Color, ASTM D1500	2.5	2.5
Flash Point (COC), °C (°F)	275(527)	275(527)
Pour Point, °C (°F)	-21(-6)	-10(14)
Viscosity		
cSt @ 40°C	150	220
cSt @ 100°C	14.9	19.3
Viscosity Index	98	99
Demulsibility, ASTM D1401, minutes to pass	5	5
Copper Corrosion, ASTM D130	1a	1a
Foam Test, ASTM D892	0/0	0/0

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

Web: www.pilotthomas.com

Email: info@spx-usa.com

Tel: 844.785.8326



Page: 1 of 1

Date: 07.14.21



Industrial

