



SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 05/08/2017 Revision date: 12/13/21 Supersedes: 08/20/2019

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Heat transfer fluid
Restrictions on use : No additional information available

1.3. Supplier

Pilot Thomas Logistics
1051 Mustang Drive, Suite 600
Grapevine, TX 76051
T 844-785-8326
URL www.pilotthomas.com



1.4. Emergency telephone number

Emergency number : PERS: 1-800-633-8253
CUSTOMER #1898

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Acute toxicity (oral), Category 4 H302 Harmful if swallowed.
Specific target organ toxicity — Repeated exposure, Category 2 H373 May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Warning
Hazard statements (GHS) : H302 - Harmful if swallowed.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Precautionary statements (GHS) : P260 - Do not breathe the mist, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P330 - Rinse mouth.
P501 - Dispose of contents/container to Collection point.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS_US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS classification
Ethylene glycol	(CAS-No.) 107-21-1	30 - <100	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
- Symptoms/effects after inhalation : Inhalation may cause: irritation, coughing, shortness of breath.
- Symptoms/effects after ingestion : Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

- Fire hazard : No specific fire or explosion hazard.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use extinguishing media appropriate for surrounding fire. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Avoid all eye and skin contact and do not breathe vapour and mist. Use personal protective equipment as required.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Do not store near food, foodstuffs, drugs, or potable water supplies.
- Incompatible products : Strong bases. Strong acids.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)		
ACGIH	Local name	Ethylene glycol
ACGIH	ACGIH TWA (ppm)	25 ppm (V - Vapor fraction)
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
ACGIH	ACGIH STEL (ppm)	50 ppm (V - Vapor fraction)
ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³
ACGIH	ACGIH Ceiling (ppm)	39.4 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
NIOSH	NIOSH REL (ceiling) (ppm)	50 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid creating mist or spray. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.
- Environmental exposure controls : Prevent leakage or spillage. Prevent contaminated water run-off.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Butyl rubber gloves. Viton

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. If needed, use an air-purifying respirator with organic vapor cartridges and a dust/mist prefilter.

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Pink. clear
Odour	: characteristic. sweet
Odour threshold	: No data available
pH	: 9.2 – 10.3
Melting point	: No data available
Freezing point	: -44 – -13 °C
Boiling point	: ≥ 109 °C
Flash point	: > 116 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 0.01 mm Hg @ 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: 427 °C
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ATE (oral)	521.921 mg/kg bodyweight
Ethylene glycol (107-21-1)	
LD50 dermal rat	> 3500 mg/kg (mouse)
LC50 inhalation rat (mg/l)	> 2.5 mg/l/4h
ATE (oral)	500 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Ethylene glycol (107-21-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day kidney
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Inhalation. Skin and eye contact.
Symptoms/effects	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Symptoms/effects after inhalation	: Inhalation may cause: irritation, coughing, shortness of breath.
Symptoms/effects after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol (107-21-1)	
LC50 fish 1	72860 mg/l Pimephales promelas
EC50 crustacea	> 100 mg/l
NOEC chronic fish	15380 mg/l Pimephales promelas
NOEC chronic crustacea	8590 mg/l Ceriodaphnia sp.

12.2. Persistence and degradability

KOSTChill EG HTF; KOSTChill EG Clear Conc; KOSTChill EG 70/30, 65/35, 60/40, 55/45, 50/50, 45/55, 40/60, 35/65, 30/70	
Persistence and degradability	Large quantities. May cause long-term adverse effects in the environment.
Ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	> 60 % 28 d

12.3. Bioaccumulative potential

KOSTChill EG HTF; KOSTChill EG Clear Conc; KOSTChill EG 70/30, 65/35, 60/40, 55/45, 50/50, 45/55, 40/60, 35/65, 30/70	
Bioaccumulative potential	Not established.
Ethylene glycol (107-21-1)	
Log Pow	- 1.36
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

KOSTChill EG HTF; KOSTChill EG Clear Conc; KOSTChill EG 70/30, 65/35, 60/40, 55/45, 50/50, 45/55, 40/60, 35/65, 30/70	
Ecology - soil	Not established.

12.5. Other adverse effects

Other information	: No additional information available.
-------------------	--

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description : RQ, UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Ethylene Glycol), 9, III
UN-No.(DOT) : UN3082
Proper Shipping Name (DOT) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Ethylene Glycol
Transport hazard class(es) (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



- DOT Symbols : G - Identifies PSN requiring a technical name
Other information : RQ: EG HTF >= 5,219 lbs; Conc Clear >= 5,219 lbs; 70/30 >= 7,142 lbs; 65/35 >= 7,692 lbs; 60/40 >= 8,333 lbs; 55/45 >= 9,090 lbs; 50/50 >= 10,000 lbs; 45/55 >= 11,111 lbs; 40/60 >= 12,500 lbs; 35/65 >= 14,285 lbs; 30/70 >= 16,666 lbs

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Ethylene glycol	CAS-No. 107-21-1	30 - <100%
-----------------	------------------	------------

Ethylene glycol (107-21-1)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

Ethylene glycol (107-21-1)
Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Ethylene glycol (107-21-1)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Ethylene glycol (107-21-1)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Ethylene glycol(107-21-1)		X				8700 µg/day (oral)
Propylene oxide(75-56-9)	X					
Ethylene oxide(75-21-8)	X	X	X	X	2 µg/day	20 µg/day

Component	State or local regulations
Ethylene glycol(107-21-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End-use applications **NOT** supported by KOST® USA, Inc. for monoethylene glycol, diethylene glycol and triethylene glycol. These limitations include products restricted by law, applications in which may raise unacceptable risks, and other applications which KOST® USA, Inc. has decided not to, including minimizing unnecessary risk and liabilities to the company. KOST® USA, Inc. does not knowingly market these products into these non-supported applications. This list is not all-inclusive, and KOST® USA, Inc. reserves the right to modify the same at any time.

- The use of production of tobacco and in the manufacture of tobacco products (including but not limited to additives, humectants, filters, inks, and paper)
- The use for the generation of artificial smoke / theatrical fogs / mist. This includes applications such as artificial / e-cigarettes.
- The use as ingredient in fuel for warming foods (Sterno™-like application) or in fuel for heating an enclosed space where human exposure is possible.
- The use in fire extinguishing sprinkler systems.
- The use in the manufacture of munitions.
- The use in the production of de-icers for use on roadways, sidewalks and in aircraft lavatories.
- The use as a component of heat transfer fluids in systems where the heat transfer fluids could infiltrate (i.e., via an exchanger leak, backflow prevention failure, or other means) a potable water.
- The use as a non-reacted component in a formulation for direct internal or external human / animal contact, including, but not limited to ingestion, inhalation, and skin contact and in medical / veterinary devices and medial / veterinary. Examples of some such applications are uses as a direct component in foods, beverages, pharmaceuticals, cosmetics, personal care products or children's products.
- The use for consumer or hospital usage for deodorizing or air "purifying" purposes by spraying as an aerosol.
- The use as a non-reacted component in adhesives, plasticizers, and softening agents for packaging having direct contact with food or beverage.

SPX ETHYLENE GLYCOL 100%, 80%, 50%, 30%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- The use as a non-reacted component in the formulation of glues, pastes, ice / heat packs or other items where the potential for significant human contact and/or ingestion exists (including but not limited to children's school glue/paste or arts/craft glue/paste, toys, children products).
- The use as a fluid for pressure testing piping.

For more information contact your KOST® USA, Inc. representative.

Revision date : 01/27/2020
Data sources : European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
Other information : None.


Full text of H-statements:

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	DNEL: Derived No Effect Level
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals)
	LD50: Lethal Dose for 50% of the test population
	NOEC: No Observable Effect Concentration
	OSHA: Occupational Safety & Health Administration
	PBT: Persistent, Bioaccumulative, Toxic
	PNEC: Predicted No Effect Level
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Product identifier. General information. Composition/information on ingredients.

SDS Prepared by: The Redstone Group
110 Polaris Pkwy
Suite 200
Westerville, OH USA 43082
P: +1 (614) 923-7472
www.redstonegrp.com