BustApart™

Where Performance Meets Prevention.

BUSTAPART™ MOLY AEROSOL

BustApart™ Moly Aerosol is a molybdenum disulfide dry film lubricant that withstands high pressures and temperatures. Lubricates moving parts of all kinds. Fast drying with minimal transfer. Protects from rusting and corrosion by displacing moisture. Reduces metal to metal contact on treated surfaces. Service temperatures range from -40°F to 600°F. Convenient aerosol is ideal for lubricating surfaces where a liquid lubricant is not practical.

BustApart™ Moly Aerosol was designed for lubrication of all metal moving parts including high speed gears, machine tools, pump assemblies, conveyors, bearings, wire cable, pipe, engines, heavy equipment, and exposed metal parts. Areas of use include industrial plants, oil rigs, pipe yards, construction areas, machine shops, farm equipment, repair services, office machines, aircraft manufacturers and suppliers, and commercial printers.

DANGER

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

HEALTH AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment. As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted into a collection vessel and not allowed to soak into the ground or enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, wipe up or scrape up product and deposit in a sealable container. Thoroughly clean area with detergent solutions and rinse well with water.

⚠ WARNING!

Prolonged or repeated skin contact may cause irritation. Use protective wear to avoid eye and skin contact. Wash thoroughly after use. For skin contact, wash with soap and water. If swallowed, seek medical attention immediately. For eye contact, flush with water for 15 minutes and contact a physician. For additional information read the Safety Data Sheet for this product. **KEEP OUT OF REACH OF CHILDREN.**

⚠ **WARNING: This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.**

AVAILABLE PACKAGING SIZES

12 OZ AEROSOL | 1 LB BRUSHTOP | 35 LB PAIL | 120 LB KEG

PRIMARY INDUSTRIES

AUTOMOTIVE | CONSTRUCTION | DRILLING | MAINTENANCE | MINING

TECHNICAL DATA

TEST	BUSTAPART™ MOLY
FORM	SOLVENT-BASED AEROSOL
ODOR	MILD SWEET
COLOR	BLACK
DETERGENCY	NONE
TOXICITY	25 PPM OSHA TLV
WETTING ABILITY	N/A
STORAGE STABILITY	1 YEAR
COLD STABILITY	0°F
PHOSPHATES	NONE
FLASH POINT	N/A
FLAME EXTENSION	12"
SOLUBILITY IN WATER	IMMISCIBLE
SPECIFIC GRAVITY	1.29
% VOLATILE BY VOLUME	96%
pH	N/A
PROPELLANT	HYDROCARBON
EVAPORATION RATE	SLOW
BIODEGRADABILITY	NO

CONTAINS (CAS#): Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Isopropyl Alcohol (67-63-0), Molybdenum Disulfide (1317-33-5), Organophilic Clay (N/A)

GreaseCo
1101 Cumberland Dr.
Valparaiso, IN 46383
www.GreaseCo.com