

# SMARTank ST95 LTE

## Intrinsically Safe Wireless Monitoring Solution

The SMARTank™ ST95 cellular remote monitoring system combines several industry-first features that redefine what's possible with monitoring chemical inventory in Class 1, Division 1, Group D Hazardous Locations. Now with SkyBitz Tank Monitoring and SMARTank, plant operators and management can maximize employee and plant safety and monitor tanks in hazardous locations remotely for critical level, location, daily usage history information and more, without actually being in those hazardous areas. Specifically engineered for a low profile and to be intrinsically safe, the SMARTank ST95 system performs where others can't.

Discover how the ST95 monitoring system can help you maximize chemical distribution efficiency in plant areas that require Class 1, Div 1 certified electronics.

## We Make Tanks in Hazardous Locations Talk

Our single-source combination of IS hardware, software and data service provides secure key tank information 24/7. In the office or in the field, you'll know the tank level, precisely where it is, and when replenishment is needed. This helps maximize operating efficiency by eliminating run-outs, having to make costly emergency deliveries and avoiding losing the asset. It also helps you optimize plant and employee safety practices.

## Lowest Profile in the Industry

The unique, low-profile domed design of the SMARTank ST95 minimizes the height of the exposed part of the device to less than two and one-half inches above the vessel. The electronics are housed safely in the portion of the device recessed within the tank, and the antennae are under the domed cover. So, whether your tanks/totes are stacked or not, the hardware is out of harm's way.

## We Speak Intrinsic Safety

The SMARTank ST95 can be used in Class 1, Div 1, Group D Hazardous Locations, and is certified Intrinsically Safe by CSA Group. Vented tanks call for the use of gauge sensors, while unvented tanks will most often utilize absolute sensors. All electronics reside inside the enclosure – even the cellular antenna.

## Engineered for Ruggedness, Safety and Ease of Use

Reduced current consumption, OTA firmware updates and a tamper-evident enclosure with an internal antenna all combine to improve battery life, make updates seamless and enhance chemical compatibility and security, while delivering critical tank information to users 24/7.

Contact us for a detailed consultation, recommendation and quote on the ST95 wireless monitoring system for use in Class 1, Div 1 Hazardous Locations, and to find out how our total solution increases operating efficiency, reduces distribution costs and complies with OSHA and your company's safe operating procedures.



## Key Features

Certified for use in Class 1, Division 1, Group D Hazardous Locations, in vented & unvented tanks where intrinsically safe electronics are required.

Low profile domed form factor, ideal for monitoring stackable tanks, totes and shipping containers. Available with dual sensor configuration for unvented tanks (gasoline), as shown here.

Innovative enclosure and internal antennae for enhanced chemical compatibility and ruggedness.

Monitor can be removed and redeployed.

Leverages technology that operates on 3G/4G cellular networks, for longevity after the 2G Sunset.

Integrated GPS functionality for precise asset locating. Firmware updates are completed over-the-air without user involvement.

## Hardware Specifications

### Physical

Construction:	ROHS Compliant
Enclosures:	NEMA 4X; weatherproof, flame resistant Lexan top, CPVC base (UL94V-0), or stainless steel 316 model
Process Fitting:	Simultaneous 2" NPT and 2" Buttress
Unit Gross Weight:	1.3 lbs (454g)

### Wireless Communications

Mode:	LTE 4G Digital Wireless Radio with 3G fallback
RF Approval:	FCC Part 15 B approved
Frequency Bands:	FCC Part 15 B approved
GPS Receiver:	LTE 700/850/AWS1700/1900MHz

### Performance

Output Voltage:	Internal Antenna
Output Current:	Nominally 14V/24V
Load Regulation:	Rated from 0-50mA
Battery Powered:	0.5% from @ 30mA load
Output Short Circuit Protection:	7.4 VDC max
Accuracy:	Current limited to 50 mA

### Environmental

Operating Temperature:	+/-0.25%, +/-0.50%, +/-1.0% based on requirements Code T3C: -13°F to 104°F (-25°C to 40°C)
Storage Temperature:	-40°F to 185°F (-40°C to -85°C)

## Key Benefits of the SMARTank TL95

- Critical tank data available 24/7 without entering the Hazardous Location, via our SMARTank Tank Level and Analytics Portal - Mobile App available too
- Industry's lowest profile – all parts protected
- Choice of enclosure to ensure compatibility
- Low cost cellular technology
- Excellent battery life and OTA firmware updates
- Secure, reliable access to tank information when and where you need it