

FIBER CLEANING CASSETTES & PENS

PS444814-1001-RX



The PS444814-1001-RX is a NEMA Type 3R (Rainproof) enclosure with UL certification pending. The 1/8" Welded Aluminum Construction provides a lightweight and durable product. Front and Side access provided with separate compartments. The Pad Mounted Enclosure Base includes removable front panel (accessible only with the Front Door open) that is vented to allow optimum airflow throughout the entire enclosure.

Powder Coated Finish

- Meets GR-487 Requirements for "Paint Adhesion After Exposure" (25" Inches of Scribe Length Per ASTM 1654, 720 Hours Salt Fog per ASTM B117)
- Impact resistant beyond 140 in-lbs (18J) when tested in accordance with ASTM D 2794.
- Humidity Resistance (25" Inches of Scribe Length Per ASTM 1654, 100 Hours Salt Fog per ASTM B117, No Blistering under evaluation to ASTM D714)

Gasket & Seals

- Front Door and Side Access Door seal with EPDM Self Gripping Gaskets (UL® Recognized Component for Canada and the United States)

Locks

- Front Door and Side Access Door contain 2- Quarter Turn Locks (1 Padlock housing on each door)
- Watertight and dustproof to industrial protection rating IP65
- Different Lock Styles and Handle Options available
- Lock Housings are Zinc Die Chrome and/or Zinc Die Powder Coated

FIBER CLEANING CASSETTES & PENS

Wind Latch

- Stainless Steel self-activating (manual release) wind latch holds the front door open at 90 degrees.
- Wind Latch system tested per GR-487 Requirements for Dynamic Wind Tests up to 50mph (22 m/sec).

Manufacturing Facility

- ISO 9001:2000 Registered Manufacturing Facility
- "On-site" UL approved Rain Testing capabilities
- Manufacturer of UL 50 Approved cabinets for NEMA Type 1 and Type 3R (rainproof)



139 Dearborn Place, Waterloo, ON N2J 4N5
1-877-900-7996 phone: 519.748.4411 fax: 519.748.0466
customerservice@connect-telcom.com

www.connect-telcom.com