





TECHNICAL SPECIFICATIONS MODEL # DVEB-64


Designed for finished exterior systems such as **Flush Precast Exterior**











MODEL # DVEB-64-F

PERFORMANCE DATA

FOR USE

- Bathroom exhaust
- Dryer exhaust
- Kitchen hood exhaust
- Fresh air make-up

MATERIALS

- · Constructed from high temperature plastic polymers
- · Material tested for use on high temperature appliance devices or components. (max sustainable operational temperature at 235°)
- · All materials are UL compliant to UL723 flame spread rating and ASTM E84 standards
- · Devices that require exterior exhaust or intake · All components made and fully assembled in the USA

GENERAL INFORMATION

BENEFITS

- Prevents exterior air from entering interior area Interior monolithic cavity, positive pitch sidewalls
- Prevents mold & mildew*
- Eliminates water intrusion**
- Sold assembled
- · Single step installation
- · Greatly reduces labor cost
- Fits duct sizes up to 4" & 6" diameter ducts
- 100% non corrosive material
- · Box cavity designed not to interfere with structural design

FEATURES

- · Mounted flush with exterior building surface
- Paintable, primer required
- · Gravity back draft dampers
- Removable front louver for periodic maintenance and inspections
- · Face louver is attached with six stainless steel screws
- Impact resistant
- UV stabilized
- · Available in White or Custom colors

XVENTBOX - U.S.PATENTS 8,888,574 MADE IN THE USA VERSION: 06-08

^{*} with proper interior environmental conditions

^{**} in accordance with manufacturer recommendations, connected to a ducted system