# TECHNICAL SPECIFICATIONS
# MODEL # 4-ILS-12H

**The Inline Sleeve was designed to replace existing wall caps, or as an original installation where our exhaust boxes cannot be utilized**

FRONT VIEW




REAR VIEW




SECTIONAL VIEW






## MODEL #4-ILS-12H
PERFORMANCE DATA

FOR USE
- Bathroom exhaust
- Dryer exhaust
- Kitchen hood exhaust
- Fresh air make-up
- Devices that require exterior exhaust or intake

MATERIALS
- Constructed from high temperature plastic polymers
- Material tested for use on high temperature appliance devices or components. (max sustainable operational temperature at 235°)
- All materials are UL compliant to UL723 flame spread rating and ASTM E84 standards
- All components made and fully assembled in the USA

## GENERAL INFORMATION

BENEFITS
- Prevents exterior air from entering interior area
- Prevents mold & mildew*
- Eliminates water intrusion**
- Sold assembled
- Single step installation
- Greatly reduces labor cost
- Fits (1) 4" diameter duct
- 100% non corrosive material
- Box cavity designed not to interfere with structural design

FEATURES
- Interior monolithic cavity, positive pitch sidewalls
- Mounted flush with exterior building surface
- Paintable, primer required
- Gravity back draft dampers
- Removable front louver for periodic maintenance and inspections
- Face louver is attached with six stainless steel screws
- Impact resistant
- UV stabilized
- Available in White or Custom colors

* with proper interior environmental conditions
** in accordance with manufacturer recommendations, connected to a ducted system