

SEALANTS, CAULKING & FLOORING

105 Tac-Kote



Read Safety Data Sheet before using this product.

DESCRIPTION: 105 Tac-Kote is a cold applied asphalt cut-back designed specifically as a primer/adhesive for use under asphalt based roadways.

USES: 105 Tac-Kote is specifically used as a primer/adhesive for use under asphalt based roadways. The product penetrates capillaries to bind and seal dusty surfaces to provide the correct base for subsequent toppings.

SURFACE PREPARATIONS: Surfaces to be treated with 105 Tac-Kote should be oil and moisture free in order to assure proper penetration. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

APPLICATION: 105 Tac-Kote is easily applied by brush, squeegee or spray. Apply at the rate of 1 to 1.5 gallons per 100 sq. ft. Actual rate may vary due to the nature of the substrate.

COVERAGE RATE: Apply at the rate of 1 to 1.5 gallons per 100 sq. ft.

CAUTION: Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Store in a heated room and keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Exterior use only.

PACKAGING: Available in 5-gallon pails and 55-gallon drums.

If further information is needed, contact KARNAK Technical services at 800-526-4236.

PHYSICAL PROPERTIES & SPECIFICATIONS

Weight per Gallon: 7.56 lbs.

Solids by Weight: 75% Nominal

Solids by Volume: 71% Nominal

Color: Black

Application Temp.: 40°F to 120°F

Dry Time: 8 to 24 hours

VOC Content: 230 g/L MAX

ASTM D2028 RC-250

AASHTO M-81