

SDS Revision Date: 12/01/2019

1. Identification

1.1. Product identifier

Product Identity Karnak 168 Tar Roof Restaurant

Alternate Names Karnak 168 Tar Roof Restaurant, Product Code:0052

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Roof Coating

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Karnak Corporation

330 Central Ave.

Clark, NJ 07066 USA

Emergency

CHEMTREC (USA) (800) 424-9300

24 hour Emergency Telephone No.OUTSIDE THE U.S AND CANADA 1-202-483-7616

Customer Service: Karnak Corporation 1-800-526-4236

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

Skin Irrit. 2;H315 Causes skin irritation.

Eye Irrit. 2;H319 Causes serious eye irritation.
Muta. 1B;H340 May cause genetic defects.

Carc. 1A;H350 May cause cancer.

Repr. 1B;H360FD May damage fertility. May damage the unborn child.

Aquatic Chronic 1;H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

KARNAK THE SEAL OF QUALITY **SDS Revision Date:**

12/01/2019

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H360FD* May damage fertility. May damage the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P321 Specific treatment (see information on this label).

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

P391 Collect spillage.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.



SDS Revision Date: 12/01/2019

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes	
Coal tar pitch CAS Number: 0065996-93-2	50 - 75	Carc. 1A;H350 Muta. 1B;H340 Repr. 1B;H360Fd Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1][2][3]	
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	10 - 25	Asp. Tox. 1;H304	[1]	
Filler and Fiber CAS Number: MixtureFF	5 - 10	Not classified	[1]	
1-Propanamine, 3-(isodecyloxy)-, acetate CAS Number: 0028701-67-9	1 - 5	Acute Tox. 4;H302 Skin Corr. 1B;H314 Aquatic Chronic 1;H410	[1]	

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin If this product comes in contact with skin, remove material with mineral oil, then wash with

soap and plenty of water.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

^[1] Substance classified with a health or environmental hazard.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

KARNAK
THE SEAL OF QUALITY

SDS Revision Date:

12/01/2019

4.2. Most important symptoms and effects, both acute and delayed

Overview Fumes from product can be unpleasant, may cause nausea, headache and irritating to

eyes, skin, and respiratory tract. Reproductive or genetic defect hazard. See section 2 for

further details.

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Water spray, carbon dioxide, dry chemical, foam

5.2. Special hazards arising from the substance or mixture

Avoid contact with skin and eyes. Avoid inhalation of vapors. Eliminate sources of ignition. Ensure adequate ventilation.

Hazardous decomposition: Combustion causes toxic fumes. Combustion products: Nitrogen oxides, oxides of carbon, sulfur oxides.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

ERG Guide No. 130

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Avoid contact with skin and eyes. Avoid inhalation of vapors. Eliminate sources of ignition. Ensure adequate ventilation.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove



SDS Revision Date:

12/01/2019

soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid contact with skin and eyes. Avoid inhalation of vapors. Eliminate sources of ignition. Ensure adequate ventilation.

Contain spillages with sand, earth or any suitable adsorbent material. Contaminated adsorbent must be removed in sealed, plastic lined drums and disposed of via an authorized waste disposal contractor.

Keep product out of sewers and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers or waterways. Assure conformity with applicable governmental regulations.

7. Handling and storage

7.1. Precautions for safe handling

Eliminate sources of ignition. Ensure adequate ventilation. Avoid contact with skin and eyes. Avoid inhalation of vapors. Avoid release to the environment.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store at room temperature or in cool area.

Incompatible materials: Strong Oxidizers

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0028701-67-9 1-Propanamine, 3-(isodecyloxy)-, acetate	1-Propanamine, 3-(isodecyloxy)-, acetate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
	Supplier	No Established Limit	
O064742-95-6 Solvent naphtha (petroleum), light aromatic	, ,,	OSHA	No Established Limit
	aromatic	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0065996-93-2	Coal tar pitch	OSHA	TWA 0.2 mg/m3 (benzene-soluble fraction) [1910.1002]
		ACGIH	TWA: 0.2 mg/m3 A1, 1, Revised 2006,
		NIOSH	Ca TWA 0.1 mg/m3 (cyclohexane-extractable fraction)



SDS Revision Date:

12/01/2019

		Supplier	No Established Limit
MixtureFF	Filler and Fiber	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0028701-67-9 1-Propanamine, 3-(isodecyloxy)-, acetate	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0064742-95-6 Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0065996-93-2 Coal tar pitch	OSHA	Select Carcinogen: No	
	NTP	Known: Yes; Suspected: Yes	
	IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
MixtureFF Filler and Fiber		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory Use supplied-air respirator in confined areas or with vapors in high concentrations.

Eyes Wear protective eye glasses for protection against liquid splashes.

Skin Avoid skin contact. Wear suitable protective clothing and gloves. Gloves should be

changed if excessive exposure has occurred.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Black Paste

Odor Petroleum hydrocarbon

Odor thresholdNot determinedpHNot MeasuredMelting point / freezing pointNot Measured



SDS Revision Date: 12/01/2019

Initial boiling point and boiling range

Flash Point

Evaporation rate (Ether = 1) Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapor pressure (Pa)

Vapor Density Specific Gravity Solubility in Water

Partition coefficient n-octanol/water (Log Kow)
Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

Density

9.2. Other information

No other relevant information.

> 152 °C (> 306 °F)

> 40.6 °C(> 105 °F) [Closed cup]

Not available Not Applicable

Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured

Not determined Not available Not available. Negligible Not Measured

Not Measured Not Measured

Kinematic Viscosity (cSt) @ 40 °C > 20.5

1.10

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

High temperatures and fires.

10.5. Incompatible materials

Strong Oxidizers

10.6. Hazardous decomposition products

Combustion causes toxic fumes. Combustion products: Nitrogen oxides, oxides of carbon, sulfur oxides.

SDS Revision Date:

12/01/2019



11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Coal tar pitch - (65996-93-2)	3,300.00, Rat - Category: 5	5,000.00, Rat - Category: 5	No data available	No data available	No data available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	No data available
Filler and Fiber - (MixtureFF)	No data available	No data available	No data available	No data available	No data available
1-Propanamine, 3-(isodecyloxy)-, acetate - (28701-67-9)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity	1B	May cause genetic defects.
Carcinogenicity	1A	May cause cancer.
Reproductive toxicity	1B	May damage fertility. May damage the unborn child.
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.



SDS Revision Date:

12/01/2019

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Coal tar pitch - (65996-93-2)	128.00, Pagrus major	> 100.00, Daphnia magna	220.00 (72 hr), Desmodesmus subspicatus
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Filler and Fiber - (MixtureFF)	Not Available	Not Available	Not Available
1-Propanamine, 3-(isodecyloxy)-, acetate - (28701-67-9)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) **Transportation**) UN1999 14.1. **UN** number UN1999 UN1999 14.2. UN proper shipping UN1999, Tars, liquid, 3, III Tars, liquid Tars, liquid name 14.3. Transport hazard **DOT Hazard Class: 3** IMDG: 3 Air Class: 3 Sub Class: Not Applicable class(es) 14.4. Packing group Ш Ш Ш

14.5. Environmental hazards

IMDG Marine Pollutant: Yes; (Coal tar pitch)



SDS Revision Date:

12/01/2019

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory. B3 D2A

WHMIS Classification B
US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No te (Acute): Yes

Immediate (Acute): Yes Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Coal tar pitch

Pennsylvania RTK Substances (>1%):

Coal tar pitch



SDS Revision Date:

12/01/2019

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H340 May cause genetic defects.

H350 May cause cancer.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Disclaimer: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The information has been completed to the best of our knowledge and is believed to be accurate and reliable as from the date indicated. However, no warranty is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for his own particular use.

End of Document