



AS WELL AS OUR CORE FLEET, UPA CAN ALSO PROVIDE:

SPIDERLIFTS > TRUCKMOUNTS > TELEHANDLERS > PLANT > GENERATORS STORAGE AND WELFARE UNITS
HEATING > COOLING > TOOLING

ELECTRIC BOOM LIFTS				DIESEL BOOM LIFTS				HYBRID BOOM LIFTS			
Name: HR12 Narrow D/E	Name: HR15 Narrow D/E	Name: HR21 Electric 4x4	Name: HR12 Diesel 4x4	Name: HR21 Diesel 4x4	Name: S163 AJ	Name: 280 TJ	Name: HR12 D/E 4x4	Name: HR17 Hybrid 4x4	Name: HR21 Hybrid 4x4	Name: HR21 Hybrid 4x4	Name: HR21 Hybrid 4x4
Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Skyjack	Manufacturer: Manitou	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift	Manufacturer: Niftylift
Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts	Type: Boom Lifts
Power: Battery/ Bi-energy	Power: Battery/ Bi-energy	Power: Battery	Power: Diesel	Power: Diesel	Power: Diesel	Power: Diesel	Power: Hybrid	Power: Hybrid	Power: Hybrid	Power: Hybrid	Power: Hybrid
Platform Height: 10.20m	Platform Height: 13.50m	Platform Height: 18.80m	Platform Height: 10.20m	Platform Height: 18.80m	Platform Height: 19.38m	Platform Height: 21.21m	Platform Height: 10.20m	Platform Height: 15.20m	Platform Height: 18.80m	Platform Height: 18.80m	Platform Height: 18.80m
Working Height: 12.20m (40feet)	Working Height: 15.50m (51feet)	Working Height: 20.80m (69feet)	Working Height: 12.20m (40feet)	Working Height: 20.80m (69feet)	Working Height: 21.21m (70feet)	Working Height: 27.55m (91feet)	Working Height: 12.20m (40feet)	Working Height: 17.20m (56feet)	Working Height: 20.80m (69feet)	Working Height: 20.80m (69feet)	Working Height: 20.80m (69feet)
Working Reach: 6.10m	Working Reach: 9.70m	Working Reach: 12.80m	Working Reach: 6.10m	Working Reach: 12.80m	Working Reach: 12.80m	Working Reach: 12.19m	Working Reach: 6.10m	Working Reach: 9.40m	Working Reach: 12.80m	Working Reach: 12.80m	Working Reach: 12.80m
Platform Dimensions: 1.10 x 0.65m	Platform Dimensions: 1.50 x 0.80m	Platform Dimensions: 1.80 x 0.85m	Platform Dimensions: 1.10 x 0.65m	Platform Dimensions: 1.80 x 0.85m	Platform Dimensions: 2.40 x 0.91m	Platform Dimensions: 2.30 x 0.90m	Platform Dimensions: 1.10 x 0.65m	Platform Dimensions: 1.80 x 0.85m	Platform Dimensions: 1.80 x 0.85m	Platform Dimensions: 1.80 x 0.85m	Platform Dimensions: 1.80 x 0.85m
Safe Working Load: 200kg	Safe Working Load: 225kg	Safe Working Load: 225kg	Safe Working Load: 200kg	Safe Working Load: 225kg	Safe Working Load: 225kg	Safe Working Load: 350kg	Safe Working Load: 200kg	Safe Working Load: 225kg	Safe Working Load: 225kg	Safe Working Load: 225kg	Safe Working Load: 225kg
Stowed Height: 1.90m	Stowed Height: 1.99m	Stowed Height: 2.15m	Stowed Height: 1.95m	Stowed Height: 2.15m	Stowed Height: 2.54m	Stowed Height: 2.15m	Stowed Height: 1.95m	Stowed Height: 2.10m	Stowed Height: 2.15m	Stowed Height: 2.15m	Stowed Height: 2.15m
Closed Dimensions: 4.10 x 1.50m	Closed Dimensions: 6.40 x 1.50m	Closed Dimensions: 6.70 x 2.27m	Closed Dimensions: 4.10 x 1.60m	Closed Dimensions: 6.70 x 2.27m	Closed Dimensions: 9.34 x 2.44m	Closed Dimensions: 8.04 x 2.27m	Closed Dimensions: 4.10 x 1.60m	Closed Dimensions: 6.30 x 2.00m	Closed Dimensions: 6.70 x 2.27m	Closed Dimensions: 6.70 x 2.27m	Closed Dimensions: 6.70 x 2.27m
Machine Weight: 3100kg	Machine Weight: 6700kg	Machine Weight: 6500kg	Machine Weight: 3330kg	Machine Weight: 6500kg	Machine Weight: 9616kg	Machine Weight: 16500kg	Machine Weight: 3500kg	Machine Weight: 4750kg	Machine Weight: 6500kg	Machine Weight: 6500kg	Machine Weight: 6500kg

ELECTRIC SCISSOR LIFTS						DIESEL SCISSOR LIFTS					
Name: 32/19	Name: 32/26	Name: 46/26	Name: 46/32	Name: 47/40	Name: 68/26	Name: 68/32 Diesel	Name: 88/41	Name: 90/50	Name: 16/23	Name: 16/23	Name: 16/23
Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: Skyjack	Manufacturer: LGMG	Manufacturer: LGMG
Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts	Type: Scissor Lifts
Power: Electric	Power: Electric	Power: Electric	Power: Electric	Power: Electric	Power: Diesel	Power: Diesel	Power: Diesel	Power: Diesel	Power: Diesel	Power: Diesel	Power: Diesel
Platform Height: 5.79m	Platform Height: 7.92m	Platform Height: 7.92m	Platform Height: 9.75m	Platform Height: 11.80m	Platform Height: 9.75m	Platform Height: 9.75m	Platform Height: 12.50m	Platform Height: 15.24m	Platform Height: 16.00m	Platform Height: 16.00m	Platform Height: 16.00m
Working Height: 7.62m (25feet)	Working Height: 9.92m (32feet)	Working Height: 9.75m (32feet)	Working Height: 11.58m (38feet)	Working Height: 13.80m (45feet)	Working Height: 9.75m (32feet)	Working Height: 11.75m (38feet)	Working Height: 14.50m (47feet)	Working Height: 17.24m (56feet)	Working Height: 18.00m (59feet)	Working Height: 18.00m (59feet)	Working Height: 18.00m (59feet)
Platform Dimensions: 1.63 x 0.66m	Platform Dimensions: 2.13 x 0.71m	Platform Dimensions: 2.13 x 1.07m	Platform Dimensions: 2.13 x 1.07m	Platform Dimensions: 2.19 x 1.06m	Platform Dimensions: 2.44 x 1.42m	Platform Dimensions: 2.44 x 1.42m	Platform Dimensions: 3.40 x 1.20m	Platform Dimensions: 4.30 x 1.88m	Platform Dimensions: 4.30 x 1.88m	Platform Dimensions: 4.30 x 1.88m	Platform Dimensions: 4.30 x 1.88m
Extended Platform: 2.54 x 0.66m	Extended Platform: 3.04 x 0.71m	Extended Platform: 3.35 x 1.07m	Extended Platform: 3.35 x 1.07m	Extended Platform: 3.09 x 1.06m	Extended Platform: 3.96 x 1.42m	Extended Platform: 3.90 x 1.40m	Extended Platform: 5.70 x 1.70m	Extended Platform: 7.21 x 1.88m	Extended Platform: 7.21 x 1.88m	Extended Platform: 7.21 x 1.88m	Extended Platform: 7.21 x 1.88m
Safe Working Load: 227kg	Safe Working Load: 227kg	Safe Working Load: 454kg	Safe Working Load: 319kg	Safe Working Load: 350kg	Safe Working Load: 454kg	Safe Working Load: 454kg	Safe Working Load: 681kg	Safe Working Load: 681kg	Safe Working Load: 681kg	Safe Working Load: 681kg	Safe Working Load: 681kg
Lift Cycles: 132	Lift Cycles: 132	Lift Cycles: 132	Lift Cycles: 132	Lift Cycles: 45	Handrails Lowered: 1.60m	Handrails Lowered: 1.80m	Handrails Lowered: 2.20m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m
Handrails Lowered: 1.60m	Handrails Lowered: 1.90m	Handrails Lowered: 1.79m	Handrails Lowered: 1.90m	Handrails Lowered: 2.21m	Handrails Lowered: 1.60m	Handrails Lowered: 1.80m	Handrails Lowered: 2.20m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m	Handrails Lowered: 2.30m
Closed Dimensions: 1.80 x 0.80m	Closed Dimensions: 2.30 x 0.80m	Closed Dimensions: 2.31 x 1.17m	Closed Dimensions: 2.31 x 1.17m	Closed Dimensions: 2.40 x 1.19m	Closed Dimensions: 2.70 x 1.70m	Closed Dimensions: 2.70 x 1.70m	Closed Dimensions: 3.50 x 2.20m	Closed Dimensions: 4.50 x 2.30m	Closed Dimensions: 4.50 x 2.30m	Closed Dimensions: 4.50 x 2.30m	Closed Dimensions: 4.50 x 2.30m
Machine Weight: 1312kg	Machine Weight: 1890kg	Machine Weight: 2170kg	Machine Weight: 2302kg	Machine Weight: 3400kg	Machine Weight: 3305kg	Machine Weight: 3473kg	Machine Weight: 6173kg	Machine Weight: 7407kg	Machine Weight: 8000kg	Machine Weight: 8000kg	Machine Weight: 8000kg

PUSH AROUNDS			ELECTRIC VERTICAL MAST LIFTS		
Name: 10 IQ	Name: SI 16	Name: 100 VR	Name: M 26-4	Name: M 30-4	Name: Fuelcube
Manufacturer: Pop Pro	Manufacturer: Skyjack	Manufacturer: Manitou	Manufacturer: Manitou	Manufacturer: Manitou	Manufacturer: Fuel Proof
Type: Push Around	Type: Vertical Masts	Type: Vertical Masts	Type: Forklifts	Type: Forklifts	Type: Fuel Proof
Power: Electric	Power: Electric	Power: Electric	Power: Diesel	Power: Diesel	Power: Fuel Proof
Platform Height: 3.0m	Platform Height: 4.75m	Platform Height: 7.90m	Max. capacity: 2600kg	Max. capacity: 3000kg	Capacity: 900L
Working Height: 5.00m (16feet)	Working Height: 6.58m (22feet)	Working Height: 9.90m (32feet)	Lifting height: 3.70m	Max. lifting height: 5.50m	Length: 1021mm
Working Reach: 0.00m	Working Reach: 0.00m	Working Reach: 3.15m	Max. lifting height: 7.00m	Max. lifting height: 7.00m	Width: 1221mm
Platform Dimensions: 1.20 x 0.70m	Platform Dimensions: 0.93 x 0.69m	Platform Dimensions: 0.90 x 0.75m	Length: 1.99m	Length: 1.99m	Height: 1355mm
Extended Platform: N/A	Extended Platform: 1.10m (3.61m)	Extended Platform: 0.90 x 0.75m	Height: 2.73m	Height: 2.73m	Empty Weight: 350kg
Safe Working Load: 240kg	Safe Working Load: 227kg	Safe Working Load: 200kg	Weight: 5285kg	Weight: 5485kg	Full Weight: 1115kg
Lift Cycles: 132	Lift Cycles: 132	Lift Cycles: 132			
Handrails Lowered: N/A	Stowed Height: 1.79m	Stowed Height: 1.99m			
Handrails Lowered: 1.70 x 0.70m	Closed Dimensions: 1.37 x 0.77m	Closed Dimensions: 2.82 x 0.99m			
Machine Weight: 370kg	Machine Weight: 960kg	Machine Weight: 2650kg			

DELIVERED WITHIN 4HRS ON SITE ON TIME NATIONAL HIRE