

Bcompact design Pty. Ltd. Po. Box 206. 2258, Sydney, Australia p: +61413769303

w: www.bcompact.com e: info@bcompact.com ACN: 637472407

Bcompact Side folding Hybrid Stair







The bulky staircase gets a simple but brilliant upgrade with our original & groundbreaking sideways folding Bcompact Hybrid Stair with Patent Pending, Bi-folding Handrail & optional integrated safety gate.

This space-saving staircase replacement neatly folds sideways to close flush or into the wall in seconds when not in use, freeing up that valuable space, and can be used in a multitude of standard & unconventional locations, such as Infront of doors or windows, in hallways or even outdoors.

Made from sustainably sourced, aesthetically pleasing & technically unsurpassed, natural blonde Bamboo or colour stained to match your decor. Each product is tailor-made & priced to your unique & exacting specifications, which makes assembly quick & easy & installation a breeze.

With multiple angles & infinite height options, hybrid stairs are available in extra comfort width and new narrow version, great when space is even more precious.

Space today comes at a premium, so make the most of it & maximise your space with the revolutionary Bcompact Hybrid Stair.

Materials & colours

Sustainably sourced Bamboo Ply









Bcompact design Pty. Ltd. Po. Box 206. 2258, Sydney, Australia p: +61413769303

w: www.bcompact.com e: info@bcompact.com ACN: 637472407

	Wide STAIR	Narrow STAIR
Α	Height Range (floor to upper floor): 1.2m - 3.4m	Height Range (floor to upper floor): 1.2m - 3.4m
В	Angle Range: 50 - 60 degrees	Angle Range: 50 - 60 degrees
С	Overall Width Unfolded: 715mm (793mm due to Handrail Mechanism Lever arm protrusion of 78mm at 2 points)	Overall Width Unfolded: 575mm (653mm due to Handrail Mechanism Lever arm protrusion of 78mm at 2 points)
D	Overall Width Folded: 40mm main structure 55mm at 2 points due to auto folding handrail mechanisms	Overall Width Folded: 40mm main structure 55mm at 2 points due to auto folding handrail mechanisms
E	Tread Rise Height Range: 210mm - 295mm	Tread Rise Height Range: 210mm - 295mm
F	Tread dimensions: 165mm x 700mm x 25mm	Tread dimensions: 165mm x 560mm x 25mm
G	Ceiling Access Hole Requirement: Length is proportional with angle of Stair, Width min. of 750mm	Ceiling Access Hole Requirement: Length is proportional with angle of Stair, Width min. of 653mm
Н	Height above upper level in folded position: 676mm (1290mm with bi-folding handrail)	Height above upper level in folded position: 540mm (1154mm with bi-folding handrail)
Ι	Standard with a bi-folding Aluminium handrail. Rail height above floor when open 800mm	Standard with a bi-folding Aluminium handrail. Rail height above floor when open 800mm
J	(Optional Extra: Safety Gate)	(Optional Extra: Safety Gate)



