

Technical Information

November 2016

Supersedes issue dated May 2015

08_140506e-03/Page 1 of 5

WF-No. 10185

Dehypon[®] LS 24

® = Registered trademark of BASF
in many countries.

Chemical character

Dehypon® LS 24 is a low-foaming, nonionic surfactant. It is a fatty alcohol alkoxyate made from a C₁₂-C₁₄ - fatty alcohol (1 mol) ethylene oxide (2 moles) and propylene oxide (4 moles).

PRD-No.*

30528538

* BASF's commercial product numbers.

Appearance

Dehypon® LS 24 is a yellowish, clear to slightly cloudy liquid at room temperature and tends to form sediment in cold.

Handling and Storage**Handling**

- a) Dehypon® LS 24 should be stored indoors in a dry place. Storage rooms must not be overheated.
- b) Dehypon® LS 24 is a clear to cloudy liquid and tends to form sediment.
- c) Liquid that has solidified or that shows signs of sedimentation should be heated to 30 – 50 °C and homogenized before it is processed. Please mix sufficiently prior to use.
- d) Drums that have solidified or that have begun to precipitate should be reconstituted by gentle heating, preferably in a heating cabinet. The temperature must not be allowed to exceed 50 °C. Please mix sufficiently prior to use. This also applies if drums are heated by external electrical elements. Internal electrical elements should not be used because of the localized anomalies in temperature that they cause.
- e) Dehypon® LS 24 must be blanketed with nitrogen if it is stored in heated tanks (at 30 – 40 °C) to prevent it from coming into contact with air. Constant, gentle stirring helps to prevent it being discolored as a result of prolonged contact with electrical elements or external heating coils.
- f) Please refer to the latest Safety Data Sheet for detailed information on product safety.

Materials

The following materials can be used for tanks and drums:

- a) AISI 321 stainless steel (X6CrNiTi1810)
- b) AISI 316 Ti stainless steel (X6CrNiMoTi17122)

Shelf life

Provided it is stored properly and drums are kept tightly sealed, Dehypon® LS 24 has a shelf life of at least two years in its original packaging.

Properties

Some physical properties are listed in the table below. These are typical values only and not all of them are monitored on a regular basis. They are correct at the time of publication and do not necessarily form part of the product specification. A detailed product specification is available on request or via BASF's WorldAccount: <https://worldaccount.basf.com> (registered access).

Dehypon® LS 24	Unit	Value
Physical form (23 °C)		liquid
Concentration	%	approx. 100
Water content (EN 13267)	%	<0.5
Cloud points (EN 1890)*		
Method D	°C	approx. 37
Method E	°C	approx. 30
pH value (EN 1262, solution B)**		approx. 7
Density (DIN 51757, 20 °C)	g/cm ³	approx. 0.94
Pour point (ISO 2207)	°C	approx. -20
Viscosity (EN 12092, 20 °C, Brookfield, 60 rpm)	mPa·s	approx. 50
Hydroxyl value (DIN 53240)	mg KOH/g	approx. 115
Flash point (ISO 2592)	°C	approx. 200
Wetting (EN 1772, distilled water, 23 °C, 2 g Soda ash/l)		
0.5 g/l	s	approx. 200
1.0 g/l	s	approx. 160
2.0 g/l	s	approx. 150
Foam volume (EN 12728, 40 °C, 2 g/l water at a hard- ness of 1.8 mmol Ca-ions/l, after 30 s)	cm ³	approx. 0
Surface tension (EN 14370, 1 g/l in distilled water, 23 °C)***	mN/m	approx. 29

* Cloud point EN 1890:

Method D: 5 g of surfactant + 45 g of butyldiglycol solution (c = 250 g/l)

Method E: 5 g of surfactant + 25 g of butyldiglycol solution (c = 250 g/l)

** The pH value of Dehypon® LS 24 can decrease during storage, but this does not have any effect on its performance.

*** Applying Harkins-Jordan correction.

Solubility

Details on the solubility of Dehypon® LS 24 in various solvents are given in the table below:

Solubility of Dehypon® LS 24 (10% at 23 °C)

Distilled water	–
Potable water (2.7 mmol Ca ²⁺ -ions/l)	–
Caustic soda (5%)	–
Hydrochloric acid (5%)	–
Salt solution (5%)	–
Solvent naphtha	+
Ethanol, Isopropanol	+
Aromatic hydrocarbons	+

+ = *clear solution*

± = *sparingly soluble (insoluble sediment)*

– = *insoluble (phase separation)*

o = *forms an opaque soluble, homogeneous emulsion*

Viscosity

The relationship between viscosity and temperature is always an important point to consider when Dehypon® LS 24 is stored or shipped. This is shown in the following table (Brookfield LVT):

Temperature °C	Viscosity (mPa·s)
0	approx. 130
10	approx. 80
20	approx. 50
23	approx. 45
30	approx. 30
40	approx. 20
50	<20
60	<20

Safety

We are not aware of any ill effect that can result from using Dehypon® LS 24 for the purpose for which it is intended and from processing it in accordance with current practices.

According to the experience that we have gained over many years and other information at our disposal, Dehypon® LS 24 does not exert harmful effects on health, provided it is used properly, due attention is given to the precautions necessary for handling chemicals, and the information and advice given in our Safety Data Sheets are observed.

Labelling

Please consult the current Safety Data Sheets for information on the classification and labelling of our products and other information relevant to safety.

Disclaimer

This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

November 2016