

# Safety Data Sheet Luvipur® FM 85

Revision date: 2017/07/31 Page: 1/11 Version: 7.1 (30602853/SDS\_GEN\_US/EN)

#### 1. Identification

#### Product identifier used on the label

### **Luvipur® FM 85**

#### Recommended use of the chemical and restriction on use

Recommended use\*: industrial chemicals

#### Details of the supplier of the safety data sheet

Company:

BASE CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### **Emergency telephone number**

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Molecular formula: CH(2)O(2) Chemical family: carboxylic acid

#### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

Flam. Liq. 4 Flammable liquids
Acute Tox. 3 (Inhalation - vapour) Acute toxicity
Acute Tox. 4 (oral) Acute toxicity

Skin Corr./Irrit. 1B Skin corrosion/irritation

Eye Dam./Irrit. 1 Serious eye damage/eye irritation

#### Label elements

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Luvipur® FM 85

Revision date: 2017/07/31 Page: 2/11 Version: 7.1 (30602853/SDS GEN US/EN)

Pictogram:



Signal Word: Danger

Hazard Statement:

H227 Combustible liquid. H331 Toxic if inhaled. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P261 Avoid breathing vapours.
P260 Do not breathe mist or vapour.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P260 Do not breathe dust or mist.

P270 Do not eat, drink or smoke when using this product.

P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you

feel unwell.

P330 Rinse mouth.

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder

or water spray for extinction.

Precautionary Statements (Storage):

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

#### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

#### Labeling of special preparations (GHS):

Corrosive to the respiratory tract.

### Luvipur® FM 85

Revision date : 2017/07/31 Page: 3/11

Version: 7.1 (30602853/SDS\_GEN\_US/EN)

#### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u> <u>Weight %</u> <u>Chemical name</u> 64-18-6 >= 85.0 - <= 86.0% Formic Acid

#### 4. First-Aid Measures

#### **Description of first aid measures**

#### **General advice:**

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

#### If on skin:

Wash affected areas with water while removing contaminated clothing. Immediate medical attention required.

#### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

#### If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

#### Indication of any immediate medical attention and special treatment needed

Note to physician

Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

#### 5. Fire-Fighting Measures

#### **Extinguishing media**

Suitable extinguishing media:

water spray, dry powder, alcohol-resistant foam, carbon dioxide

### Luvipur® FM 85

Revision date: 2017/07/31 Page: 4/11
Version: 7.1 (30602853/SDS GEN US/EN)

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide,

The substances/groups of substances mentioned can be released if the product is involved in a fire.

#### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### **Further information:**

Keep people away and stay on the upwind side.

#### 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Breathing protection required. Avoid contact with the skin, eyes and clothing.

#### **Environmental precautions**

Do not empty into drains.

#### Methods and material for containment and cleaning up

Contain spills and cover with absorbent material. Place into appropriately labeled waste containers. Remove containers to a safe place, cover loosely, and allow to stand for 24 to 48 hours before sealing and disposing.

#### 7. Handling and Storage

#### Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Sealed containers should be protected against heat as this results in pressure build-up.

Protection against fire and explosion:

Sources of ignition should be kept well clear.

#### Conditions for safe storage, including any incompatibilities

Segregate from alkalies and alkalizing substances.

Suitable materials for containers: Stainless steel 1.4571, Stainless steel 1.4404, High density polyethylene (HDPE), Low density polyethylene (LDPE), glass

Storage stability:

Storage temperature: < 30 °C Storage duration: <= 36 Months

From the data on storage duration in this safety data sheet no agreed statement regarding the warrantee of application properties can be deduced.

#### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

Formic Acid OSHA PEL PEL 5 ppm 9 mg/m3; TWA value 5 ppm 9

mg/m3;

ACGIH TLV STEL value 10 ppm; TWA value 5 ppm;

### Luvipur® FM 85

Revision date: 2017/07/31 Page: 5/11
Version: 7.1 (30602853/SDS\_GEN\_US/EN)

#### Advice on system design:

Provide adequate exhaust ventilation to control work place concentrations.

#### Personal protective equipment

#### Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour respirator. Observe OSHA regulations for respirator use (29 CFR 1910.134).

#### Hand protection:

chloroprene rubber (Neoprene), butyl rubber, Protective glove selection must be based on the user's assessment of the workplace hazards., Consult with glove manufacturer for testing data.

#### Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

#### **Body protection:**

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

#### General safety and hygiene measures:

Contact with eyes and skin must be avoided. Avoid inhalation of vapour. Remove contaminated clothing immediately and dispose of safely. When using, do not eat, drink or smoke.

#### 9. Physical and Chemical Properties

Form: liquid

Odour: pungent odour
Odour threshold: not determined
Colour: colourless to yellow

pH value: 2.2

(10 g/l, 20 °C)

Melting point: -13 °C Boiling point: 107.3 °C

Sublimation point: No applicable information available.

Flash point: 65 °C (DIN 51755)

Flammability: Combustible liquid.

Lower explosion limit: 14.9 %(V) 14.9 %(V)

(57 °C)

Upper explosion limit: 47.6 %(V) Autoignition: 500 °C

Autoignition: 500 °C (DIN 51794)

Vapour pressure: 24.2 hPa (20 °C)

112.5 hPa ( 50 °C) 1.195 g/cm

Density: 1.195 g/cm3

( 20 °C) 1.201 g/cm3 ( 15 °C) 1.173 g/cm3 ( 40 °C) 1.161 g/cm3 ( 50 °C) 1.15 g/cm3 ( 55 °C)

Luvipur® FM 85

Revision date: 2017/07/31 Page: 6/11 Version: 7.1 (30602853/SDS\_GEN\_US/EN)

Relative density: No applicable information available. Vapour density: No applicable information available.

Partitioning coefficient noctanol/water (log Pow): -1.9 (23 °C)

Thermal decomposition: No applicable information available.

Viscosity, dynamic: 1.70 mPa.s (20 °C)

0.92 mPa.s (55 °C)

Viscosity, kinematic: 1.42 mm2/s

( 20 °C) 0.8 mm2/s ( 55 °C)

Miscibility with water: miscible in all proportions

Solubility (quantitative): No applicable information available.

Solubility (qualitative): miscible

solvent(s): organic solvents,

Molar mass: 46.03 g/mol

Evaporation rate: Value can be approximated from

Henry's Law Constant or vapor

pressure.

#### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

#### **Chemical stability**

Slow decomposition possible.

#### Possibility of hazardous reactions

Reacts with alkalies. Reacts with amines. Exothermic reaction.

#### Conditions to avoid

Temperature: > 30 degrees Celsius

#### Incompatible materials

bases, non-coated metals, base metals

#### **Hazardous decomposition products**

Decomposition products:

carbon dioxide, carbon monoxide

Thermal decomposition:

No applicable information available.

#### 11. Toxicological information

#### Primary routes of exposure

Luvipur® FM 85

Revision date: 2017/07/31 Page: 7/11 Version: 7.1 (30602853/SDS\_GEN\_US/EN)

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### **Acute Toxicity/Effects**

#### Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation. The toxicity of the product is based on its corrosivity.

#### <u>Oral</u>

Type of value: LD50 Species: rat (male/female)

Value: 730 mg/kg (OECD Guideline 401)

#### **Inhalation**

Type of value: LC50 Species: rat (male/female) Value: 7.85 mg/l (BASF-Test)

Exposure time: 4 h

#### Dermal

Study scientifically not justified.

#### Assessment other acute effects

#### Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Irritation / corrosion

Assessment of irritating effects: Highly corrosive! Damages skin and eyes.

#### <u>Skin</u>

Species: rabbit Result: Corrosive.

Method: OECD Guideline 404

Literature data.

#### <u>Eye</u>

As the product corrodes the skin, it can be expected to have a similar effect on the eyes also.

#### Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies. Caused sensitization in humans.

#### Buehler test

Species: guinea pig Result: Non-sensitizing. Method: OECD Guideline 406

#### Aspiration Hazard

No aspiration hazard expected.

#### **Chronic Toxicity/Effects**

#### Repeated dose toxicity

### Luvipur® FM 85

Revision date: 2017/07/31 Page: 8/11 Version: 7.1 (30602853/SDS GEN US/EN)

Assessment of repeated dose toxicity: After repeated administration the prominent effect is the induction of corrosion.

#### Genetic toxicity

Assessment of mutagenicity: No mutagenic effect was found in various tests with bacteria and mammalian cell culture.

Genetic toxicity in vitro: Ames-test with and without metabolic activation negative Cytogenetic assay with and without metabolic activation negative Literature data.

#### Carcinogenicity

Assessment of carcinogenicity: The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The results of various animal studies gave no indication of a carcinogenic effect.

#### Reproductive toxicity

Assessment of reproduction toxicity: The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The results of animal studies gave no indication of a fertility impairing effect.

#### **Teratogenicity**

Assessment of teratogenicity: The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. No indications of a developmental toxic / teratogenic effect were seen in animal studies.

#### Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

#### 12. Ecological Information

#### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

The product gives rise to pH shifts.

#### Toxicity to fish

LC50 (96 h) 130 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 92/69/EEC, C.1, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LC50 (96 h) 68 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration. After neutralization, it is no longer toxic.

#### Aquatic invertebrates

EC50 (48 h) 365 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The statement of the toxic effect relates to the analytically determined concentration.

### Luvipur® FM 85

Revision date: 2017/07/31 Page: 9/11 Version: 7.1 (30602853/SDS\_GEN\_US/EN)

EC50 (48 h) 32.19 mg/l, Daphnia magna (Directive 79/831/EEC, static)

The details of the toxic effect relate to the nominal concentration. The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample.

#### Aquatic plants

EC50 (72 h) 1,240 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

EC50 (72 h) 32.64 mg/l (growth rate), Scenedesmus subspicatus (DIN 38412 Part 9, static) The details of the toxic effect relate to the nominal concentration. The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample.

#### Chronic toxicity to aquatic invertebrates

No observed effect concentration (21 d) >= 102 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

The statement of the toxic effect relates to the analytically determined concentration. The product will cause changes in the pH value of the test system. The result refers to a neutralized sample. No effects at the highest test concentration.

#### Microorganisms/Effect on activated sludge

#### Toxicity to microorganisms

other aerobic

activated sludge, domestic, non-adapted/EC10 (13 d): 72 mg/l

#### DIN EN ISO 8192 aerobic

activated sludge, industrial/EC20 (0.5 h): > 1,000 mg/l

The details of the toxic effect relate to the nominal concentration. The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample.

#### DIN 38412 Part 8 aerobic

bacterium/EC50 (17 h): 46.7 mg/l

The details of the toxic effect relate to the nominal concentration. The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample.

#### Persistence and degradability

Assessment biodegradation and elimination (H2O)

Readily biodegradable (according to OECD criteria).

#### Elimination information

100 % DOC reduction (9 d) (OECD 301E/92/69/EEC, C.4-B) (aerobic, municipal sewage treatment plant effluent)

#### **Bioaccumulative potential**

#### Bioaccumulation potential

No significant accumulation in organisms is expected as a result of the distribution coefficient of noctanol/water (log Pow).

#### Mobility in soil

#### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

# Safety Data Sheet Luvipur® FM 85

Revision date : 2017/07/31 Page: 10/11

Version: 7.1 (30602853/SDS\_GEN\_US/EN)

#### 13. Disposal considerations

#### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into waterways or sewer systems without proper authorization.

#### Container disposal:

RCRA empty containers may be landfilled at a licensed facility; other containers must be disposed of in a RCRA licensed facility. If containers are not empty, they must be disposed of in a RCRA-licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

RCRA: U123

This product is regulated by RCRA.

#### 14. Transport Information

#### Land transport

**USDOT** 

Hazard class: 8 Packing group: II

ID number: UN 1779 Hazard label: 8, 3

Proper shipping name: FORMIC ACID

#### Sea transport

**IMDG** 

Hazard class: 8 Packing group: II

ID number: UN 1779 Hazard label: 8, 3 Marine pollutant: NO

Proper shipping name: FORMIC ACID

#### Air transport

IATA/ICAO

Hazard class: 8 Packing group: II

ID number: UN 1779 Hazard label: 8, 3

Proper shipping name: FORMIC ACID

#### 15. Regulatory Information

#### **Federal Regulations**

#### Registration status:

Chemical TSCA, US released / listed

Feed TSCA, US released / exempt

### Luvipur® FM 85

Revision date: 2017/07/31 Page: 11/11
Version: 7.1 (30602853/SDS GEN US/EN)

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire

**EPCRA 313:** 

CAS Number 64-18-6 Chemical name Formic Acid

CERCLA RQ CAS Number Chemical name

5000 LBS 64-18-6; 64-19-7 Formic Acid; Acetic acid

**NFPA Hazard codes:** 

Health: 3 Fire: 2 Reactivity: 0 Special:

#### Assessment of the hazard classes according to UN GHS criteria (most recent version):

Skin Corr./Irrit. 1B Skin corrosion/irritation Flam. Liq. 4 Flammable liquids

Eye Dam./Irrit. 1 Serious eye damage/eye irritation

Acute Tox. 4 (oral) Acute toxicity
Acute Tox. 3 (Inhalation - vapour) Acute toxicity

#### 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2017/07/31

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Luvipur® FM 85 is a registered trademark of BASF Corporation or BASF SE IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**