

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27

Version: 3.0

Page: 1/10

(30044042/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Plurafac® LF 120

Recommended use of the chemical and restriction on use

Recommended use*: surfactants

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: alcohols

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 2/10
(30044042/SDS_GEN_US/EN)



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P273	Avoid release to the environment.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 100 % dermal

This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request or at the request of a detergent manufacturer.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
	75.0 - 100.0%	Trade Secret: NJTSRN 489909-5016-P-PC

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 3/10
(30044042/SDS_GEN_US/EN)

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.
------------	---

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours, carbon oxides
Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27

Page: 4/10

Version: 3.0

(30044042/SDS_GEN_US/EN)

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, section 8.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Place absorbed material in the same container as the spilled substance/product for disposal.

7. Handling and Storage

Precautions for safe handling

Protect against moisture. Shut containers immediately after taking product because product takes up the humidity of air.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Stainless steel 1.4401, Stainless steel 1.4301 (V2), Aluminium, High density polyethylene (HDPE), glass, Low density polyethylene (LDPE)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

The product is not damaged by low temperatures or by frost.

Protect from temperatures above: 70 °C

Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 5/10
(30044042/SDS_GEN_US/EN)

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:	not determined	
Colour:	colourless to yellowish	
pH value:	approx. 6 (50 g/l, 23 °C)	(DIN EN 1262)
solidification temperature:	approx. 5 °C	(DIN ISO 2207)
Boiling point:	> 250 °C	
Flash point:	> 100 °C	(DIN 51758)
Flammability:	hardly combustible	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 200 °C	(DIN 51794)
Vapour pressure:	< 0.1 hPa (20 °C)	
Density:	approx. 1 g/cm ³ (20 °C)	
Relative density:	approx. 1 (20 °C)	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not determined	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C	
Viscosity, dynamic:	approx. 60 mPa.s (23 °C)	(DIN EN ISO 2555 (LVT))
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	soluble	
Miscibility with water:	miscible in all proportions	
Solubility (qualitative):	soluble	
Evaporation rate:	solvent(s): polar solvents, Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 6/10
(30044042/SDS_GEN_US/EN)

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid

Avoid humidity. See MSDS section 7 - Handling and storage.

Incompatible materials

caustics, halogens, Alkalines, acids, reactive chemicals

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

> 300 °C

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation.

Oral

Type of value: LD50

Species: rat

Value: > 2,000 - < 5,000 mg/kg (BASF-Test)

Inhalation

Species: rat

Value: (IRT)

Exposure time: 8 h

No mortality within the stated exposition time as shown in animal studies.

Dermal

Type of value: LD50

Species: rat

not determined

Assessment other acute effects

No data available.

Irritation / corrosion

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 7/10
(30044042/SDS_GEN_US/EN)

Assessment of irritating effects: May cause severe damage to the eyes. Causes skin irritation.

Skin

Species: rabbit
Result: moderately irritating
Method: BASF-Test

Eye

Species: rabbit
Result: Risk of serious damage to eyes.
Method: BASF-Test

Sensitization

Assessment of sensitization: No data available.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria.

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

Reproductive toxicity

Assessment of reproduction toxicity: No data available.

Teratogenicity

Assessment of teratogenicity: No data available.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Further important symptoms and effects are so far not known.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 1 - < 10 mg/l, *Leuciscus idus* (DIN 38412 Part 15)

Aquatic invertebrates

EC50 > 1 - < 10 mg/l, *Daphnia magna*

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants

EC50 > 10 - < 100 mg/l, algae

acute Effect The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 8/10
(30044042/SDS_GEN_US/EN)

No observed effect concentration > 0.1 - < 1 mg/l, algae
long-term effect The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to fish
No data available.

Chronic toxicity to aquatic invertebrates
No observed effect concentration > 0.1 - < 1 mg/l, Daphnia magna
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of terrestrial toxicity
No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
DEV-L2 activated sludge/EC10: > 1,000 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H₂O)
Readily biodegradable (according to OECD criteria).

Elimination information

> 60 % CO₂ formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic, activated sludge, domestic)

> 90 % Bismuth-active substance (mod. OECD 301E)

Bioaccumulative potential

Assessment bioaccumulation potential
Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is possible.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Add. remarks environm. fate & pathway:
Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:
Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not allow to enter soil, waterways or waste water channels.

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 9/10
(30044042/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
100 LBS	106-88-7; 123-91-1	1,2-epoxy-n-butane; 1,4-dioxane
10 LBS	75-21-8	Ethylene Oxide

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

[Other Prop 65 components may be present in the product.]

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 0 Special:

Safety Data Sheet

Plurafac® LF 120

Revision date : 2017/11/27
Version: 3.0

Page: 10/10
(30044042/SDS_GEN_US/EN)

HMIS III rating

Health: 3 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2017/11/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Plurafac® LF 120 is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET