Technical Bulletin

Dehypound® Advanced



Dehypound® Advanced is a proprietary blend of specialty surfactants. The INCI name is caprylyl/decyl glucoside (and) deceth-5(and) PPG-6-laureth-3. This is a finely balanced surfactant system and HLB. It is strongly recommended that no glycol ether solvents be used with Dehypound® Advanced due to a potential loss in cleaning performance. Dehypound® Advanced is a synergistic surfactant blend with superior hard surface detergency and low foam. Dehypound® Advanced has the following advantages in hard surface cleaning formulation:

- Superior detergency compared to NPE or LAE
- Significant cost saving on formulation
- No solvent required for premium performance
- No builder needed
- Neutral cleaning as good as leading brand in the US
- Controlled foam

- No gel phase allows rapid incorporation into
- Low viscosity/light color
- **Excellent formulation flexibility**
- Conforms to EU detergent regulations
- Components all on EPA Inert List
- Overall better choice for the environment

Storage

Temperatures above 45°C for extended periods should be avoided as this can lead to yellowing of product. Dehypound® Advanced is preserved with 4,4dimethyl-oxazolidine at approximately 0.16%.

Shelf Life

BASF will endorse the results on the certificate of analysis for a period of up to 2 years from the date of

Specifications	
Visual appearance vs. standard	Corresponds to std.
Solid matter content,%	74.9 – 78.9
pH value , as is, 25°C	7.0 – 9.0
Typical properties	
Form	Liquid
1 01111	Liquid
Cloud Point, 1% (°F)	80 – 84

manufacture for material in original, unopened, properly stored containers. Beyond 2 years, we recommend the quality of the material be confirmed prior to use, by retesting the certificate of analysis parameters.

Please refer to the Material Safety Data Sheet (MSDS) for this product for instructions on safe and proper handling and disposal.

Dehypound® is a registered trademark of BASF in many countries

For More Information:

Order Placement

To place orders for delivery in the United States or Canada, please call our toll free number (800) 443-6460.

For Other Information

Including product literature and Material Safety Data Sheets please call (734) 324-6101.

Or Visit Our Website At:

www.performance.basf-corp.com

Important: While the information and data contained in this bulletin are presented in good faith and believed to be reliable, they do not constitute a part of our terms and conditions of sales unless specifically incorporated in our Order Acknowledgment. NOTHING HEREIN SHALL BE DEEMED TO CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, THAT SAID INFORMATION OR DATA ARE CORRECT OR THAT THE PRODUCTS DESCRIBED ARE MERCHANTABLE OR FIT FOR A PARTICULAR PURPOSE, OR THAT SAID INFORMATION, DATA OR PRODUCTS CAN BE USED WITHOUT INFRINGING PATENTS OF THIRD PARTIES.

© 2016 BASF Corporation. All rights reserved. BASE Corporation 100 Park Ave Florham Park, New Jersey 07932 800-443-6460