

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12

Version: 5.0

Page: 1/10

(30044021/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Plurafac® LF 400

Recommended use of the chemical and restriction on use

Recommended use*: Raw material for the chemical-technical industry

Recommended use*: Chemical

Suitable for use in industrial sector: chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION

100 Park Avenue

Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: fatty alcohol alkoxylate, Polymer

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Aquatic Acute	1	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 2/10
(30044021/SDS_GEN_US/EN)

Pictogram:



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P273	Avoid release to the environment.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P391	Collect spillage.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 100 %

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
120313-48-6	>= 75.0 - <= 100.0%	Alcohols, C12-15-branched and linear, ethoxylated propoxylated

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 3/10
(30044021/SDS_GEN_US/EN)

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.
------------	---

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours, carbon oxides
Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12

Version: 5.0

Page: 4/10

(30044021/SDS_GEN_US/EN)

High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Place absorbed material in the same container as the spilled substance/product for disposal.

7. Handling and Storage

Precautions for safe handling

Shut containers immediately after taking product because product takes up the humidity of air.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301 (V2), Aluminium, Polyester resin, glass reinforced (Palatal A410), High density polyethylene (HDPE), tinned carbon steel (Tinplate), glass, Low density polyethylene (LDPE), Galvanized carbon steel (Zinc)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

The product is not damaged by low temperatures or by frost.

Protect from temperatures above: 70 °C

Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 5/10
(30044021/SDS_GEN_US/EN)

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:	not determined	
Colour:	colourless to yellowish	
pH value:	approx. 7 (50 g/l, 23 °C)	(DIN EN 1262)
solidification temperature:	approx. 0 °C	(DIN ISO 2207)
Boiling point:	not applicable	
Flash point:	> 100 °C	(DIN 51758)
Flammability:	not flammable	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 200 °C	(DIN 51794)
Vapour pressure:	< 0.1 hPa (20 °C)	
Density:	approx. 0.97 g/cm3 (23 °C)	(DIN 51757)
Relative density:	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C	
Viscosity, dynamic:	70 mPa.s (23 °C)	
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	(25 °C) soluble	
Miscibility with water:	miscible in all proportions	
Solubility (qualitative):	soluble solvent(s): petroleum spirit, Ethanol, 2-Propanol	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 6/10
(30044021/SDS_GEN_US/EN)

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid

Avoid humidity. See MSDS section 7 - Handling and storage.

Incompatible materials

caustics, halogens, Alkalines, acids, reactive chemicals

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
> 300 °C

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact.

Oral

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg

Dermal

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg

Assessment other acute effects

No data available.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12

Version: 5.0

Page: 7/10

(30044021/SDS_GEN_US/EN)

Skin

Species: rabbit

Result: Irritant.

Method: BASF-Test

Eye

Species: rabbit

Result: Risk of serious damage to eyes.

Method: BASF-Test

Sensitization

Assessment of sensitization: No data available.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria.

Genetic toxicity in vitro: Ames-test negative

Carcinogenicity

Assessment of carcinogenicity: No data available.

None of the components in this product at concentrations greater than 0.1% are listed by IARC; NTP, OSHA or ACGIH as a carcinogen.

Reproductive toxicity

Assessment of reproduction toxicity: No data available.

Teratogenicity

Assessment of teratogenicity: No data available.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 0.1 - 1 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EEC, C.1, static)

Aquatic invertebrates

EC50 (48 h) > 1 - 10 mg/l, Daphnia magna (Directive 79/831/EEC)

Aquatic plants

EC50 (72 h) > 0.1 - 1 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201)
acute Effect

EC10 (72 h) > 0.1 - 1 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201)

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 8/10
(30044021/SDS_GEN_US/EN)

long-term effect

Chronic toxicity to fish
No data available.

Chronic toxicity to aquatic invertebrates
No data available.

Assessment of terrestrial toxicity
No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
DIN 38412 Part 8 bacterium/EC10: > 1,000 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H₂O)
Readily biodegradable (according to OECD criteria).

Elimination information

>= 90 % Bismuth-active substance (OECD 301 A (new version))

> 60 % CO₂ formation relative to the theoretical value (28.000000 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C)

Bioaccumulative potential

Bioaccumulation potential
Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is possible.

Additional information

Sum parameter

Chemical oxygen demand (COD): 2,215 mg/g

Biochemical oxygen demand (BOD): 310 mg/g

Biochemical oxygen demand (BOD) Incubation period 30 d: 1,700 mg/g

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Add. remarks environm. fate & pathway:
Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12

Version: 5.0

Page: 9/10

(30044021/SDS_GEN_US/EN)

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class:	9
Packing group:	III
ID number:	UN 3082
Hazard label:	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains FATTY ALCOHOL ALCOXYLATE)

Sea transport

IMDG

Hazard class:	9
Packing group:	III
ID number:	UN 3082
Hazard label:	9, EHSM
Marine pollutant:	YES
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains FATTY ALCOHOL ALCOXYLATE)

Air transport

IATA/ICAO

Hazard class:	9
Packing group:	III
ID number:	UN 3082
Hazard label:	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains FATTY ALCOHOL ALCOXYLATE)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safety Data Sheet

Plurafac® LF 400

Revision date : 2019/06/12
Version: 5.0

Page: 10/10
(30044021/SDS_GEN_US/EN)

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
100 LBS	75-56-9; 123-91-1	Propylene oxide; 1,4-dioxane
10 LBS	75-21-8	Ethylene Oxide

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 3 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2019/06/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Plurafac® LF 400 is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET