



Installation Technology Transfer Program

## Performance Testing of a Novel Dry-Fog Mold Remediation and Prevention Process

Shane D. Hirschi and Dale L. Herron

August 2018



The U.S. Army Engineer Research and Development Center (ERDC) solves the nation's toughest engineering and environmental challenges. ERDC develops innovative solutions in civil and military engineering, geospatial sciences, water resources, and environmental sciences for the Army, the Department of Defense, civilian agencies, and our nation's public good. Find out more at <a href="https://www.erdc.usace.army.mil">www.erdc.usace.army.mil</a>.

To search for other technical reports published by ERDC, visit the ERDC online library at <a href="http://acwc.sdp.sirsi.net/client/default">http://acwc.sdp.sirsi.net/client/default</a>.

# Performance Testing of a Novel Dry-Fog Mold Remediation and Prevention Process

Shane D. Hirschi and Dale L. Herron

U.S. Army Engineer Research and Development Center (ERDC) Construction Engineering Research Laboratory (CERL) 2902 Newmark Dr. Champaign, IL 61824

#### Final Report

Approved for public release; distribution is unlimited.

Prepared for Assistant Chief of Staff for Installation Management,

Washington, DC 20310-0600

Under ITTP, "Performance Testing of a Novel Dry-Fog Mold Remediation and

Prevention Process"

## **Abstract**

Mold is an ongoing problem for Army installations and contingency basing locations. This work was undertaken to demonstrate the effectiveness of a two-step dry-fog mold remediation process technology to remove mold spores and provide long-term mold prevention in two buildings at Fort Campbell, KY. Treating each test building took 5 to 6 hours and included: mobilization, air and surface sampling before and after the application, and demobilization. This work concluded that the dry-fog technology provides rapid and quantifiable improvements to indoor air quality, and reduces exposure of personnel to harmful chemicals resulting from current mold remediation practices. Results indicated that the dry-fog technology could potentially support mold remediation needs resulting from indoor air quality maintenance and from natural hazards. Current rough estimates for application of the dry-fog technology are approximately \$1.00/sq ft. Early project results were shared with Region IV of the Federal Emergency Management Agency (FEMA) and the Huntington District of the U.S. Army's Corps of Engineers.

**DISCLAIMER:** The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products. All product names and trademarks cited are the property of their respective owners. The findings of this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

DESTROY THIS REPORT WHEN NO LONGER NEEDED. DO NOT RETURN IT TO THE ORIGINATOR.

## **Contents**

Abs	bstractii				
Fig	gures and Tables	iv			
Pre	eface	vi			
1	Introduction	1			
	1.1 Background	1			
	1.2 Objective				
	1.3 Approach	3			
	1.4 Mode of technology transfer				
2	Demonstration Process	5			
	2.1 Site validation	5			
	2.1.1 Bldg. 2261	6			
	2.1.2 Bldg. 6733	7			
	2.2 Baseline/background sampling and analysis	9			
	2.2.1 General information	9			
	2.2.2 Background sampling for this demonstration project	11			
	2.2.3 Sample analysis	13			
	2.3 Two-step dry-fog application	13			
	2.4 Verification sampling and analysis	19			
3	Results	20			
	3.1 Summary results	20			
	3.2 Dining facility – Bldg. 2261	24			
	3.2.1 Air sampling	24			
	3.2.2 Surface sampling	26			
	3.3 Barracks-Bldg. 6733	27			
	3.3.1 Air sampling	27			
	3.3.2 Surface sampling	28			
4	Conclusions and Recommendations	29			
Ref	ferences	30			
Acr	ronyms and Abbreviations	31			
Apı	pendix A: Material Safety Data Sheets for INSTAPure and EVERPure	32			
Apı	pendix B: Laboratory Analytical Reports	75			
Rei	port Documentation Page (SF 298)	81			

## **Figures and Tables**

## **Figures**

1	Dry-fog application system	2
2	Fort Campbell cantonment area showing demonstration locations	5
3	Exterior of Bldg. 2261—dining facility	6
4	Kitchen area inside Bldg. 2261	6
5	Dining area inside Bldg. 2261	7
6	Exterior of Bldg. 6733 - barracks	8
7	Classroom area inside Bldg. 6733	8
8	Bathroom area inside Bldg. 6733	9
9	Sampling locations at Bldgs. 2261 and 6733 (not to scale)	12
10	Air and surface sampling equipment	12
11	Equipment to apply the dry-fog treatment	14
12	Dry-fog technology apparatus	14
13	Dry-fog being applied via spray nozzle in Bldg. 2261	
14	Dry-fog being applied to intake of HVAC ducting Bldg. 2261	16
15	Dry-fog being applied via spray nozzles in Bldg. 6733	16
16	Positive pressure at various points within Bldg. 2261	
17	Dry-fog accumulation in kitchen area within Bldg. 2261	
18	Indicator strips signify treatment (i.e., white to black)	
19	Mold growing near duct vents in Bldg. 2261	
20	Air and surface sampling	19
21	Bldg. 2261 Stachybotrys/Chaetomium vs. Stachybotrys/Chaetomium (background)	21
22	Bldg. 2261—Total Spores vs. Total Spores (background)	21
23	Bldg. 2261—Hyphal Fragments vs. Hyphal Fragments (background)	22
24	Bldg. 6733—Stachybotrys/Chaetomium vs. Stachybotrys/Chaetocmium (background)	22
25	Bldg. 6733—Total Spores vs. Total Spores (background)	23
26	Bldg. 6733—Hyphal Fragments vs. Hyphal Fragments (background)	23
27	Wall surface moisture content of 100% near Sample Location #4	25
28	Leakage from ceiling piping or roofing	26
Table	s	
1	Prior related demonstration – 2009	
2	Prior related demonstration – 2010	3
3	U.S. national outdoor average for April	10
4	U.S. national outdoor average for July	11

5	U.S. national outdoor average for October	11
6	Annual outdoor average for Illinois	11
7	Surface sampling results in Bldg. 2261	22
8	Surface sampling results in Bldg. 6733	23
9	Air sampling results (#spores/m³) for Bldg. 2261	24
10	Surface sampling results for Bldg. 2261	27
11	Air sampling results (#spores/m³) for Bldg. 6733	27
12	Surface sampling results for Bldg. 6733	28

## **Preface**

This study was conducted for the Assistant Chief of Staff for Installation Management (ACSIM) under the Installation Technology Transition Program (ITTP), project element "Performance Testing of a Novel Dry-Fog Mold Remediation and Prevention Process." The technical monitor was Natalie Myers, CEERD-CNN.

The work was performed by the Energy Branch (CFE) of the Facilities Division (CF), U.S. Army Engineer Research and Development Center, Construction Engineering Research Laboratory (ERDC-CERL). Special thanks is owed to the personnel from Fort Campbell, KY for their collaboration, knowledge, experience, and field support. At the time of publication, Giselle Rodriguez was Chief, CEERD-CFE; Donald K. Hicks was Chief, CEERD-CF; and Kurt Kinnevan, CEERD-CZT was the Technical Director for Facilities. The Deputy Director of ERDC-CERL was Dr. Kirankumar V. Topudurti and the Director was Dr. Lance D. Hansen.

COL Ivan P. Beckman was Commander of ERDC, and Dr. David W. Pittman was the Director.

## 1 Introduction

## 1.1 Background

Mold is a fungus that can grow on virtually any substance, provided moisture is present. Without treatment or preventive measures, mold can damage buildings and negatively affect the health of building occupants. Mold is typically removed and remediated when it becomes visually apparent (when it "looks bad"). Unfortunately, common mold removal practices address only the visual evidence of mold; they do not remove or remediate the mold spores.

In fact, air and surface sampling are required to test whether mold spores have been completely removed. However, since there are no indoor air quality regulations/limitations for mold spores, it is difficult to enforce and/or provide rationale to justify mold treatment based on indoor air quality. This question can only be verified and resolved through sample collection and analysis via an approved laboratory. Interpreting laboratory results for mold can be difficult for several reasons. First, there are no set maximum exposure limits (MELs) for airborne indoor mold concentrations. Setting limits is a difficult matter for many reasons. To begin with, there are limited data on the relationship between exposure and human response. Furthermore, an MEL would have to account for variation in sampling techniques; sensitivity to microbial exposures across the human population; and the vast number of varying types of mold and other biological pollutants within the indoor environment (NAVFAC 2011).

The current preferred process for mold eradication is to control and eliminate the source of moisture that precipitates mold growth (USAPHC 2002). However, in U.S. Department of Defense (DoD) installations, it can be difficult to implement this common solution. In most, if not all, real-world operational settings, occupants often adjust system specific heating, ventilation, and air-conditioning (HVAC) set points, and open or close such physical controls as windows, doors, etc. to enhance their comfort without regard for how those actions affect the building's propensity for mold growth. This, combined with outstanding maintenance needs on systems that control moisture in buildings, are reoccurring issues on military installations that promote mold growth. Consequently, mold continues to

be an ongoing problem for Army installations and contingency basing locations (Vavrin and Stein 2015). The problem is further compounded by the fact that current mold remediation technologies are labor intensive, and that workers must wear various levels of personal protective equipment (PPE) during mold removal and prevention processes. These specific requirements are detailed in UFGS-02 85 00.00 20, Mold Remediation (NAVFAC 2011).

In this work, Fort Campbell, KY, and the U.S. Army Engineer Research and Development Center (ERDC) partnered with the Army Office of the Assistant Chief of Staff for Installation Management's (OACSIM) Installation Technology Transfer Program (ITTP) to demonstrate the effectiveness of the two-step dry-fog mold remediation process technology developed by Pure Maintenance LLC, a commercial partner that owns the patented treatment technology. The dry-fog demonstration took place at two buildings at Fort Campbell, KY: a vacant dining facility, and a dormant barracks administration section that included classrooms, restrooms, and offices.

## 1.2 Objective

The objective of this ITTP demonstration was to conduct independent performance testing of the novel dry-fog mold remediation and prevention process to determine the effectiveness of the treatment process at eliminating mold and preventing regrowth at military installations and contingency basing locations. Specific technical objectives were to:

- Demonstrate the dry-fog process via the 2<sup>nd</sup> generation application system (Figure 1) in two buildings at Fort Campbell, KY.
- 2. Determine the efficacy and performance (via sampling and analysis) of the dry-fog process.
- Verify initial remediation impact(s) and non-reoccurrence of mold/mildew over a test period of 6 months (via sampling and analysis).

Figure 1. Dry-fog application system.



## 1.3 Approach

This project is related to two prior ITTP studies/demonstrations performed separately in Fiscal Year 2009 (FY09)\* and FY10 (Stephenson, Lattimore, and Torrey 2011). Both these projects were performed at Fort Polk, LA. The data in Tables 1 and 2, respectively, briefly summarize the FY09 and FY10 studies/demonstrations.

Parameter	Data
Year of Study	2009
Study	Demonstration of Mold Assessment and Removal Technologies at Fort Polk, LA (L.D. Stephenson et al. 2009)
Approach/ Objective	Determine the mold burden, eradicate mold, and mitigate its recurrence
Findings	Dry ice was successfully tested on concrete and concrete block surfaces, along with biocide protectants applied post-removal
	Although dry ice was shown to be a successful multi-step mold removal process, a simple mold removal and long-term prevention strategy is desired

Table 1. Prior related demonstration - 2009.

Table 2. Prior related demonstration - 2010.

Parameter	Data
Year of Study	2010
Study	Prevention of Toxic Molds in Army Facilities Using Surface-Applied Biocides (L.D. Stephenson, J.L. Lattimore, and K.M. Torrey 2011)
Approach/ Objective	Evaluate the efficacy of a two-step mold removal process, which involves application of biocidal "eradicants" to remove mold from a variety of surfaces, followed by application of biocidal "protectants" to prevent recurrence of mold
Findings	Two best tests for quantifying potential for growth, existing mold, mold removal and long-term efficacy of protectants are: (1) viable swab test and (2) viable airborne spore count
	Best performing eradicants were: Sporicidin® (a phenolic-based product) and Shockwave® (a quaternary ammonium chloride-based product)
	Best performing antimicrobial protectants were Fosters 40-20 and Indoor Air Quality (IAQ) 6000
	Full body coverage, rubber gloves, eye protection, and dust filter should be used during application of both eradicants and protectants
	American Society for Testing and Materials (ASTM) D5590 successfully predicted the long-term efficacy of protectants to mitigate recurrence of mold growth at Fort Polk. The 4-week accelerated test is suggested as a way to quantify relative efficacy among newly emerging protectants and can be used for screening purposes

<sup>\*</sup> L. D. Stephenson, J. L. Lattimore, Ashok Kumar, and Raymond E. Patenaude. 2009. *Demonstration of Mold Assessment and Removal Technologies at Fort Polk, Louisiana*. Draft Technical Report. Champaign, IL: Engineer Research and Development Center, Construction Engineering Research Laboratory (ERDC-CERL).

This project involves a demonstration and evaluation of the short term and long-term effects of a dry-fog technology. To demonstrate/validate this technology, the researcher partners:

- 1. Identified two buildings suitable with existing mold problems at Fort Campbell that are suitable for use in the demonstration project.
- 2. Conducted pretreatment air and surface sampling in the demonstration buildings to determine existing mold levels.
- 3. Treated the designated areas within the buildings using the dry-fog process.
- 4. Sampled immediately after treatment to determine the initial effects of the treatment process.
- 5. Performed additional sampling after 1 month, 3 months, and 6 months following treatment to determine the long-term effects of the treatment.
- 6. Performed analyses to determine the efficacy of the dry-fog treatment technology.

## 1.4 Mode of technology transfer

The project team delivered the following technology transfer elements and activities during project execution:

- A Public Works Digest article (Hirschi and Herron 2017) was submitted for publishing.
- The Huntington, West Virginia District of the Corp of Engineers and Region IV of the Federal Emergency Management Agency (FEMA) were briefed on early project results via telecom.
- A U.S. Army Corps of Engineers (USACE) Engineering and Construction webinar was provided.
- A one-page project summary delivered to the OACSIM Program Management Office (PMO).
- A webinar with all 10 Regions and FEMA Headquarters is pending.

## **2 Demonstration Process**

This project team, made up of individuals from Fort Campbell, KY, the Engineer Research and Development Center, Construction Engineering Research Laboratory (ERDC-CERL), and Pure Maintenance LLC performed site validation, completed baseline/background sampling and analysis, executed the treatment process using the two-step dry-fog technology and performed verification sampling and analysis to demonstrate the two-step dry-fog technology.

#### 2.1 Site validation

Before initiation of any onsite activities, the project team held a kick-off meeting via telecon to identify the potential facilities and associated infrastructure at Fort Campbell, KY. On 9 March 2017, a site visit was held to facilitate a walk-through of the two demonstration locations, Bldg. 2261 (Dining Facility) and Bldg. 6733 (Barracks). Figure 2 shows their locations within the cantonment area of Fort Campbell. Both of these buildings were vacant and determined to be good candidates for the demonstration.



Figure 2. Fort Campbell cantonment area showing demonstration locations.

Source: Map Data 2017<sup>®</sup> Google.

## 2.1.1 Bldg. 2261

Bldg. 2261 (Figure 3) is a vacant dining facility with an interior area of 4000 sq ft, of which approximately 3700 sq ft were treated. Figures 4 and 5 show the existing conditions inside the facility. Mold was visible on most all surfaces to varying degrees.



Figure 3. Exterior of Bldg. 2261—dining facility.







Figure 5. Dining area inside Bldg. 2261.

#### 2.1.2 Bldg. 6733

Bldg. 6733 (Figure 6) is a vacant hammerhead style barracks facility with interior area of 38,000 sq ft, of which approximately 2800 sq ft were treated. Only the administrative area of the first floor (i.e., classroom, offices, and restrooms) were included in this demonstration. Figures 7 and 8 show the amounts of mold visible on the wall surfaces.

These buildings were chosen because they were vacant, and because they were known to have high levels of mold. Given the short (8-month) demonstration period, vacant buildings were selected to make it easier to schedule treatments and to control building ingress and egress. However, the absence of personnel and functioning HVAC systems made it difficult to ensure constant environmental/occupational conditions. Outside temperatures had an additional impact on the variables of interest within the two buildings.



Figure 6. Exterior of Bldg. 6733 – barracks.







Figure 8. Bathroom area inside Bldg. 6733.

## 2.2 Baseline/background sampling and analysis

#### 2.2.1 General information

Mold analyses are typically reported in terms of marker molds, outdoor molds, and hyphal fragments. This report focuses on marker molds, outdoor molds, and hyphal fragments described below (Kung'u 2016):

- Marker molds are uncommon mold types that are not typically found in significant numbers outside. These mold types, which are associated with more serious health problems, are often the best indicator of indoor mold issues. The following are typical marker molds:
  - Stachybotrys, known as "black mold," is considered the most dangerous mold type and is typically found in low numbers, if at all in outdoor samples. This mold has been linked with infant death.
  - o *Chaetomium*, a marker mold that is not commonly found at significant levels indoors and is associated with health problems including fibromyalgia, MS, Lyme disease, and others.

Common outdoor molds are typically molds that start growing outdoors, and that can still cause health issues when growing indoors.
 Health issues are usually related to cold, allergy, sinus, and respiratory problems. Typical outdoor molds are:

- o Penicillium/Aspergillus, a genus that includes approximately 200 species and that is the most common fungal genus in the United States. Penicillium/Aspergillus is commonly found in house dust, water damaged wall paper and sheet rock, wallpaper glue, fabrics moist chipboards, in rotting food, in materials concealed behind.
- Cladosporium, a genus that includes approximately 28-40 species and that is one of the top three most common genuses in the United States found indoors on a variety of substrates.
- Basidiospores, which is an extremely common mold genus in outdoor samples that originate from fungus in gardens, forests, and woodlands. Basidiospores are often found in dirt of indoor potted plants or dust.
- Hyphal Fragments are produced during mold reproduction and are often an indicator of active growth. Hyphal fragments can be found in small amounts outdoors and indoors in healthy environments. Indoor levels under 200 are generally considered "normal."

Tables 3 to 6 list "typical" U.S. outdoor average mold levels for various parts of the United States (EMLab 2012, pp 22-23, 29) for the location and months closest to those applicable to this demonstration. Data were not available for Kentucky or Tennessee, and Illinois was determined the most representable data set based on the demonstration's geographic location and weather patterns.

Table 3. U.S. national outdoor average for April.

Fungal Type	Low (Dry Climate) (#spores/m³)	Medium (#spores/m³)	High (Humid Climate) (#spores/m³)
Alternaria	13	27	53
Basidiospores	67	240	960
Chaetomium	13	13	27
Cladosporium	107	320	1013
Penicillium/Aspergillus Types	53	160	400
Stachybotrys	13	13	40

Low (Dry Climate) (#spores/m³)	Medium (#spores/m³)	High (Humid Climate) (#spores/m³)
13	40	107

427

13

747

213

13

3067

27 2120

613

40

Table 4. U.S. national outdoor average for July.

107

13

213

80

13

**Fungal Type** 

Basidiospores Chaetomium

Cladosporium

Stachybotrys

Penicillium/Aspergillus Types

Alternaria

Table 5	IIC nations	al outdoor average	for October
Table 5.	U.S. Dallona	n ourdoor average	ior ucioner

		•	
Fungal Type	Low (Dry Climate) (#spores/m³)	Medium (#spores/m³)	High (Humid Climate) (#spores/m³)
Alternaria	13	40	107
Basidiospores	133	627	3625
Chaetomium	13	13	27
Cladosporium	213	800	2720
Penicillium/Aspergillus Types	100	267	747
Stachybotrys	13	13	40

Table 6. Annual outdoor average for Illinois.

Fungal Type	Low (Dry Climate) (#spores/m³)	Medium (#spores/m³)	High (Humid Climate) (#spores/m³)
Alternaria	13	53	187
Basidiospores	160	780	3220
Chaetomium	7	13	27
Cladosporium	120	693	2773
Penicillium/Aspergillus Types	53	133	400
Stachybotrys	13	13	53

#### 2.2.2 Background sampling for this demonstration project

Before application of the dry-fog technology in the demonstration buildings, background air samples and surface samples were taken inside and outside each building (Figure 9). Samples were taken at Bldg. 2261 on 20 March 2017 and at Bldg. 6733 on 21 March 2017. In Figure 9 below, the background/outdoor sample location at each building is shown as Locations #5 and #17, respectively.

Figure 10 shows the sample collection containers for both air and surface sampling. Air sampling was conducted using a Zefon International Mold

Sampling Pump P/Z-Lite-IAQ (Figure 20). Sampling protocol for normal office space requires an air flow rate of 15 liters per minute (lpm) for a 5-minute period (EMLab 2012, pp 22-23, 29). Zefon Air-O-Cell™ sample containers were used to capture the air samples. Surface samples were taken using the tape pull method (EMLab 2012, pp 37-38, 29).




Figure 9. Sampling locations at Bldgs. 2261 and 6733 (not to scale).





#### 2.2.3 Sample analysis

Spore trap analysis and direct microscopic examination were performed for the samples collected at each location by EMLab P&K (Lab Identification [ID] #102297). Both of these methods are considered standard analyses when determining mold levels within the air and on surfaces of interest:

- Spore trap analysis is used to determine the number of a particular mold spore type within a known volume of air at a specific location. Results are reported in number of spores per cubic meter (#/m³). Positive results indicate airborne mold spores. Airborne mold spores contribute to an unhealthy environment and often lead to respiratory (and other) illnesses.
- Direct microscopic examination is used to determine specific types of mold spores present on the surface of any material at a particular location. Positive results indicate mold growth on the identified surface.

One of these two types of samples was performed on each sample collected during the demonstration. Chapter 3 of this report gives the results.

## 2.3 Two-step dry-fog application

The dry-fog is a gas/vapor with micron sized particles that can cover, penetrate, and envelope mold spores. The small size (6–8 microns) of the particles\* makes it possible to treat materials and spaces that current mold removal technologies cannot access. The first step of the two-step dry-fog process is the application of InstaPURE, which is a powerful disinfectant that destroys mold spores and disinfects any surface it touches. The second step of the two-step process is the application of EverPURE, which is an antimicrobial barrier that destroys bacteria or viruses that come in contact with surfaces treated with EverPURE. The U.S. Environmental Protection Agency (USEPA) has approved both InstaPURE and EverPURE for use in all 50 U.S. states.

The dry-fog treatment system is completely mobile. It includes compressed air, spray nozzles, and the dry-fog box (Figure 11).

<sup>\*</sup>Personal communication with Brandon Adams. 2 October 2017. Bountiful, Utah: Pure Maintenance LLC.



Figure 11. Equipment to apply the dry-fog treatment.

The dry-fog technology is housed inside the metal box (Figure 12). Independent control of the flow rates and pressures for the liquid and air provides the patented ability to generate the dry-fog. The dry fog is made up of particles ranging from 6-8 microns in diameter. Mold spores generally vary from 10-30 microns in diameter (Peacock Enterprises 2017). The dry fog's small particle size (much smaller than the mold spores) provides a mechanism to treat areas inaccessible to liquid treatments, and ensures that the fog can physically infiltrate all spaces and porous materials available to mold spores.



Figure 12. Dry-fog technology apparatus.

Air compressors provide pressure to quickly distribute the dry fog. The dry fog disseminates rather readily covering 1000 sq ft having 8- to 10-ft ceiling heights in approximately 1 hour (i.e., 10,000 cu ft per hour [cu ft/hr]). This is accomplished with minimal manpower requirements. A single individual can completely treat, including mobilizing and demobilization, a 2000 sq ft single-story facility/space in approximately 3 hours. Larger treatment volumes take correspondingly longer treatment times for a given number of air compressors and spray nozzles.

Bldg. 2261 took approximately 5 hours to treat. This included mobilization, surface and air sampling, and demobilization. Bldg. 6733 took a total of approximately 4 hours to treat and accomplish the same tasks.

The dry-fog technology is relatively inexpensive when compared to current mold removal procedures and their labor intensive requirements. Costs for the treatment of a one story building are estimated at approximately \$0.90-\$1.20/sq ft. This estimate does not include travel costs by the vendor. Actual costs will be higher or lower depending on travel time, on multi- versus single-story buildings, and on special circumstances such as the geographical location, building use(s), and building layout.

Appendix A includes Material Specifications and Data Sheets (MSDSs) for InstaPURE and EverPURE. Given the chemical make-up of these liquids and the application process, i.e., the addition of deionized water and atmospheric air, there are no (and to date have not been) adverse effects to humans or the contents within the treated buildings. The vendor (and others) have treated thousands of residential, commercial, and industrial buildings with these products with no negative effects on inhabitants or materials within treated buildings.

The dry-fog technology is currently available via licensing from the vendor. The vendor provides startup equipment, training (in person and online), and access to chemicals, local/national marketing materials, and business development support.

The treatment is performed by introducing the dry-fog via spray nozzles (Figures 13-15).



Figure 13. Dry-fog being applied via spray nozzle in Bldg. 2261.

Figure 14. Dry-fog being applied to intake of HVAC ducting Bldg. 2261.




Figure 15. Dry-fog being applied via spray nozzles in Bldg. 6733.



Figure 16 shows an example of minimalistic plastic barriers put in place to generate enough back pressure to provide positive pressure and to ensure coverage when doing smaller areas within larger, more spacious rooms. Although these barriers do not completely contain the dry-fog, they do allow the dry fog to accumulate sufficiently to provide treatment (Figure 17).



Figure 16. Positive pressure at various points within Bldg. 2261.





Indicator strips are placed at various locations within the treatment area to ensure coverage. The strips are initially white and turn black (Figure 18) as the dry-fog fills the air at a concentration sufficient to indicate full treatment. HVAC systems are operated long enough to ensure complete coverage (i.e., multiple duct system volumes) throughout the duct work and associated filters/vents.




Figure 18. Indicator strips signify treatment (i.e., white to black).

Note that the treatment does not remove the black appearance of mold (Figure 19). Even though the treatment has eliminated the mold spores, treated surfaces will still appear "moldy" so it is essential that air and surface sampling be performed (before and after treatment) to provide quantitative measurements of the treatment's removal effectiveness. An additional advantage of the dry-fog treatment is that surfaces can be cleaned with typical household cleaning products rather than with the more hazardous chemicals used for traditional mold treatment and cleaning.



Figure 19. Mold growing near duct vents in Bldg. 2261.

## 2.4 Verification sampling and analysis

After the dry-fogging application, Pure Maintenance, LLC (with members of the project team present) conducted air and surface sampling (Figure 20). Continued sampling occurred at 1 month (25 April 2017), 3 months (22 June 2017), and 6 months (12 September 2017) following treatment. Chapter 3 of this report includes results and analyses of these sampling events. Appendix B includes all raw laboratory analysis results.




Figure 20. Air and surface sampling.

## 3 Results

## 3.1 Summary results

The dry-fog treatment was successful in reducing and maintaining mold at below background levels over the 6-month demonstration period. Figures 21 to 23 show and Table 7 lists the results of air sampling and surface sampling at Bldg. 2261. Figures 24 to 26 show and Table 8 lists the results of air sampling and surface sampling at Bldg. 6733. Sections 3.1 and 3.2 give detailed results specific to individual surface and air sampling locations within each building.

Figure 22 shows that the total spore count weighted across all air sampling locations associated with Bldg. 2261 decreased from 64,126 spores/m³ before treatment, to 3,067 spores/m³ at 6 months after treatment. Over this same time period, the outdoor/background total spore count increased from 590 spores/m³ before treatment, up to 19,000 spores/m³ at 6 months after treatment. Simply put, while the outdoor/background total spore count increased 3,120%, the indoor (i.e., treated space) total spore count decreased 95.21%.

Figure 25 shows that the total spore count weighted across all air sampling locations associate with Bldg. 6733 decreased from 556,057 spores/m³ before treatment, to 3,044 spores/m³ at 6 months after treatment. Over this same time period, the outdoor/background total spore count increased from 3,100 spores/m³ to 20,000 spores/m³ at 6 months after treatment. As the outdoor total spore count increased 545.2 %, the indoor (i.e., treated space) total spore count decreased by 99.45%

Figure 21. Bldg. 2261 Stachybotrys/Chaetomium vs. Stachybotrys/Chaetomium (background).





Figure 22. Bldg. 2261—Total Spores vs. Total Spores (background).




#spores/m3 1 Month 3 Month 6 Month Before After ■ Hyphal Fragments Hyphal Fragments (Background) Sampling Event

Figure 23. Bldg. 2261—Hyphal Fragments vs. Hyphal Fragments (background).

Table 7. Surface sampling results in Bldg. 2261.

Fungal Type	Before	After	1 Month	3 Month	6 Month
Cladosporium	6+	<1	0	0	0
Penicillium/Aspergillus	0	0	0	0	0
Total	very few	very few	very few	0	0

Figure 24. Bldg. 6733—Stachybotrys/Chaetomium vs. Stachybotrys/Chaetocmium (background).






Figure 25. Bldg. 6733-Total Spores vs. Total Spores (background).

Figure 26. Bldg. 6733—Hyphal Fragments vs. Hyphal Fragments (background).




Table 8. Surface sampling results in Bldg. 6733.

Fungal Type	Before	After	1 Month	3 Month	6 Month
Cladosporium	10+	<1+	0	0	0
Penicillium/Aspergillus	0	2+	0	0	0
Total	very few	very few	very few	0	very few

## 3.2 Dining facility - Bldg. 2261

#### 3.2.1 Air sampling

Table 9 lists the results of the air sampling at Bldg. 2261. Each sampling location was allocated a representative number of square feet within the total square footage treated. A summation of the #spores/m³ at each sampling location within the building, multiplied by the associated square feet for each sample, divided by the total number of square feet treated, provides a weighted average of the sampling results, which comprises a single value for each fungal type for each building. The efficacy of the treatment is determined by comparing these values to the background levels at the time of each sampling. Values at or below background levels indicate that the treatment and/or removal was (and continues to be) effective.

Table 9. Air sampling results (#spores/m³) for Bldg. 2261.

ID	Associated Area (sq ft)	Fungal Type	Before	After	1 Month	3 Month	6 Month
#1	2268	Stachybotrys/ Chaetomium	0	0	0	0	0
		Total	19000	15000	1500	170	2800
		Hyphal Fragments	1300	430	0	0	0
#2	756	Stachybotrys/ Chaetomium	0	0	0	0	0
		Total	48000	12000	1400	480	4300
		Hyphal Fragments	2000	0	0	0	0
#3	486	Stachybotrys/ Chaetomium	0	0	0	0	0
		Total	110000	12000	2000	2800	2500
		Hyphal Fragments	2700	0	0	0	53
#4	198	Stachybotrys/ Chaetomium	520000	0	13	13	0
		Total	530000	11000	2000	2600	2800
		Hyphal Fragments	5800	0	0	0	53
#5	Outdoor/ Background	Stachybotrys/ Chaetomium	0	0	0	0	0
		Total	590	590	3400	9000	19000
		Hyphal Fragments	110	110	0	0	0

Samples #3 and #4 show an increase in hyphal fragments at the 6-month sampling event (highlighted in yellow). Even though the levels increased (from zero for the previous sampling events), they are still well below the levels before treatment. However, levels are above the background level of zero. Ideally, a future sampling round could potentially determine if this is an increasing trend, or an increase due to activity within the room where Sample #4 was taken, and adjacent to the area represented by Sample #3.

While performing the 3-month sampling event, team members encountered demolition activities in the room represented by Sample #4. Figure 27 shows the debris and the meter reading showing 100% moisture content on the wall surface. The wall was damp to the touch and clearly saturated with water. The adjacent room, represented by Sample #3, had recently began to leak from the ceiling (Figure 28). It is believed that these changes to the interior environmental/structural conditions played a role in the increased total spore count. However, it should be noted that the background total spore count continued to increase beginning with the 1-month sampling event through the 6-month sampling event, where background was between four and seven times greater than the indoor sample results.



Figure 27. Wall surface moisture content of 100% near Sample Location #4.



Figure 28. Leakage from ceiling piping or roofing.

#### 3.2.2 Surface sampling

Table 10 lists the results of the surface sampling at Bldg. 2261. Initially all surfaces indicated the presence of mold. Immediately after treatment, only a "very few" total spore count was present at Sample Locations #6 and #7. Sample Location #8 showed  $\leq$  1+. No surface mold was detected at any surface sample location for the 3-month sampling event. Mold levels at all sample locations remained zero thru the 6-month sampling event.

ID	Fungal Type	Before	After	1 Month	3 Month	6 Month
#6	Cladosporium	2+	0	0	0	0
	Penicillium/ Aspergillus	0	0	0	0	0
	Total	very few	very few	0	0	0
#7	Cladosporium	2+	0	0	0	0
	Penicillium/ Aspergillus	0	0	0	0	0
	Total	very few	very few	0	0	0
#8	Cladosporium	2+	<1+	0	0	0
	Penicillium/ Aspergillus	0	0	0	0	0
	Total	very few	very few	very few	0	0

Table 10. Surface sampling results for Bldg. 2261.

## 3.3 Barracks-Bldg. 6733

#### 3.3.1 Air sampling

Table 11 lists the results of the air sampling at Bldg. 6733. Each sampling location was allocated a representative number of square feet within the total square footage treated. A summation of the #spores/m³ at each sampling location within the building, multiplied by the associated square feet for each sample, divided by the total number of square feet treated provides a weighted average of the sampling results, which comprises a single value for each fungal type for each building. The efficacy of the treatment is determined by comparing these values to the background levels at the time of each sampling. Values at or below background levels indicate that the treatment and/or removal was (and continues to be) effective.

	Associated						
ID	Area (sq ft)	Fungal Type	Before	After	1 Month	3 Month	6 Month
	1458	Stachybotrys/ Chaetomium	0	0	0	0	0
#10		Total	110000	210000	1200	430	93
		Hyphal Fragments	0	0	0	0	0
		Stachybotrys/ Chaetomium	0	0	0	0	0
#11	L 768	Total	1400000	100000	1100	480	210
		Hyphal Fragments	150	0	0	0	0
		Stachybotrys/ Chaetomium	80	0	0	0	0
#12	648	Total	3400	13000	3300	1200	10000
		Hyphal Fragments	110	53	0	0	
_		Stachybotrys/ Chaetomium	0	0	0	0	0
#17	Outdoor/ Background	Total	3100	3100	8100	14000	20000
		Hyphal Fragments	0	0	0	0	0

Table 11. Air sampling results (#spores/m³) for Bldg. 6733.

Note that between the 3-month and 6-month sampling events, the Fort Campbell personnel and/or contractor personnel began to renovate the building. It is very likely that ingress and egress of these personnel had some effect on the existing conditions. However, no monitoring or oversight was in place to account for these differing site conditions. This may explain the drastic increase of total spores for the 6-month sampling event (1200 spores/m³ to 10,000 spores/m³) at Location #12 (basement of the administrative area) in Bldg. 6733, which represents a 733% increase while the background spore count only increased by 42.9%. Despite this drastic increase, indoor levels were only 50% of the background level suggesting continued treatment.

#### 3.3.2 Surface sampling

ΙD

Total

Fungal Type

Table 12 lists the results of the surface sampling at Bldg. 6733. Initially all surfaces indicated the presence of mold, specifically cladosporium. One month after treatment, only a "very few" total spore count was present at Sample Locations #14 and #16. Three months following treatment, "very few" were reported for Location #14 and no mold spores were present at Locations #15 and #16. Levels appeared to be rising between the 3-month and 6-month sampling events. During this time, the building's interior changed from an uninhabited space to a space undergoing renovation. This change in environment, combined with added occupancy and ongoing renovation activities, created varying conditions that could have triggered an increased total spore count. Continued monitoring and sampling could have provided greater insight as to whether this trend would continue. Unfortunately, the scope of work did not include this continued work.

טו	i uligal Type	Deloie	AILEI	T MOULT	3 Month	O WIOTUT
#14	Cladosporium	2+	0	0	0	0
	Penicillium/ Aspergillus	0	0	0	0	0
	Total	very few				
#15	Cladosporium	4+	0	0	0	0
	Penicillium/ Aspergillus	0	2+	0	0	0
	Total	0	very few	0	0	very few
#16	Cladosporium	4+	<1+	0	0	0
	Penicillium/ Aspergillus	0	0	0	0	0

Table 12. Surface sampling results for Bldg. 6733.

Refore

0

Δfter

very few

1 Month 3 Month 6 Month

0

few

very few

# 4 Conclusions and Recommendations

The sampling results of this demonstration indicate that the dry-fog technology was capable of rapidly eliminating mold spores. Results also showed that the second step of the dry-fog technology's (application of EVERpure) continued to reduce mold spore levels over time; with minor exceptions, while total spore counts outdoors increased throughout the demonstration, indoor levels continued to decrease. However, the increased values for hyphal fragments at Locations #3 and #4 in Bldg. 2261 during the 6-month sampling event did not conclusively confirm the technology's treatment effectiveness beyond 6 months.

This work concluded that the dry-fog technology provides rapid and quantifiable improvements to indoor air quality, and also that it drastically reduces exposure of Army building occupants and maintenance workers to harmful chemicals resulting from current mold remediation practices.

Current rough estimates for application of the dry-fog technology are approximately \$1.00/sq ft. Actual costs would deviate from this estimate dependent on location and proximity to the vendor. It is likely that an installation could achieve additional cost savings by acquiring an in-house capability to apply the treatment. Implementing the dry-fog technology at Army installations would be relatively straightforward. The equipment could be purchased and the vendor engaged to train personnel in its use. Ongoing inhouse training could be planned to disseminate additional treatment systems across Army installations. Treatment systems could be purchased for use at each installation, or for use on a regional basis to share the technology across installations in neighboring geographic locations.

It is recommended that additional demonstration(s) be completed for longer periods (12 to 24 months). Ideally the demonstration(s) would be conducted in buildings where the indoor environment and building usage would remain constant throughout the demonstration period. It is also recommended that the dry-fog technology be demonstrated at new construction sites where it could potentially serve as a preventive measure.

# References

- EMLab P&K IAQ. 2012. *Pocket Reference Guide*. 7<sup>th</sup> ed. Marlton, NJ: EMLab P&K, pp. 22-23, 29, 37-38. https://www.emlab.com/s/services/pocketguide.html
- Hirschi, S. D., and D. L. Herron. 2017. Lab looks at "dry-fog' technology for mold remediation, prevention. *Public Works Digest*, Vol. XXIX, No. 4, p. 30.
- Kung'u, Jackson. 2016. How to Interpret Laboratory Results for Airborne Fungal (Mould) Samples. Mississauga, Ontario: Mold & Bacteria Consulting Laboratories (MBL) Inc. <a href="http://pahi.org/sitebuildercontent/sitebuilderfiles/howtointerpretlaboratoryresultsforair-bornefungalmoldsamples.pdf">http://pahi.org/sitebuildercontent/sitebuilderfiles/howtointerpretlaboratoryresultsforair-bornefungalmoldsamples.pdf</a>
- Naval Facilities Engineering Command (NAVFAC). 2011. *Mold Remediation*. Unified Facilities Guide Specification (UFGS) 02 85 00.00 20. Washington, DC: NAVFAC (Preparing Agency). https://www.wbdg.org/FFC/D0D/UFGS/UFGS%2002%2085%2000.00%2020.pdf
- Peacock Enterprises. 2017. Common Particles and Their Sizes in Microns. <a href="http://airqualityindoors.com/particlesizes.htm">http://airqualityindoors.com/particlesizes.htm</a>
- Stephenson, L. D., J. L. Lattimore, and K. M. Torrey. 2011. *Prevention of Toxic Molds in Army Facilities Using Surface-Applied Biocides*. ERDC/CERL TR-11-22. Champaign, IL: Engineer Research and Development Center, Construction Engineering Research Laboratory (ERDC-CERL).
- U.S. Army Public Health Command (USAPHC). 2002. Army Facilities Management Information Document on Mold Remediation Issues. TG 277. https://usaphc.amedd.army.mil/PHC%20Resource%20Library/TG277.pdf
- Vavrin, John L., and William J. Stein. 2015. *Mold Remediation and Recommendations to Resolve Other Major Issues in Concrete B-Huts at Bagram Air Field, Afghanistan*. ERDC/CERL TR-15-27. Champaign, IL: ERDC-CERL.

# **Acronyms and Abbreviations**

**USAPHC** 

**Term Definition** Assistant Chief of Staff for Installation Management **ACSIM** American National Standards Institute ANSI **ASTM** American Society for Testing and Materials **CEERD** US Army Corps of Engineers, Engineer Research and Development Center **CERL** Construction Engineering Research Laboratory DoD U.S. Department of Defense **ERDC** U.S. Army Engineer Research and Development Center **ERDC-CERL** Engineer Research and Development Center, Construction Engineering Research Laboratory **FEMA** Federal Emergency Management Agency **HVAC** Heating, Ventilating, and Air-Conditioning IAQ Indoor Air Quality ID Identification ITTP Installation Technology Transition Program LLC Limited Liability Company MBL Mold & Bacteria Consulting Laboratories MEL Maximum Exposure Limit **MSDS** Material Safety Data Sheet (OSHA) **NAVFAC** Naval Facilities Engineering Command NSN National Supply Number OACSIM Office of the Assistant Chief of Staff for Installation Management OMB Office of Management and Budget **PMO** Program Management Office PPE Personal Protective Equipment SAR Same As Report SF Standard Form TR **Technical Report UFGS** Unified Facilities Guide Specification **USACE** U.S. Army Corps of Engineers **USEPA** U.S. Environmental Protection Agency

U.S. Army Public Health Command

# **Appendix A: Material Safety Data Sheets for INSTAPure and EVERPure**

**Pure Maintenance** Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com info@MoldREPORT.com

Approved by:

Operations Manager Joshua Cox

Dates of Analysis: MoldReport Direct exam: 03-27-2017

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or EMLab P&K ("the Company") shall have no liability to the client or the client or customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client sustomer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

MoldREPORT

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall Fort Campbell Before Treatment

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

### Laboratory Results

### MoldREPORT: Spore Trap Analysis

Location:	1: #1 North West Corner BT		2: #2 Middle West Side BT		3: #3 South East Kitchen BT	
Comments (see below)	None			lone	1	Vone
Lab ID-Version‡:	792	1457-1	792	1458-1	792	1459-1
Analysis Date:	03/2	7/2017	03/2	7/2017	03/2	7/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-	-	-	-	_	-
Basidiospores	-	-	-	-	-	-
Chaetomium	Am	-	-	-	-	_
Cladosporium	345	18,000	175	47,000	203	110,000
Fusarium	**	-	-	-	-	-
Penicillium/Aspergillus types	1	53	18	960	_	_
Stachybotrys		-	-	-	-	_
Trichoderma	-	-	-	-	_	_
Ulocladium	-	-	-	-	_	_
Others	6	320	7	370	2	110
§ Total:		19,000		48,000		110,000
Additional Information:						110,000
Hyphal fragments	1,	300	2,000		2,700	
Skin cells	80 - 4,000		80 - 4,000		80 - 4,000	
Pollen	53		< 13		110	
Background debris (1-4)†	3		4		3	
Limit of detection		13		13		13
Sample volume (liters)		75		75		75

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Peniclium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699377, Page 2 of 3

<sup>‡</sup> A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".
† Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

Project: Mess Hall Fort Campbell Before Treatment

Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

MoldREPORT EMLab P & K

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

### Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	4: #4 South West Office BT		9: Outside #5 Air Sample	
Comments (see below)	1	None	None	
Lab ID-Version‡:	792	1460-1	792	1461-1
Analysis Date:	03/2	27/2017	03/2	7/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-		-	-
Basidiospores	10	530	2	110
Chaetomium	-	-	-	-
Cladosporium	33	1,800	9	480
Fusarium	-		-	-
Penicillium/Aspergillus types	69	3,700	-	
Stachybotrys	390	520,000		-
Trichoderma	-		-	-
Ulocladium	-	•	-	-
Others	2	110	-	-
§ Total:		530,000		590
Additional Information:				
Hyphal fragments	5	,800	110	
Skin cells	80 -	4,000	13	- 67
Pollen	< 13		370	
Background debris (1-4)†	2			1
Limit of detection		13		13
Sample volume (liters)		75		75

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange the state of the conditions. exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699377, Page 3 of 3

<sup>‡</sup> A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".
† Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall Fort Campbell Before Treatment Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017

Date of Report: 03-27-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# **Laboratory Results**

#### MoldREPORT: Direct Microscopic Examination

Location:	5: #6 Middle Divider Wall	6: #7 West Wall	7: #8 Kitchen Wall
Comments (see below):	None	None	None
Lab ID-Version‡:	7921454-1	7921455-1	7921456-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-	-	-
Chaetomium	-	-	-
Cladosporium	2+	2+	2+
Fusarium	-	-	-
Lumber mold†	-	-	···
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	
Trichoderma	-	-	-
Ulocladium	-	-	-
Spore types present (not indicative of mold growth)§:			
All spore types	Very few	Very few	Very few
Other particles detected§:			
Skin cells	Very few	Very few	Very few
Pollen	-	•	
Background Debris and/or Description**:	Moderate	Moderate	Moderate

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

†Lumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant, Moderate, Heavy, or Very Heavy. Very Heavy beckground debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported.

‡ A "Version" indicated by "\*" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

The limit of detection is < 1+ when mold growth is detected.

§All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Aerotech Laboratories, Inc

EMLab ID: 1699377, Page 2 of 2

MoldREPORT EMLab P & K

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Head Fort Campbell Before Treatment

Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

### MoldREPORT: Spore Trap Analysis

Location:	1: #10 North West Classroom BT		2: #11 Mens Bathroom BT	
Comments (see below)		None	1	None
Lab ID-Version‡:	792	21647-1	792	1648-1
Analysis Date:	03/	27/2017	03/2	27/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-	-	-	-
Basidiospores	-	-	1	53
Chaetomium	-	-	-	-
Cladosporium	2,672	1,400,000	1	53
Fusarium	-	-	-	
Penicillium/Aspergillus types	-	-	197	110,000
Stachybotrys	-	-	-	-
Trichoderma	-	-	-	-
Ulocladium	3	40	-	-
Others	1	13	1	53
§ Total:		1,400,000		110,000
Additional Information:				
Hyphal fragments		160		110
Skin cells	13	- 67	80 -	4,000
Pollen		< 13		< 13
Background debris (1-4)†	1			2
Limit of detection		13		13
Sample volume (liters)		75		75

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicllium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

† Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699368, Page 2 of 3

MoldREPORT EMLab P & K

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Head Fort Campbell Before Treatment

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:		3: #12 Basement BT		10: Hammerhead	
Comments (see below)	N	None		lone	
Lab ID-Version‡:	792	1649-1	792	1650-1	
Analysis Date:	03/2	7/2017	03/2	7/2017	
Spore types detected:	raw ct.	per m3	raw ct.	per m3	
Aureobasidium	-	-	-	_	
Basidiospores	19	1,000	23	1,200	
Chaetomium	1	13	_	-	
Cladosporium	30	1,600	22	1,200	
Fusarium		-	-	-	
Penicillium/Aspergillus types	8	430	4	210	
Stachybotrys	5	67		-	
Trichoderma	-	-	-	-	
Ulocladium	-	*		-	
Others	6	320	10	530	
§ Total:		3,400		3,100	
Additional Information:					
Hyphal fragments		110	-		
Skin cells		4,000	The second control of	- 67	
Pollen	<	< 13		110	
Background debris (1-4)†		2		2	
Limit of detection		13		13	
Sample volume (liters)		75		75	

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicllium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699368, Page 3 of 3

<sup>‡</sup> A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the

The restormal indicated by - x after the Lab ID# with a value greater than 1 indicates a sample with antistact data. The revision futures is reflected by the value of "x".

† Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Head Fort Campbell Before Treatment

Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# **Laboratory Results**

## MoldREPORT: Direct Microscopic Examination

Location:	5: #14 Basement South Wall BT	6: #15 Mens Bathroom South Wall BT	7: #16 North Wall Of North West Classroom BT
Comments (see below):	None	None	None
Lab ID-Version‡:	7921644-1	7921645-1	7921646-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-	-	-
Chaetomium	-	-	-
Cladosporium	2+	-	4+
Fusarium	-	-	-
Lumber mold†	-	-	-
Penicillium/Aspergillus types	-	4+	-
Stachybotrys	-	-	-
Trichoderma	-	-	-
Ulocladium	-	-	-
Spore types present (not indicative of mold growth)§:			
All spore types	Very few	-	-
Other particles detected§:			
Skin cells	Very few	-	=
Pollen	-		-
Background Debris and/or Description**:	Light	Scant	None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

<sup>\*\*</sup>PLumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant, Moderate, Heavy, or Very Heavy. Very heavy background debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported.

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of 'x".

The limit of detection is < 1+ when mold growth is detected.

§All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

EMILab ID: 1699368, Page 2 of 2

MoldREPORT

EMLab P & K

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall Fort Campbell After Treatment

Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

MoldDEPORT: Snore Tran Analysis

MoldREPORT: Spore Trap Aliasy Location:	1: #1A North West Corner AT		2: #2A Middle West Side AT		3: #3A South East Kitchen AT	
Comments (see below)	N	one	N	one		one
Lab ID-Version‡:	7925	892-1	7925	5893-1	7925	5894-1
	03/2	7/2017	03/2	7/2017	03/2	7/2017
Analysis Date:	raw ct.	per m3	raw ct.	per m3	raw ct.	per m3
Spore types detected:			ILW CL	-	-	-
Aureobasidium	-	110	2	110	2	110
Basidiospores	2	110	2	-		-
Chaetomium	-	1000	42	2,200	25	1,300
Cladosporium	92	4,900		2,200	Lund	1,500
Fusarium	-		- 107	10,000	198	11,000
Penicillium/Aspergillus types	185	9,900	187	10,000		11,000
Stachybotrys	-	-	-	-	-	
Trichoderma	-	-	-	-		-
Ulocladium	-	-	-	-	-	-
Others	-	-	2	110	-	10,000
§ Total:		15,000		12,000		12,000
Additional Information:						
Hyphal fragments	The second secon	430	_		- 1000	
Skin cells	80 - 4,000		13 - 67		80 - 4,000	
Pollen	53		< 13		< 13	
Background debris (1-4)†	2		1		2	
Limit of detection		13		13		13
Sample volume (liters)		75		75		75

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

- ‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the
- value of "x". † Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc EMLab ID: 1699379, Page 2 of 3

MoldREPORT

Project: Mess Hall Fort Campbell After Treatment

Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

### MoldREPORT: Spore Trap Analysis

Location:	4: #4A South West Office AT		9: Outside #5 Air Sample	
Comments (see below)	N	Vone		A
Lab ID-Version‡:	792	5895-1	792	1561-0
Analysis Date:	03/2	7/2017		7/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-	-	-	-
Basidiospores	-	*	2	110
Chaetomium	-	-	-	-
Cladosporium	11	590	9	480
Fusarium	-	-	-	
Penicillium/Aspergillus types	197	11,000	-	-
Stachybotrys	-	-	-	
Trichoderma	-	-	-	-
Ulocladium	-	-	_	_
Others	_	-	-	-
§ Total:		11,000		590
Additional Information:				
Hyphal fragments		-	110	
Skin cells	13	- 67		- 67
Pollen	< 13		370	
Background debris (1-4)†	1		1	
Limit of detection		13		13
Sample volume (liters)		75		75

Comments: A) Data transferred from EMLab ID: 1699377 at client's request.

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the

value of "x".

Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699379, Page 3 of 3

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall Fort Campbell After Treatment

Date of Sampling: 03-20-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# **Laboratory Results**

## MoldREPORT: Direct Microscopic Examination

Location:	5: #6A Middle Divider Wall AT	6: #7A West Wall AT	7: #8A Kitchen Wall AT
Comments (see below):	None	None	A
Lab ID-Version‡:	7921486-1	7921487-1	7921488-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-		-
Chaetomium		lai.	-
Cladosporium	-	-	< 1+
Fusarium	-	-	-
Lumber mold†	-	-	-
Penicillium/Aspergillus types	-	*	
Stachybotrys	-	*	-
Trichoderma	-		-
Ulocladium	-	-	-
Spore types present (not indicative of mold growth)§:			
All spore types	Very few	Very few	Very few
Other particles detected§:			
Skin cells	Very few	Very few	Very few
Pollen	-	-	-
Background Debris and/or Description**:	Light	Light	Light

Comments: A) A few Penicillium/Aspergillus group spores detected.

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

†Lumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant, Moderate, Heavy, or Very Heavy. Very heavy background debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported..

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

The limit of detection is < 1+ when mold growth is detected.

§All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Aerotech Laboratories, Inc.

EMLab ID: 1699379, Page 2 of 2

MoldREPORT

EMLab P & K

Project: Hammer Head Fort Campbell After Treatment Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	1: #10A North West Classroom AT		2: #11A Mens Bathroom AT	
Comments (see below)	N	Vone	None	
Lab ID-Version‡:	792	1657-1	792	1658-1
Analysis Date:	03/2	27/2017	03/2	27/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium		-	-	-
Basidiospores	-	-		-
Chaetomium	-	-	-	~
Cladosporium	-		-	-
Fusarium	-		-	-
Penicillium/Aspergillus types	388	210,000	191	100,000
Stachybotrys	-		-	-
Trichoderma	-		-	-
Ulocladium	-		-	-
Others	-	-	1	53
§ Total:		210,000		100,000
Additional Information:				
Hyphal fragments	A THE STATE OF THE	-		-
Skin cells		- 67		3 - 67
Pollen	< 13			< 13
Background debris (1-4)†	1		2	
Limit of detection		13		13
Sample volume (liters)		75		75

#### Comments:

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicllium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor growth.

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".
† Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

The analytical sensitivity is the spores/ $m^3$  divided by the raw count, expressed in spores/ $m^3$ . The limit of detection is the analytical sensitivity (in spores/ $m^3$ ) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc

EMLab ID: 1699373, Page 2 of 3

Project: Hammer Head Fort Campbell After Treatment

Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

MoldREPORT

EMLab P & K

1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

MoldREPORT: Spore Trap Analysis

Location:	3: #12A Basement AT		10: #17 Outside Hammerhead	
Comments (see below)	None		A	
Lab ID-Version‡:	792	1659-1	792	1660-0
Analysis Date:	03/2	7/2017	03/2	7/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-		-	-
Basidiospores	-	-	23	1,200
Chaetomium	-	44		-
Cladosporium	189	10,000	22	1,200
Fusarium	-	-	-	
Penicillium/Aspergillus types	53	2,800	4	210
Stachybotrys	-		-	
Trichoderma	-	-	-	-
Ulocladium	-	-	-	-
Others		-	10	530
§ Total:		13,000		3,100
Additional Information:				
Hyphal fragments		53	-	
Skin cells	13 - 67		13 - 67	
Pollen	< 13		110	
Background debris (1-4)†	2		2	
Limit of detection		13		13
Sample volume (liters)		75		75

Comments: A) Data transferred from EMLab ID: 1699368 at client's request.

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor

- ‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the
- † Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

The analytical sensitivity is the spores/m^3 divided by the raw count, expressed in spores/m^3. The limit of detection is the analytical sensitivity (in spores/m^3) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Rev02 03/11 Aerotech Laboratories, Inc

EMLab ID: 1699373, Page 3 of 3

Project: Hammer Head Fort Campbell After Treatment

Date of Sampling: 03-21-2017 Date of Receipt: 03-24-2017 Date of Report: 03-27-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# **Laboratory Results**

# MoldREPORT: Direct Microscopic Examination

Location:	5: #14A Basement South Wall AT	6: #15A Mens Bathroom South Wall AT	7: #16A North Wall Of North West Classroom AT
Comments (see below):	None	None	None
Lab ID-Version‡:	7921654-1	7921655-1	7921656-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-	•	-
Chaetomium	-	-	-
Cladosporium	-	-	< 1+
Fusarium	-	-	-
Lumber mold†	-	-	-
Penicillium/Aspergillus types	-	2+	-
Stachybotrys	-	-	-
Trichoderma	-	-	-
Ulocladium	-	-	-
Spore types present (not indicative of mold growth)§:			
All spore types	Very few	Very few	Very few
Other particles detected§:			
Skin cells	Very few	Very few	Few
Pollen	-	-	-
Background Debris and/or Description**:	Scant	Light	Light

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

\*\*Lumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant, Moderate, Heavy, or Very Heavy background debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported..

‡ A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

The limit of detection is < 1+ when mold growth is detected.

§All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Aerotech Laboratories, Inc.

EMLab ID: 1699373, Page 2 of 2

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 04-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Client: Pure Maintenance

MoldREPORT

Contact: Mr Brandon Adams Project: Mess Hall 1 Month Post Treatment

Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017 Date of Report: 04-28-2017 EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:		1:		2:		3:
	Northwes	t Corner A1	Middle W	est Side A1	South Wo	st Office A1
Comments (see below)	7.	one	N	one	N	one
Lab ID-Version*:	8013	2803-1	8013	2804-1	8013	2805-1
Analysis Date:	04/2	8/2017	04/2	8/2017	. 04/2	8/2017
Spore types detected:	raw et.	per m3	raw et.	per m3	raw et.	per m3
Aureobasidium	<u> </u>	-	-	-	-	_
Basidiospores	5 .	270	10	530	14	750
Chaetomium		-	_	-	1	13
Cladosporium	13	690	7	370	-	-
Fusarium		-	-	-	-	-
Penicillium/Aspergillus types	5	270	5	270	17	910
Stachybotrys		-	-	-	-	-
Trichoderma	- '	-	-	-	-	-
Ulocladium	-	-	-	-	-	-
Others	7	370	4	210	6	320
§ Total.		1,600		1,400		2,000
Additional Information:						
Hyphal fragments		-				-
Skin cells	80 -	4,000	80 -	4,000	80 -	4,000
Pollen	4	13	43	: 13		53
Background debris (1-4)†		2		2	-	2
Limit of detection		13		13		13
Sample volume (liters)		75		75	•	75

#### Comments:

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicillium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium. Chaetomium, Fusarium, Trichederma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the sporesim\*3 divided by the raw count, expressed in spores/m\*3. The limit of detection is the analytical sensitivity (in spores/m\*3) multiplied by the sample volume (in liters) divided by 1000 liters.

 $\S$  Total has been rounded to two significant figures to reflect analytical precision.

Rev 00, 03/11

Aerotech Laboratories, Inc.

EMLab ID: 1717739, Page 2 of 3

<sup>7</sup> A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4

<sup>\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts.

**Client: Pure Maintenance** Contact: Mr Brandon Adams Project: Mess Hall 1 Month Post Treatment

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017 Date of Report, 04-28-2017

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	South Eas	4: t Kitchen A1	6; Outside 5A1	
Comments (see below)	V	Jone	l N	Vone
Lab ID-Version‡:	801	2806-1	801	2807-1
Analysis Date:	04/2	8/2017	04/2	28/2017
Spore types detected:	raw et.	per m3	raw ct.	per m3
Aureobasidium			-	-
Basidiospores	14	750	99	26,000
Chaetomium	-	-	-	-
Cladosporium	-	-	17	910
Fusarium	-	-	-	-
Penicillium/Aspergillus types	. 10	530	3	160
Stachybotrys	-	-	-	-
Trichoderma	-	-	-	-
Ulocladium	]	-	]	-
Others	13	690	122	6,500
§ Total	:_	2,000		34,000
Additional Information:				
Hyphal fragments		-		-
Skin cells	80 - 4,000		13 - 67	
Pollen	< 13		750	
Background debris (1-4)*	2		2	
Limit of detection		13	1.3	
Sample volume (liters)		75		75

#### Comments:

Basidiospores (basidiomycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladesporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladesporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores/m<sup>3</sup>3 divided by the raw count, expressed in spores/m<sup>3</sup>5. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>5) multiplied by the sample volume (in liters) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1717739, Page 3 of 3

<sup>1</sup> A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

Background debris is an indication of the amounts of non-biological particulate matter present on the slide (dust in the air) and is graded from 1 to 4 with 4.

indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 04-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Aerotech Laboratories, Inc

EMLab ID: 1717739, Page 1 of 2

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall 1 Month Post Treatment

Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017 Date of Report: 04-28-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651 4962 P (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

### MoldREPORT: Direct Microscopic Examination

Location:	7: Middle Divider Wall	8: Kitchen Wall	9: West Wall
Comments (see below):	None	A	None
Lab ID-Version‡:	8012800-1	8012 <b>8</b> 01-1	8012802-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-		-
Chaetomium	-	<b>-</b>	-
Cladosporium	· -	<u>-</u>	-
Fusarium		-	-
Lumber mold†	-	•	-
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	-
Trichoderma	` -	- '	-
Ulocladium			-
Spore types present (not indicative of mold growth)§:			
All spore types	-	Very few	-
Other particles detected§:			
Skin cells	Very few	Very few	Very few
Pollen	•	-	-
Background Debris and/or Description**:	Light	Scant	Light

Comments: A) A few Penicillium/Aspergillus group spores detected.

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Aerotech Laboratories, Inc

EMLab ID: 1717739, Page 2 of 2

<sup>†</sup>Lumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.
"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Very heavy background debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported.

‡ A "Version" indicated by "X" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "X".

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www.MoldREPORT.com info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 04-28-2017 and 04-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 1 Month Post Treatment Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017

Date of Report: 04-28-2017

### Laboratory Results

# MoldREPORT: Spore Trap Analysis

Location:	1: Mens Bathroom HA1		2: Northwest Classroom 10A1	
Comments (see below)		ione	Ŋ	lone
Lab ID-Version‡:	801.	3119-1	801.	3120-1
Analysis Date.	04/2	8/2017	04/3	8/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-	-		-
Basidiospores	2	110	9	480
Chaetomium		-	-	-
Cladosporium	1 .	53	. 1	53
Fusarium		-		-
Penicillium/Aspergillus types	16	850	3	160
Stachybotrys		-		-
Trichoderma	-	-	-	-
Ulocladium		-		-
Others	2 .	110	. 9 .	480
§ Total:		1,100		1,200
Additional Information:				
Hyphal fragments		-		-
Skin cells	4,000 - 8,000		13 - 67	
Pollen	~ 13		. 110	
Background debris (1-4)†	3			1
Limit of detection		1.3	13	
Sample volume (liters)		75		75

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1717764, Page 2 of 3

 $<sup>\</sup>equiv A$  "Version" indicated by "x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 1 Month Post Treatment Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017

Date of Report: 04-28-2017

### Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	Basem	3: ent 12A1	5: Outside 17.\1	
Comments (see below)	>	ione	1	lone
Lab ID-Version‡:	801	3121-1	801	3122-1
Analysis Date.	04/0	8/2017	04/0	8/2017
Spore types detected:	raw ct.	per m3	raw ct.	per m3
Aureobasidium	-	-	<u>-</u>	-
Basidiospores	29	1,500	21	1,100
Chaetomium		-		-
Cladosporium	7	370	. 3	160
Fusarium		-		-
Penicillium/Aspergillus types	4	210	4	210
Stachybotrys		-		-
Trichoderma	-	-	-	-
Ulocladium		-		-
Others	22	1,200	124	6,600
§ Total:		3,300		8,100
Additional Information:				
Hyphal fragments		-		-
Skin cells	13 - 67		13 - 67	
Pollen	~ 13		. 110	
Background debris (1-4)*	2			
Limit of detection		1.3		13
Sample volume (liters)		75		75

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1717764, Page 3 of 3

Z.A."Version" indicated by ."x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 04-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Acrotech Laboratories, Inc

EMLab ID: 1717764, Page 1 of 2

MoldREPORT

(800) 651-4802 Fax (623) 780-7695

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 1 Month Post Treatment

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651 4962 P

Date of Sampling: 04-25-2017 Date of Receipt: 04-27-2017 Date of Report: 04-28-2017

# Laboratory Results

### MoldREPORT: Direct Microscopic Examination

Location:	6: Bathroom Southwall	7: Basement Southwall	8: Northwest Classroom
Comments (see below):	None	None	None
Lab ID-Version‡:	8013116-1	8013117-1	8013118-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	<u>-</u>	-	-
Chaetomium	•	- :	-
Cladosporium	•	-	-
Fusarium	. •	-	•
Lumber mold†	<u>-</u>	-	-
Penicillium/Aspergillus types	-	-	-
Stachybotrys	- -	-	-
Trichoderma	· -	-	-
Ulocladium			-
Spore types present (not indicative of mold growth)§:			
All spore types	· -	Very few	Very few
Other particles detected§:			
Skin cells	Very few	Very few	Very few
Pollen	•	-	-
Background Debris and/or Description**:	Scant	Light	Scant

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

<sup>†</sup>Lumber mold: Fungi in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.
"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Very heavy background debris may obscure visibility for the analyst. Some sample types are not graded for background debris, in which case a brief description of the material is reported.

‡ A "Version" indicated by "X" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "X".

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www. MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 06-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Head AT MoldREPORT

EMIlab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	()ı	1: utside	2: Basement	
Comments (see below)		ione		A
Lab ID-Version‡:	817	1009-1	. 817	1010-1
Analysis Date.	06/0	18/2017	06/2	8/2017
Spore types detected:	raw et.	per m3	raw ct.	per m3
Aureobasidium	-	-	-	-
Basidiospores	42	5,600	4	2]11
Chaetomium		-		-
Cladosporium	8	430	50	870
Fusarium	- [	-	·	-
Penicillium/Aspergillus types	2	110	<u> </u>	53
Stachybotrys	1 _	13		-
Trichoderma	-	-	<u>-</u>	-
Ulocladium		-		-
Others	61	8,100	2	110
§ Total:		14,000		1,200
Additional Information:				
Hyphal fragments		-		-
Skin cells	13 - 67		13	- 67
Pollen	~ 13		~ I3	
Background debris (1-4)*	1		1	
Limit of detection		13	13	
Sample volume (liters)		75		75

Comments: A) 45 of the raw count Cladosporium spores were present as a single clump.

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woodlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors.

Pencellium/Aspergillus types: Peniellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types. Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Others: Molds in the "Others" category are generally found outdoors in moderate numbers, and are therefore not considered markers of indoor growth

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1749926, Page 2 of 3

<sup>[</sup>A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Head AT MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

### Laboratory Results

# MoldREPORT: Spore Trap Analysis

Location:	3: N.W. Classroom		4: Mens Bathroom	
Comments (see below)		one	7	lone
Lab ID-Version‡:	817	101 <b>1</b> -1	817	1012-1
Analysis Date.	06/2	8/2017	06/2	8/2017
Spore types detected:	raw et.	per m3	raw ct.	per m3
Aureobasidium	-	-	<u>-</u>	-
Basidiospores	-	-	-	-
Chaetomium		-		-
Cladosporium	3	160	1	53
Fusarium		-		-
Penicillium/Aspergillus types	3	160	5	270
Stachybotrys		-		-
Trichoderma	-	-	-	-
Ulocladium		-		-
Others	2 .	110	3	160
§ Total:		430		480
Additional Information:				
Hyphal fragments		-		-
Skin cells	13 - 67		13 - 67	
Pollen	~ 13		% L3	
Background debris (1-4)*	1			
Limit of detection	1.3		13	
Sample volume (liters)		75		75

#### Comments:

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pencetilium/Aspergillus types: Pencellium and Aspergillus are among the most common molds found growing both indoors and outdoors feven in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in nuclerate numbers, and are therefore not considered markers of indeor growth.

The analytical sensitivity is the spores mind divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores mind) multiplied by the sample volume (in literal divided by 1006 liters).

§ Total has been rounded to two significant figures to reflect analytical precision.

neod 591 Aerotech Laboratories, Inc.

EMLab ID: 1749926, Page 3 of 3

<sup>[</sup>A "Version" indicated by -"x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 06-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Acrotech Laboratories, Inc

EMLab ID: 1749926, Page 1 of 2

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammer Hend AT

Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

MoldREPORT EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4860 Feb. (62) (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

# MoldREPORT: Direct Microscopic Examination

Location:	7: Basement	8: Classroom	9: Mens Bathroom
Comments (see below):	None	None	None
Lab ID-Version‡:	8171006-1	8171007-1	8171008-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-	-	•
Chaetomium	-	-	-
Cladosporium	-	-	•
Fusarium	•	-	-
Lumber mold†	-	-	
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	•
Trichoderma	-	-	
Ulocladium	-	-	<u> </u>
Spore types present (not indicative of mold growth)§:			•
All spore types	Very few	-	•
Other particles detected§:			-
Skin cells	Moderate	Very few	Very few
Pollen	Very few	-	-
Background Debris and/or Description**:	Light	Scant	Scant

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium. Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

<sup>†</sup>Lumber mold: Fungl in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Levy heavy beckground debris may obscure visibility for the analyst. Some sample types are not graded for background debris. In which case a brief description of the material is reported.

‡ A "Version" indicated by ""," after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of 'x."

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 06-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT Date of Sampling: 06-22-2017 Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

### Laboratory Results

# MoldREPORT: Spore Trap Analysis

Location:	Ou	1: tside		2: Corner		3: Office
Comments (see below)	N	one	N N	one	N	one
Lab ID-Version‡:	817	1189-1	817	1190-1	817	1191-1
Analysis Date.	06/2	8/2017	06/2	8/2017	06/2	8/2017
Spore types detected:	raw et.	per m3	raw et.	per m3	raw et.	per m3
Aureobasidium	-	-	-	-	_	-
Basidiospores	97	5,200	2	27	7	370
Chaetomium	-	-	-	-	, l	13
Cladosporium	10	530	-	-	24	1,300
Fusarium	-	-	-	-		-
Penicillium/Aspergillus types	2	110	9	120	5	270
Stachybotrys	- ]	-	_ ]	-		-
Trichoderma	-	-	-	-	-	-
Ulocladium	-	-	-	-		-
Others	611	3,200	2	27	1.3	690
§ Total:		9,000		170		2,600
Additional Information:						
Hyphal fragments		-		-		-
Skin cells	13	- 67	13	- 67	13	- 67
Pollen	-	. 13	٠.	- 13		: 13
Background debris (1-4)*		3		1		2
Limit of detection		13		13		13
Sample volume (liters)		75		75		75

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1749950, Page 2 of 3

 $<sup>\</sup>equiv A$  "Version" indicated by "x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT Date of Sampling: 06-22-2017 Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

### Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	4: Middle West		5: S.E. Comer	
Comments (see below)		one	7	lone
Lab ID-Version‡:	817	1192-1	817	1193-1
Analysis Date.	06/2	8/2017	06/2	8/2017
Spore types detected:	raw et.	per m3	raw ct.	per m3
Aureobasidium	-	-	<u>-</u>	-
Basidiospores	2	110	8	4311
Chaetomium		-		-
Cladosporium	1 .	53	23	1,200
Fusarium		-		-
Penicillium/Aspergillus types	]	53	5	270
Stachybotrys		-		-
Trichoderma	-	-	-	-
Ulocladium		-		-
Others	5 .	270	, 16	850
§ Total:		480		2,800
Additional Information:				
Hyphal fragments		-		-
Skin cells	13 - 67		13 - 67	
Pollen	~ 13		~ 13	
Background debris (1-4)*	1		1	
Limit of detection	1.3		13	
Sample volume (liters)		75		75

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1749950, Page 3 of 3

Z.A."Version" indicated by ."x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 06-28-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Acrotech Laboratories, Inc

EMLab ID: 1749950, Page 1 of 2

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT Date of Sampling: 06-22-2017 Date of Receipt: 06-27-2017 Date of Report: 06-28-2017

MoldREPORT EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4860 Feb. (62) (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

### MoldREPORT: Direct Microscopic Examination

Location:	7: Kitchen	8: West Wall	9: Divider Wall
Comments (see below):	None	None	None
Lab ID-Version‡:	8171186-1	8171187-1	8171188-1
Spore types present (indicative of mold growth)§:			•
Aureobasidium	-	-	<u>-</u>
Basidiospores	-	-	•
Chaetomium	-	-	-
Cladosporium			<u>-</u> _
Fusarium	-	•	-
Lumber mold†	-	-	-
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	<u>-</u>
Trichoderma	-	-	-
Ulocladium	-	<u>-</u>	<u>-</u>
Spore types present (not indicative of mold growth)§:		,	
All spore types	-	-	
Other particles detected§:			
Skin cells	-	-	
Pollen	-	-	- -
Background Debris and/or Description**:	Scant	Light	Light

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium. Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

<sup>†</sup>Lumber mold: Fungl in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Levy heavy beckground debris may obscure visibility for the analyst. Some sample types are not graded for background debris. In which case a brief description of the material is reported.

‡ A "Version" indicated by ""," after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of 'x."

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 09-19-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT 6 Months Date of Sampling: 09-12-2017 Date of Receipt: 09-18-2017 Date of Report: 09-19-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	1: NW Corner		2: Sw Office		3: Middle West		
Comments (see below)	N	one	N N	one	None		
Lab ID-Version‡:	8397	7804-1	8391	7805-1	8397806-1		
Analysis Date.	09/19	9/2017	09/1	9/2017	09/1	9/2017	
Spore types detected:	raw et.	per m3	raw et.	per m3	raw ct.	per m3	
Aureobasidium	-	-	-	-	_	-	
Basidiospores	16	850	16	850	17	910	
Chaetomium	-	-	-	-		-	
Cladosporium	7	370	11	590	11	590	
Fusarium	-	-	-	-		-	
Penicillium/Aspergillus types	5	270	28	1,500	4	210	
Stachybotrys	-	-		-		-	
Trichoderma	-	-	-	-	-	-	
Ulocladium	-	-	-	-		-	
Others	25	1,300	26	1,400	1.5	800	
§ Total:		2,800		4,300		2,500	
Additional Information:							
Hyphal fragments		-		-		53	
Skin cells	13	- 67	13	- 67	80 -	4,000	
Pollen	*- 13		~ 13		< 13		
Background debris (1-4)*		2		2		` 2	
Limit of detection		13		13		13	
Sample volume (liters)		75		75		75	

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1795837, Page 2 of 3

Z.A."Version" indicated by ."x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT 6 Months Date of Sampling: 09-12-2017 Date of Receipt: 09-18-2017 Date of Report: 09-19-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

# MoldREPORT: Spore Trap Analysis

Location:	4: South East Office		5: Outside		
Comments (see below)		ione	None 8397808-1		
Lab ID-Version‡:	839	7807-1			
Analysis Date.	09/1	9/2017	09/1	9/2017	
Spore types detected:	raw ct.	per m3	raw ct.	per m3	
Aureobasidium	-	-		-	
Basidiospores	15	800	148	7,900	
Chaetomium		-		-	
Cladosporium	16	850	45	2,400	
Fusarium	-	-	-	-	
Penicillium/Aspergillus types	2	110	4	210	
Stachybotrys		-		-	
Trichoderma	-	-	-	-	
Ulocladium		-		-	
Others	20	1,100	164	8,700	
§ Total:		2,800		19,000	
Additional Information:					
Hyphal fragments		53		-	
Skin cells	13 - 67		13 - 67		
Pollen		- 13	~ I3		
Background debris (1-4)†		3		3	
Limit of detection		1.3	13		
Sample volume (liters)		75		75	

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1795837, Page 3 of 3

 $<sup>\</sup>equiv A$  "Version" indicated by "x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 09-19-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Aerotech Laboratories, Inc

EMLab ID: 1795837, Page 1 of 2

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Mess Hall AT 6 Months Date of Sampling: 09-10-2017 Date of Receipt: 09-18-2017

Date of Report: 09-19-2017

MoldREPORT EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4860 Feb. (62) (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

# MoldREPORT: Direct Microscopic Examination

Location:	6: West Wall	7: Kitchen Wall	8: Divider Wall
Comments (see below):	None	None	None
Lab ID-Version‡:	8397801-1	8397802-1	8397803-1
Spore types present (indicative of mold growth)§:			•
Aureobasidium	-	-	-
Basidiospores	-	- '	-
Chaetomium	-	-	<u>-</u>
Cladosporium	-	- '	-
Fusarium	•	-	-
Lumber mold†	-	-	-
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	•
Trichoderma	-	-	-
Ulocladium	<u>-</u>	-	<u>-</u>
Spore types present (not indicative of mold growth)§:			
All spore types	-	-	
Other particles detected§:			
Skin cells	-	Very few	Very few
Pollen	-	-	- -
Background Debris and/or Description**:	None	Scant	Light

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium. Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

Aerotech Laboratories, Inc

EMLab ID: 1795837, Page 2 of 2

<sup>†</sup>Lumber mold: Fungl in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Levy heavy beckground debris may obscure visibility for the analyst. Some sample types are not graded for background debris. In which case a brief description of the material is reported.

‡ A "Version" indicated by ""," after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of 'x."

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300 Bountiful, UT 84010 USA (801) 529-2976





EMLab P & K

www.MoldREPORT.com

info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Spore trap: 09-19-2017 and 09-19-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Spore trap (EM-MY-S-1038) AIHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

The analytical sensitivity is the spores/m<sup>3</sup> divided by the raw count, expressed in spores/m<sup>3</sup>. The limit of detection is the analytical sensitivity (in spores/m<sup>3</sup>) multiplied by the sample volume (in liters) divided by 1000 liters.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

MoldREPORT

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 6 Months AT Date of Receipt: 09-12-2017 Date of Receipt: 09-18-2017 Date of Report: 09-19-2017

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	1: Northwest Classroom		2: Mens Restroom		
Comments (see below)	>	Cone	None 8397837-1 09/19/2017		
Lab ID-Version‡:	839	7836-1			
Analysis Date.	09/1	9/2017			
Spore types detected:	raw ct.	per m3	raw ct.	per m3	
Aureobasidium	-	-		_	
Basidiospores	2	27	1	53	
Chaetomium		-			
Cladosporium		-			
Fusarium		-			
Penicillium/Aspergillus types	]	13	2	110	
Stachybotrys		-	,		
Trichoderma	-	-	-	-	
Ulocladium		-			
Others	4 .	53	. 1	. 53	
§ Total:		93		210	
Additional Information:					
Hyphal fragments		-	,	-	
Skin cells	13 - 67		13 - 67		
Pollen	4.	- 13	~ 13		
Background debris (1-4)*		]		3	
Limit of detection		1.3	13		
Sample volume (liters)		75		75	

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

neod sen Aerotech Laboratories, Inc

EMLab ID: 1295834, Page 2 of 3

Z.A."Version" indicated by ."x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

MoldREPORT EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4802 Fax (623) 780-7695

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 6 Months AT Date of Receipt: 09-12-2017 Date of Receipt: 09-18-2017 Date of Report: 09-19-2017

# Laboratory Results

#### MoldREPORT: Spore Trap Analysis

Location:	3: Basement		4: Outside			
Comments (see below)		one	, N	lone		
Lab II)-Version‡:	839	7838-1	8397839-1			
Analysis Date.	09/1	9/2017	09/1	9/2017		
Spore types detected:	raw et.	per m3	raw ct.	per m3		
Aureobasidium	-	-	-	-		
Basidiospores	52	2,800	193	10,000		
Chaetomium		-		-		
Cladosporium	8	430	13	690		
Fusarium		-		-		
Penicillium/Aspergillus types	75	4,000	1	53		
Stachybotrys		-		-		
Trichoderma	-	-	-	-		
Ulocladium		-		-		
Others	55	2,900	164	8,700		
§ Total:		10,000		20,000		
Additional Information:						
Hyphal fragments		-		-		
Skin cells	13 - 67		13 - 67			
Pollen	~ <b>13</b>		. 53			
Background debris (1-4)†		1	1			
Limit of detection		1.3	13			
Sample volume (liters)		75		75		

Basidiospores (basidiornycetes): Basidiospores are extremely common outdoors and originate from fungi in gardens, forests, and woedlands. It is rare for the source of basidiospores to be indoors. However, basidiospores may be an indicator of wood decay.

Cladosperium: One of the most commonly found molds outdoors and frequently found growing indoors. Spores from Cladosporium are generally present in outdoor and indoor air, even in relatively clean, mold-growth-free, indoor environments. Levels vary based upon activity levels, weather conditions, dustiness, outside air exchange rates, and other factors

Pemertilium Aspergillus types: Pemellium and Aspergillus are among the most common molds found growing both indoors and outdoors (even in relatively clean, mold-growth-free, indoor environments). Levels vary based upon activity levels, dustiness, weather conditions, outside air exchange rates, and other factors.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium, Chaetomium, Fusanium, Trichoderma, and Ulceladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem

Others: Molds in the "Others" category are generally found outdoors in moderate mimbers, and are therefore not considered markers of indoor growth.

The analytical sensitivity is the spores mi3 divided by the raw count, expressed in spores in 3. The limit of detection is the analytical sensitivity (in spores in 3) multiplied by the sample volume (in litera) divided by 1000 liters.

§ Total has been rounded to two significant figures to reflect analytical precision.

Aerotech Laboratories, Inc.

EMLab ID: 1295834, Page 3 of 3

Z.A."Version" indicated by ."x" after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of "x".

<sup>\*\*</sup> Background debris is an indication of the amounts of non-biological particulate matter present on the slide plust in the air) and is graded from 1 to 4 with 4 indicating the largest amounts

Pure Maintenance Mr Brandon Adams 596 w 750 s Suite 300





EMLab P & K

www.MoldREPORT.com info@MoldREPORT.com

Approved by:

Dates of Analysis: MoldReport Direct exam: 09-19-2017

Operations Manager Joshua Cox

Service SOPs: MoldReport Direct exam (EM-MY-S-1039) AlHA-LAP, LLC accredited service, Lab ID #102297

All samples were received in acceptable condition unless noted in the Report Comments portion in the body of the report. Due to the nature of the analyses performed, field blank correction of results is not applied. The results relate only to the items tested.

EMLab P&K ("the Company") shall have no liability to the client or the client's customer with respect to decisions or recommendations made, actions taken or courses of conduct implemented by either the client or the client's customer as a result of or based upon the Test Results. In no event shall the Company be liable to the client with respect to the Test Results except for the Company's own willful misconduct or gross negligence nor shall the Company be liable for incidental or consequential damages or lost profits or revenues to the fullest extent such liability may be disclaimed by law, even if the Company has been advised of the possibility of such damages, lost profits or lost revenues. In no event shall the Company's liability with respect to the Test Results exceed the amount paid to the Company by the client therefor.

Aerotech Laboratories, Inc

EMLab ID: 1795834, Page 1 of 2

Client: Pure Maintenance Contact: Mr Brandon Adams Project: Hammerhead 6 Months AT Date of Sampling: 09-12-2017 Date of Receipt: 09-18-2017 Date of Report: 09-19-2017

MoldREPORT

EMLab P & K 1501 West Knudsen Drive, Phoenix, AZ 85027 (800) 651-4860 Feb. (62) (800) 651-4802 Fax (623) 780-7695

# Laboratory Results

# MoldREPORT: Direct Microscopic Examination

Location:	5: Basement	6: Mens Bathroom	7: NW Classroom
Comments (see below):	None	None	None
Lab ID-Version‡:	8397833-1	8397834-1	8397835-1
Spore types present (indicative of mold growth)§:			
Aureobasidium	-	-	-
Basidiospores	-	-	-
Chaetomium	-	-	-
Cladosporium	-	-	-
Fusarium	-	-	-
Lumber mold†	-		-
Penicillium/Aspergillus types	-	-	-
Stachybotrys	-	-	-
Trichoderma	-	-	-
Ulocladium	-	-	-
Spore types present (not indicative of mold growth)§:			
All spore types	Very few	Very few	Few
Other particles detected§:			
Skin cells	Few	Very few	Few
Pollen	-	-	Very few
Background Debris and/or Description**:	Moderate	Moderate	Moderate

Comments: None

Basidiomycetes: Commonly found outdoors. Occasionally may grow indoors, mostly as agents of wood decay.

Cladosporium: One of the most commonly found molds outdoors and frequently found growing indoors.

Penicillium/Aspergillus types: Penicilium and Aspergillus are among the most common molds found growing both indoors and out.

Stachybotrys and other marker types: Certain types of mold, such as Aureobasidium. Chaetomium, Fusarium, Trichoderma, and Ulocladium, are generally found in very low numbers outdoors. Consequently their presence indoors, even in relatively low numbers, is often an indication that these molds are originating from growth indoors. When present, these mold types are often the clearest indicator of a mold problem.

<sup>†</sup>Lumber mold: Fungl in the Ceratocystis/Ophiostoma group are commonly called "Lumber mold". Lumber mold is present on the wood framing of most homes that are built with lumber. Their presence alone is not indicative of an indoor water problem.

"Background debris is an indication of the amounts of non-biological particulate matter present. This background material is graded and described as Scant. Moderate, Heavy, or Very Heavy, Levy heavy beckground debris may obscure visibility for the analyst. Some sample types are not graded for background debris. In which case a brief description of the material is reported.

‡ A "Version" indicated by ""," after the Lab ID# with a value greater than 1 indicates a sample with amended data. The revision number is reflected by the value of 'x".

The limit of detection is < 1+ when mold growth is detected.

\$All readers are advised to refer to the document "Understanding Direct Microscopic Examination Results" which is available at our website, www.moldreport.com, or by request from the laboratory.

# **Appendix B: Laboratory Analytical Reports**

Material Safety Data Sheet PM 2301
InstaPURE Cold Sterilant

Compilation date: 15 April 2009

#### 01. Identification of Product and Company

Product name:

Article numbers: 78397-982 / 78397-983 / 78398-229 / 78400-377

Application: Disinfection liquid REACH: 05-2117310704-54-0000

Company name:

Phone: Fax:

E-mail: info@puremaintenance.com

Home page:

Emergency Number: CHEMTREC +1-703-527-3887

#### 02. Hazards Identification

Component	EINECS	CAS	Amount w/w [%]	Symbol/ R-phrases
Hydrogen Peroxide	231-765-0	7722-84-1	20-24	O, C, R 22-41
Peracetic Acid	201-186-8	79-21-0	4-6	Xi, R 34
Acetic Acid	200-580-7	64-19-7	8-10	Xi. R 36/38

## 03. Composition/Information on Ingredients

The product is an Oxidizer and Corrosive that can cause burns. Direct contact could cause irreversible damage to eyes and skin tissue. Irritating to the respiratory system.

#### 04. First Aid Measures

#### General

If clothing is contaminated, remove clothing, and wash clothing before reusing.

#### Eyes and skin

Flush immediately with excess water for at least 15 minutes. If burn or irritation has occurred, seek medical attention.

#### Ingestion

Drink large amounts of water. Do not induce vomiting. Seek medical attention if necessary.

#### Inhalation

Move to fresh air and breathe deeply. Seek medical attention if necessary.

# 05. Fire Fighting Measures Extinguishing Media

Water spray / Foam / CO<sub>2</sub> / dry chemicals

# **Extinguishing Media to Avoid**

Direct water jet.

# Exposure Risks from Combustion Product / Gases

Danger of developing toxic Pyrolyse products.

# **Special Equipment for Fire-fighters**

Protect the respiratory ways. Use visors and gloves.

# **Additional Measures**

Cool risky containers with water spray. Damaged products and contaminated water shall be disposed according to local laws and requirements.

### 06. Accidental Release Measures

## **Personal Precautions**

Put on eye protection, protective gloves, boots, clothing and a respirator if air contamination is above the permitted levels. Arrange sufficient ventilation of air. People should move away from any vapors in the contaminated area.

#### **Environmental Precautions**

In case of accidental spillage, contain the spill and neutralize it with sodium bicarbonate or sodium carbonate.

# If allowed by local legislation:

Flush spill to the sewer. If mops, towels, paper towel or similar material is used, insure that these items are thoroughly rinsed with large amounts of water. Do not reuse the liquid material.

#### Material Safety Data Sheet InstaPURE Cold Sterilant

Compilation date: 15 April 2009

#### 07. Handling and Storage

#### Handling

Keep container closed by using a vented cap. Do not transfer product from original container and once the product has been removed, do not return to the original container. Exhaust required at point of use.

#### Fire- and Explosion

Degradation of this product produces oxygen; keep away from heating/ignition sources. Do not smoke.

#### Storage

Store in a cool dry area (below 24°C) away from heating sources. Heating will lead to pressure increase and danger of bursting the container. Floor needs a protective coating against acid.

#### **Combined Storage**

Do not store with flammable materials, metals, oxidizing or caustic materials.

#### 08. Exposure Controls/Personal Protection

#### **Technical Measures**

Assure sufficient air exhaust and supply of fresh air.

# Exposure limits at work place Component

#### Acetic Acid

MAK/TLV: 10ppm, MAK/TLV: 25 mg/m3,

F=1=(DFG, EU)

## Hydrogen Peroxide

MAK/TLV: 1ppm, MAK/TLV: 1,4 mg/m3,

F=1=(DFG)

MAK = maximum work place concentration, TLV = Threshold Limit Value,

F = Factor, Short Limit ∨alue

# Respiratory protection

If air contamination is above the permitted levels, use a mask for acid vapors, Combination filter B-P2.

#### Hand protection

Protective gloves. (e.g. nitrite, latex, neoprene) Refer to glove manufacturer specifications for compatibility.

#### Eye protection

Safety glasses or goggles. A face shield should be worn when splashes are likely.

### Skin protection

Protective apron should be worn when splashes are likely. Rubber boots should be used for spill

#### **General Measures**

Avoid contact with eyes and skin. Do not breathe gases / vapors / aerosols.

#### Hygienic Measures

Do not eat, drink, or smoke. Immediately remove contaminated clothing. Wash hands before breaks and at end of shift. Preventive hand care by hand crème.

#### Limitation and Monitoring of Environmental **Emission**

Not determined

# 09. Physical and Chemical Properties

Physical state: liquid Appearance: clear Odor: acid, pungent pH:  $0.8 \pm 0.3$ Boiling point [℃]: Not determined Flashing point [°C]: Not determined Ignition conditions: Not determined Lower explosion limit: Not determined Upper explosion limit: Not determined Fire fortifying:

Yes <110

Vapor pressure at 50℃ [kPA]: Vapor density [g/ml]: Not determined Specific gravity (H<sub>2</sub>O) [kg/l]: 1.090 - 1.140Solubility in water (by weight): complete Ratio n-Octanol / Water: Not determined Viscosity: Not determined

Relative vapour density

relative to air: Not determined **Evaporation rate:** Not determined Freezing point [°C]: Not determined Melting point [℃]: Not determined Self-reactivity: Not a self reactive substance

#### 10. Stability and Reactivity

### Materials to Avoid

Avoid heavy metals including iron, copper, copper alloys, brass and aluminium, salts, flammable organics, alkalis, caustics, chlorine and formaldehyde.

# Stability

Product is stable.

# **Conditions to Avoid**

Avoid direct sunlight, heat and hot storage (>24°C).

## **Hazardous Decomposition**

Oxygen & Heat. Do not mix with chlorinated products as this could liberate toxic corrosive chlorine gas

#### Material Safety Data Sheet InstaPURE Cold Sterilant

#### **Hazardous Polymerisation**

Will not occur

#### 11. Toxicological Information

#### **Effects from Eye Contact**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, significantly impaired vision or potentially a complete loss of vision.

#### **Effects from Skin Contact**

Corrosive (Skin Burns): Signs/symptoms may include turning the skin chalky white, swelling, itching, intense pain, blistering, and potential tissue destruction.

#### Effects from Inhalation

Upper Respiratory Tract Irritation: Signs/ symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Effects from Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

#### 12. Environmental Information

This product has been tested and determined to be toxic to fish and aquatic invertebrates:

- Daphnia Magna / Water Flea: LC50 2.61 mg ai/L
- Rainbow Trout: LC50 6.68 mg ai/L
- · Bluegill: LC50 4.25 mg ai/L

# 13. Disposal Considerations

# **Product Disposal**

Dispose of this product in accordance with all applicable European and Local regulations

# Disposal of Bottle and Packaging

Bottles and packaging can be disposed according European and Local regulations. Bottles should be thoroughly rinsed before disposal

#### 14. Transportation Information

14.1 Classification according to ADR

ADR class:

Proper Shipping Name: UN3149 Hydrogen Peroxide and Peracetic

Acid Mixture, Stabilized

5.1 (8) II UN 3149

UN number: Factor, ADR 1.1.3.6:

Transpon Emergency

Card: 58 Labeling: 5.1 & 8 LQ, ADR 3.4.6: Vapor pressure [kPa]: <110, [50°C]

14.2 Classification according to IMDG IMDG-Code Number: 5.1

Proper Shipping Name: Hydrogen Peroxide and

Peracetic Acid Mixture Stabilized 5.1 8 UN 3149 II Hydrogen Peroxide and

Classification: Peracetic Acid Mixture, Stabilized UN 3149

5.1-02 EmS: Labeling: LQ, ADR [l/kg] 5.1 & 8 0.5

14.3 Classification according to IATA Forbidden for transported by air.

# 15. Regulatory Information

The product is classified and marked according to EC-Guidelines

In accordance with Directives 67/548/EEC and 1999/45/EC this product is classified as corrosive and oxidising,

#### Risk Phrases

R 22: Harmful if swallowed.

R 34: Causes burns.

R 36/38: Irritating to eyes and skin.

R 41: Risk of serious damage to eyes.

# Material Safety Data Sheet InstaPURE Cold Sterilant

Compilation date: 15 April 2009

#### Safety Phrases

S 3/7: Keep container tightly closed in a cool place. Only use vented caps. S 14: Keep away from identified in Section 7:

Handling and Storage.

S 23: Do not breathe gas/fumes/vapour/spray. S 26: In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice.

S 28: After contact with skin immediately flush affect area with copious amounts of water.

S 36/37/39: Wear suitable protective clothing, gloves and eye/face protection

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S 61: Avoid release to the environment. Refer to Section 13: *Disposal Considerations*.

#### **National Legislation**

Follow all relevant national laws or other national relevant measures

#### 16. Other information

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge. This information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated in this document and may not be valid if the product is used in combination with any other materials or processes, unless specified in the text.

# Guidelines

- 2001/58/EC
- 67/548/EEC
- 1999/45/EC
- 91/689/EEC
- 1907/2006/EC
- ADR (2003)
- IMDG-Codé (30. Amdt.)
- IATA-DGR (2003)

# **EverPURE**

# MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION:				
MANUFACTURER Put	reShield Inc.			
info	@puremaintenar	ice.com		
	C p an amount			
EMERGENCY PHONE NUMBERInfo PRODUCT NAME	Trac 800-535-505	3 (day/night)		
CHEMICAL FAMILYOrg	anosilane			
EPA Registration #875				
Last Revision Date7/8/				
II. PHYSICAL DATA				
BOILING POINT>210°F		ITY (WATER)		
VAPOR PRESSURE N/A	ODOR		Mild	
VAPOR DENSITY N/A		ANCE		
% VOLATILES ND		ATION RATE		
pH of PRODUCT approx 5.0	SPECIFIC	C GRAVITY	1.003	
III. CHEMICAL COMPONENTS				
COMPONENT	C.A.S.#	HAZARD	from% - to%	T.L.V.
(1) 3-(Trimethoxysilyl)	27668-52-6	Irritant	5.00 %	None
propyldimethyloctadecyl ammonium				
IV. FIRE AND EXPLOSION DATA				
FLASH POINT ('F)N/A				
	I/A	(lower) N/	/A	
EXTINGUISHING MEDIA Dry chemica				
SPECIAL FIRE-FIGHTING PROCEDUR	ES Must be equi	ipped with self con	tained breathing app	
UNUSUAL FIRE AND EXPLOSION HAZ		drums with water s	spray to prevent burs	sting.
ONO CONET INTE AND EXITED CONTINUE	ANDO NOTIC			
V. HEALTH HAZARD DATA				
Harmful if swallowed, inhaled or absorbe	ed through the skin.			
TLV NO ACGIH TLV PUBLISH		NO OSHA PEL	PUBLISHED	
EYES Prolonged contact may ca				
SKIN Prolonged contact may ca	use irritation.			
INHALATION Harmful if inhaled.				
INGESTION Harmful if swallowed.				
EFFECTS OF OVEREXPOSURENot I	known			
*********				
EYES: Flush with plenty of water for at I	east 15 minutes. I	f irritation persists,	get medical attention	n.
SKIN: Remove clothing if necessary, rin	se skin, if irritation	persists get medic	al attention.	

INHALATION: Remove to fresh air. If not breathing, Call 911 and then give artificial respiration.

INGESTION: Do not induce vomiting. Call a poison control center or doctor immediately for treatment advice. Have the person sip a glass of water if able to swallow. Do not give anything to an unconscious person.

In all cases call Poison Control Center or Doctor for treatment advice.

VI. REACTIVITY DATA STABILITY
INCOMPATIBILITY Sodium oxidizers
HAZARDOUS DECOMPOSITION PRODUCTS: HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID:
VII. SPILL OR LEAK PROCEDURES  X STOP FLOW X AVOID SKIN CONTACT BURY IN REMOTE AREA NEUTRALIZE ELIMINATE ALL SOURCES X OBSERVE FEDERAL X ABSORB OR SCRAPE OF IGNITION OR FLAME SPILL & WATER UP MATERIAL WASH AWAY WITH WATER QUALITY REGULATIONS X AVOID INHALATION VACUUM UP USE AS LANDFILL
DISPOSAL CONSIDERATION  Product/Soil/Water maybe subject to RCRA/OSHA hazardous waste. Landfill solids at permitted sites. Follow all federal, state and local waste management regulations Where permissible, consider discharge to TW, biological treatment, or incineration.  To inactivate product, add anionic surface or detergent in equal amount to the product.
VIII. SPECIAL PROTECTION INFORMATION  RESPIRATORY
IX. SPECIAL PRECAUTION  No special precautions beyond routine prudent safe handling of chemical substances are necessary.
X. REGULATORY INFORMATION  DOT SHIPPING NAME

# XI. MISCELLANEOUS

# COMPANY CONTACT: Dan Hill

This Material Safety Data Sheet has been prepared in compliance with the 29CFR 1910.1200. The information contained herein is prepared by qualified personnel at Hill Chemical and we believe that the information contained is accurate and current as of the date of preparation; however, no warranty, expressed or implied is given regarding the accuracy of the data or the results to be obtained from the use thereof. Since the use of this information and the conditions of use of this product are beyond our control, Hill Chemical, assumes no liability for injuries or damages associated with the use or the product described herein. It is the user's responsibility to ensure that his activities comply with applicable federal, state or provincial, and local laws.

# REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)	2. REPORT TYPE	3. DATES COVERED (From - To)
08/20/2018	Final	
4. TITLE AND SUBTITLE		5a. CONTRACT NUMBER
Performance Testing of a Novel Dry-Fog Mol	d Remediation and Prevention Process	
		5b. GRANT NUMBER
		5c. PROGRAM ELEMENT
6. AUTHOR(S)		5d. PROJECT NUMBER
Shane D. Hirschi and Dale L. Herron		ITTP
		5e. TASK NUMBER
		5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(\$\foatsu.S.\ Army Engineer Research and Developm Construction Engineering Research Laborato PO Box 9005, Champaign, IL 61826-9005	ent Center (ERDC)	8. PERFORMING ORGANIZATION REPORT NUMBER ERDC/CERL TR-18-17
9. SPONSORING / MONITORING AGENCY	NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
Assistant Chief of Staff for Installation Mana 600 Army Pentagon	ACSIM	
Washington, DC 20310-0600	11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
40 DIOTRIBUTION / AVAIL ABILITY OT AT		

#### 12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

# 13. SUPPLEMENTARY NOTES

#### 14. ABSTRACT

Mold is an ongoing problem for Army installations and contingency basing locations. This work was undertaken to demonstrate the effectiveness of a two-step dry-fog mold remediation process technology to remove mold spores and provide long-term mold prevention in two buildings at Fort Campbell, KY. Treating each test building took 5 to 6 hours and included: mobilization, air and surface sampling before and after the application, and demobilization. This work concluded that the dry-fog technology provides rapid and quantifiable improvements to indoor air quality, and reduces exposure of personnel to harmful chemicals resulting from current mold remediation practices. Results indicated that the dry-fog technology could potentially support mold remediation needs resulting from indoor air quality maintenance and from natural hazards. Current rough estimates for application of the dry-fog technology are approximately \$1.00/sq ft. Early project results were shared with Region IV of the Federal Emergency Management Agency (FEMA) and the Huntington District of the U.S. Army's Corps of Engineers.

### 15. SUBJECT TERMS

Molds (Fungi)-Control, Indoor air quality, Indoor air pollution-Research, Military bases, Buildings

16. SECURITY CLAS	SIFICATION OF:		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified	SAR	89	19b. TELEPHONE NUMBER (include area code)