



proline

decorative concrete systems

Accent Color

Translucent Stain



Also available in AC-700 Black and AC-800 White

Proline Accent color is a water-based acrylic stain that is specially formulated to accent any decorative concrete surface. Accent color is quickly and easily applied to decorative concrete flatwork, vertical surfaces and rockscapes for accent colors and natural-looking variations. There are 18 standard Accent colors, but any of the 18 colors can be mixed together for customized results.

The colors shown are approximate, and as close as possible, to represent concrete with flat trowel finish and sealed with Dura Seal HG Sealer. Proline is not responsible for application methods, finishing techniques, job site conditions, curing methods, and other conditions and therefore cannot guarantee an exact match. Various texturing and finishing techniques such as troweling or brooming, the use of sealers, and color variations in raw materials can produce variations in colors. Proline highly recommends a representative job sample be done for each product.



Accent Color Translucent Stain

- A translucent, water-based acrylic stain
- Designed for accenting any decorative concrete surface
- Quickly and easily applied with a variety of techniques
- 18 standard colors available with custom colors possible

DESCRIPTION:

Proline Accent Color Translucent Stain is a water-based acrylic stain that is specially formulated to accent any decorative concrete surface. It is a translucent stain that is designed to blend with the base color over which it is applied. Accent Color is quickly and easily applied to decorative concrete flatwork, vertical surfaces and rockscapes for accent colors and natural-looking variations. There are 18 standard Accent Colors available, which can be mixed together for customized, varying results.

STORAGE:

Store in a cool, dry place, in temperatures below 120°F. Shelf life is approximately 2 years, but will last much longer if containers are kept tightly sealed.

COVERAGE:

Coverage rate is impossible to predict. 1 gallon should cover at least 600 square feet, under the assumption that you should be accenting no more than 25-30% of any given project. If you are looking for opaque coverage this is not the correct product. In that case we would recommend Pro-Stain.

APPLICATION:

For professional use only. A hard troweled surface must be etched prior to application. We suggest Dura-Etch and/or Dura-Clean be used to achieve the proper surface condition. Proline Accent Color Water-Based Acrylic Stain comes in a 1 gallon jug that must be shaken thoroughly before use and periodically during use. Accent Color is a concrete stain that is designed to be translucent, blending with or accenting the base color while allowing that base to show through. **Do not over-apply Accent Color by layering multiple coats, over application will result in product failure. This product is not designed to be completely opaque.** For full opaque coverage we recommend Pro-Stain solid color stain.

For large areas, the best results are achieved by spraying through an HVLP Sprayer (High Volume Low Pressure) or a Pump Sprayer. For smaller accent areas, a standard trigger sprayer is ideal. Sprayers whose tips can be adjusted from fine mist to stream will give the best results. Proline Accent Color can also be applied with a variety of faux finish techniques including rolling, brushing, sponging, and ragging. Water can be sprayed on during the application to blend different colors and soften hard edges. This product can be cleaned up easily with water while it is still wet, but removal of dried product must be accomplished with a stripper.

For best results, seal over Accent Color with one of our Proline DuraSeal products.

WARRANTY:

This product is warranted to be of uniform quality within reasonable manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

WARNING:

Before using this product, the end user should completely read the Proline TECHNICAL DATA SHEET and SDS. KEEP OUT OF REACH OF CHILDREN!

SAFE HANDLING INSTRUCTIONS:

DO NOT TAKE INTERNALLY. Avoid contact with eyes and skin. Close container after each use. Wear rubber gloves and aprons to protect skin and wear safety eye goggles. Use good hygiene when handling this product and wash and bathe after each use.