



# HP-88

## LOW PH TOUCHLESS PRESOAK

### HIGH TDS WATER

#### DESCRIPTION

A low-foaming, acid-based presoak with a mixture of high acid and low surfactant levels, which helps to penetrate and remove dirt, oil, grease, bug residue, and road film from the vehicle surfaces when cleaning in high TDS water conditions.

#### FEATURES

- Unscented
- High TDS Water
- Medium foaming formula
- Versatile presoak for slightly stubborn environments
- ECOLOGO™ Certified

#### APPLICATION

- Touchless
- APPROXIMATE USAGE: 15-30 ML/ APPLICATION\*
- Use proportioner tips (i.e. HydroMinder, Dema, etc.) in conjunction with downstream injection (i.e. Dema, venturi, etc.) to achieve final use dilution
- Use this presoak to prep and clean the vehicle surface before applying an alkali-based presoak. Combining these products helps to overcome poor cleaning conditions.

#### PACKAGING

5, 30 & 55 USG / 18.9, 114 & 208L

#### SPECIFICATIONS

**Hyper-Concentrated**

**Appearance:** Clear yellow, thin liquid

**Foam Color:** None

**pH:** <1.5

**SG:** 1.08

**DOT Labeling:** UN 3264, CLASS 8, PG III

**\*Approximate Number of Washes per 5 USG container:** 631-1262

#### TITRATION

Amount: 5ml

Reagent: 0.2N NaOH

Dilution - Drops

80:1 -	21
100:1 -	15
120:1 -	14
140:1 -	10
160:1 -	9
180:1 -	9
200:1 -	9
220:1 -	7
240:1 -	6

**REFER TO SAFETY DATA SHEET FOR EMERGENCY MEDICAL INFORMATION**