

Cutting and Mowing Equipment



Rotary Cutters

If you need a rugged, mid-priced rotary cutter that can handle heavy grass, thick brush, and weeds, a Frontier Rotary Cutter is worth a closer look.

- Four efficient models feature 4 to 7 ft. (121.9 to 213.4 cm) cutting widths
- iMatch compatible on RC2048, RC2060, and RC2072 only
- Category 2 Quick Hitch compatible on RC2084 only

Model	Working Width	PTO HP	Hitch
RC2048	48 in. (121.9 cm)	18 - 45 hp (13.4 - 33.6 kW)	Cat. 1 & adaptable to Cat. 2
RC2060	60 in. (152.4 cm)	19 - 65 hp (14.2 - 48.5 kW)	Cat. 1 & adaptable to Cat. 2
RC2072	72 in. (182.9 cm)	25 - 65 hp (18.6 - 48.5 kW)	Cat. 1 & adaptable to Cat. 2
RC2084	84 in. (213.4 cm)	45 - 90 hp (33.6 - 67.1 kW)	Category 2



Flex-Wing Grooming Mowers

Go with the Flex-Wing Grooming Mowers for a quality cut over uneven fields. Features wider working widths to make quick work at sod farms, golf courses, and parks.

- 12 to 20 ft. (3.7 to 6.1 m) cutting widths
- 8-gauge steel plate deck (10-gauge on FM3012)
- Auto-engage transport latch

Model	Working Width	PTO HP	Hitch
FM1012	12 ft. (3.7 m)	30 - 80 hp (22.4 - 59.7 kW)	Pull-Type
FM2012R	12 ft. (3.7 m)	25 - 80 hp (18.6 - 59.7 kW)	Pull-Type
FM2112R	12 ft. (3.7 m)	35 - 80 hp (26.1 - 59.7 kW)	Pull-Type
FM3012	12 ft. 6 in. (3.8 m)	25 - 60 hp (18.6 - 44.7 kW)	Pull-Type
FM1015	15 ft. (4.6 m)	35 - 80 hp (26.1 - 59.7 kW)	Pull-Type
FM2015R	15 ft. (4.6 m)	30 - 80 hp (22.4 - 59.7 kW)	Pull-Type
FM2115R	15 ft. (4.6 m)	35 - 80 hp (26.1 - 59.7 kW)	Pull-Type
FM1017	17 ft. (5.2 m)	40 - 80 hp (29.8 - 59.7 kW)	Pull-Type
FM2017R	17 ft. (5.2 m)	35 - 80 hp (26.1 - 59.7 kW)	Pull-Type
FM2117R	17 ft. (5.2 m)	35 - 80 hp (26.1 - 59.7 kW)	Pull-Type
FM2120R	20 ft. (6.1 m)	50 - 80 hp (37.3 - 59.7 kW)	Pull-Type



Grooming Mowers

The Grooming Mower delivers a smooth cut for lawns, sporting fields, and golf courses.

- 4 to 9 ft. (121.9 to about 279.4 cm) cutting widths
- Single- or dual-belt drive
- High blade speed for thorough cutting and uniform distribution
- Category 1 iMatch compatible with optional kit
- Rear discharge

Model	Working Width	PTO HP	Hitch
GM1048E	48 in. (121.9 cm)	16 - 30 hp (11.9 - 22.4 kW)	Category 1
GM1060E	60 in. (152.4 cm)	20 - 30 hp (14.9 - 22.4 kW)	Category 1
GM1072E	72 in. (182.9 cm)	25 - 30 hp (18.6 - 22.4 kW)	Category 1
GM1060	60 in. (152.4 cm)	15 - 40 hp (11.2 - 29.8 kW)	Category 1
GM2060R	60 in. (152.4 cm)	20 - 50 hp (14.9 - 37.3 kW)	Category 1
GM1072	72 in. (182.9 cm)	20 - 40 hp (14.9 - 29.8 kW)	Category 1
GM2072R	72 in. (182.9 cm)	20 - 50 hp (14.9 - 37.3 kW)	Category 1
GM1084	84 in. (213.4 cm)	25 - 40 hp (18.6 - 29.8 kW)	Category 1
GM2084R	84 in. (213.4 cm)	20 - 50 hp (14.9 - 37.3 kW)	Category 1
GM1190	90 in. (228.6 cm)	45 - 75 hp (33.6 - 56 kW)	Category 1 and 2
GM2190R	90 in. (228.6 cm)	45 - 75 hp (33.6 - 55.6 kW)	Category 1
GM2109R	110 in. (279.4 cm)	40 - 70 hp (29.8 - 52.2 kW)	Category 1
GM3054	54 in. (137.2 cm)	15 - 25 hp (11.2 - 18.6 kW)	Limited Category 1
GM3060	60 in. (152.4 cm)	15-35 hp (11.2 - 26.1 kW)	Category 1
GM3072	72 in. (182.9 cm)	20-35 hp (14.9 - 26.1 kW)	Category 1



How to Mow Along A Roadside Fence

So that's how you do it.

TipsNotebook.com