

220 LOW VOC TRANSITION CEMENT MEDIUM BODY/GREEN

General Description:

E-Z Weld Transition Cement is a medium bodied, fast set PVC Solvent Cement. This cement is formulated for use on non-pressure transition joints between ABS and PVC/uPVC pipes and fittings.

Application:

Green, Medium Body, ABS to PVC / uPVC cement for use on non-pressure transition joints with interference fit through 6" (160 mm) diameter. Cement recommended sewer, conduit and DWV. Never add thinner or additive. Never use the cement if it is stringy or jelly like.

Always follow instructions on the label.

Application temperature: 32°F to 110°F (0°C to 43°C).

Storage temperature: 45°F to 110°F (7°C to 43°C).

ASTM has developed the following schedule and may be used as a guide (for relative humidity 60% or less. Sch. 40 size pipe.) eg. a 2" pipe size joint made at 55°F, 50% Relative Humidity and a test pressure of 100 psi would require a cure time of 4 hrs.

Certification:

This product is tested, certified and approved by NSF International for use on drain, waste and potable water systems. It is also listed by the International Association of Plumbing & Mechanical Officials (IAPMO). It carries the Uniform Plumbing Code (UPC) seal. This cement meets ASTM Standard D3138.



PW, DWV, SW

Quality Assurance:

Every batch of cement is carefully checked and monitored to assure Every batch of cement is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. All ingredients are purchased from approved suppliers. This cement has passed the following test (performed in accordance with ASTM Std. D3138.)

Lap Shear:

- 600 psi (4.1 Mpa) after 72-hour cure time at 73°F (23°C)

Hydrostatic Burst:

- 200 psi (1.4 Mpa) after 72-hour cure time at 73°F (23°C)



Physical Properties:

Color: Green

Body: Medium Bodied

Set: Fast

Specific Gravity: 0.960

Shelf Life: 3 years (unopened can)

LOW VOC (VOLITILE ORGANIC COMPOUND)

Maximum VOC per SCAQMD 1168/316A: 510 g/l

Availability:

Size	Part No. Regular	(UPC No.)
1/4pt	EZ22101	812574014136
1/2pt	EZ22002	812574014143
Pt	EZ22003	812574010985
Qt	EZ22004	812574011012
Gal	EZ22005	812574014150

Pt. And Qt. cans are supplied with dauber inside cap. Gallon sizes supplied with plain cap only.



220 LOW VOC TRANSITION CEMENT MEDIUM BODY/GREEN

Packaging:

Size	¼ Pt	½ Pt	Pt	Qt	Gal
Fluid oz	4	8	16	32	128
Liters	0.12	0.24	0.47	0.95	3.78
Units per case	24	24	12	12	6
Weight per case - Lb.	9.5	16	15.5	28	54
Weight per case - Kg	4.32	7.27	7.05	12.73	24.55
Cubic feet per case	0.260	0.420	0.404	0.762	1.221
Cubic meter per case	0.007	0.012	0.011	0.022	0.035
Cases per pallet	145	90	88	56	27

Safety Precautions:

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headaches or eye watering. If symptoms are experienced use respiratory protection (NOISH/MSHA TC-23C or equivalent) or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing by use of safety glasses and gloves. Professionals should consult ASTM Standard F402-18 Standard Practice for Safe Handling of Solvent Cements, Primers, and Cleaners Used for Joining Thermoplastic Pipe and Fittings. Professional users should also read the Safety Data Sheet for the product.

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention.

Internal: If swallowed give 1 or 2 glasses of water immediately, call physician, hospital or poison control immediately.
DO NOT INDUCE VOMITING.

Shipping / Transportation:

Material packaged in less than a liter size is exempted under "Limited Quantity Rules" by DOT. These packages may be shipped with the description ORM - D Consumer Commodity. Packages shipped under this description are not subject to shipping paper requirements for flammable materials.

For a liter and larger sizes (gallon and above container):

Proper Shipping Name: Adhesive

Flammable Class: 3

UN No: UN 1133

Packing Group: PG II

REV/12/18